

Name of work :- BLP 2025-26 Providing Road Furniture in Various Roads Of Choryasi Taluka (2 Roads)

:: BILL OF QUANTITY ::

Sr. No.	Item of work	Estimated Quantity but may be more or less	Unit	Rate	Total amount according to estimated quantities.
1	3	2	6	4	7
1	Village name :-Providing and fixing sing boards made out of 2mm aluminium sheet; size 90 x 60cms. rectangle as as per the design of IRC-67-1977 pre treated with phospheting process & acid etching; coated with one coat of epoxy primer and two coats of best quality epoxy paint; reflectorised with retro reflective sheeting as per latest M.O.S.T. Specifications; Letters and numerals should be as per IRC-30-1968, 3.1m long (2 nos) stand post and frame fabricated from suitable size iron angle of 50 x 50 x 5mm painted with best quality epoxy coatings in black and white bends. the details of symbol or inscription / numerals for each board shall be as per the instruction of engineer in charge. The fixing at site shall be in 1:2:4 CC block of size 45 x 45 x 60cms. for each leg. including excavation curing etc. complete under the supervision of engineer in charge.(A) Engineer Grade(VR)...	3.00	Nos	5045.36	15136.08
2	Cautionary Warning Sign :-Providing and fixing sing boards made out of 2mm aluminium sheet; size 90 x 90 x 90 cms. equilateral triangle as per design of IRC-67-1977. Pre treated with phospheting process & acid etching; coated with one coat of epoxy primer and two coats of best quality epoxy paint ;reflectorised with retro reflectivesheeting as per latest M.O.S.T.Specifications; 3.1m long stand postand frame fabricated from suitable sizeiron angle of 35 x 35 x 3mm, 75 x 75 x 6mm as required; painted with bestquality epoxy coatings in black andwhite bends. The details of symbol foreach board shall be as per theinstruction of engineer in charge. The fixing at site shall be in 1:2:4 CC blockof size 45 x 45 x 60 Cms. for each leg.including excavation, curing etc.complete under the supervision of engineer in charge.(A) Engineer Grade(VR)	36.00	Nos	3808.66	137111.76
3	Road marking with hot applied thermoplastic paints with reflectorising glass beads on bitumin surface providing and laying a hot applied thermoplastic compound 2.5 mm thick including reflectorising glass beads @ 250gms per sqm area, thickness of 2.5mm is excluding of surface applied glass beds as per IRC:35-2015. The finished surface to be level, uniform and free from streaks and holes. zebra patta /bump patta lane/center line/ edge line/cut patta. The white color marking should provide liminance coefficin et on cemend road shalll be min 130 mcd/m2/lux and Asphalt road shall be min 100 mcd/m2/lux during the service life during the day time. The marking should meet the performance criteria for night time reflectivity, wet reflectivity and skid resistance as mentioned in the section-15 of IRC 35-2015.	1365.00	Sqm	367.72	501937.80

1	3	2	6	4	7
4	<p>Cat Eye / Road Stud / RPM: Supplying of Molded Twin Shanks Raised Pavement Markers made of polycarbonate and ABS moulded body and reflective panels with micro prismatic lens capable of providing total internal reflection of the light entering the lens face and shall support a load of 13635 kgs. tested in accordance to ASTM D 4280 Type H and complying to Specifications of Category A of MORTH Circular No RW/NH/33023/10-97 DO III Dt 11.06. 1997. The height, width and length shall not exceed 20 mm, 130 mm and 130 mm and with minimum reflective area of 13 Sqcm on each side and the slope to the base shall be 35 +/- 5 degree. The strength of detachment of the integrated cylindrical shanks, (of diameter not less than 19 +/- 2 mm and height not less than 30+/- 2 mm) from the body is to be a minimum value of 500 Kgf. Fixing will be by drilling holes on the road for the shanks to go inside, without nails and using epoxy resin based adhesive as per manufacturers recommendation and The color of the marker should be as per the IRC 35-2015 and as directed by Engineer-in-charge.</p>	1270.00	Nos	326.23	414312.10
5	<p>Regulatory / Mandatory Sign :-Providing and fixing sign boards made out of 2mm aluminium sheet / 4mm ACP (Aluminum composite Panel); size 60 cms. Dia Circle as per design of IRC-67-2012. Pre treated with phosphating process & acid etching; coated with one coat of epoxy primer and two coats of best quality epoxy paint ; reflectorised with High Intensity Prismatic Grade retro reflectivesheeting of Type-4 as per ASTM D-4956 and latest M.O.S.T.Specifications; 3.6mtr long stand post of Iron Angle 75 x 75 x 6mm / 65NB Circular MS Pipe as required and frame fabricated from suitable size iron angle of 35 x 35 x 3mm; painted with bestquality epoxy coatings in black and white bends. The details of symbol for each board shall be as per the instruction of engineer in charge. The fixing at site shall be in 1:2:4 CC blockof size 45 x 45 x 60 Cms. for each leg including excavation, curing etc.complete under the supervision of engineer in charge. A warranty for 7 years for the Retro reflective sheeting from original manufacturer & a certified copy of 3 year outdoor exposure test report from third party test lab for the product offered shall be submitted by contractor. (B) Class-B Type-4 Retro Reflective sheeting.</p>	4.00	Nos	3540.12	14160.48
6	<p>Hazard Marker Sign :-Providing and fixing sing boards made out of 2mm aluminium sheet; size 90 x 30cms. rectangle as as per the design/drawing attached (IRC) pretreated with phosphating process & acid etching; coated with one coat of epoxy primer and two coats of best quality epoxy paint; reflectorised with retro reflective sheeting as per latest M.O.S.T. Specifications; 3.1m long stand post and frame fabricated from suitable size iron angle of 35 x 35 x 3mm & 50 x 50 x 5mm painted with best quality epoxy coatings The fixing at site shall be in 1:2:4 CC block of size 45x45x 60cms. for each leg. including excavation curing etc. complete under the supervision of engineer in charge.(A) Engineer Grade(VR)...</p>	7.00	Nos	2423.74	16966.18

1	3	2	6	4	7
7	Chevron sign :-Providing and fixing sign boards made out of 1.5mm aluminium sheet / 3mm ACP (Aluminum composite Panel); size 60x50cm rectangular as per design of IRC-67-2012. Pre treated with phospheting process & acid etching; coated with one coat of epoxy primer and two coats of best quality epoxy paint ; reflectorised with High Intensity Prismatic Grade retro reflectivesheeting of Type-4 as per ASTM D-4956 and latest M.O.S.T.Specifications; 3.3 mtr long stand post of Iron Angle 75 x 75 x 6mm / 65NB Circular MS Pipe as required and frame fabricated from suitable size iron angle of 35x35x3mm; painted with bestquality epoxy coatings in black and white bends. the details of symbol or inscription / numerals for each board shall be as per the instruction of engineer in charge. The fixing at site shall be in 1:2:4 CC block of size 45 x 45 x 60 Cms. for each leg including excavation, curing etc.complete under the supervision of engineer in charge. A warranty for 7 years for the Retro reflective sheeting from original manufacturer & a certified copy of 3 year outdoor exposure test report from third party test lab for the product offered shall be submitted by contractor. (A) Class-B Type-4 Retro Reflective sheeting	24.00	Nos	3711.75	89082.00
					1188706.40
					1188706.40

I/We am/are willing to carry out the work at% above/below (percent should be written in figures and words) of the estimated rates mentioned above. Amount of my/our tender works out as under.

*Estimated amount

Put to tender 1188706.40
Deduct % below Rs.....
Net Rs.
In words

*(please strike out whichever is not applicable)

*Estimated amount

Put to tender
... % Above Rs.....
Rs.

Note :- All works shall be carried out as public works department Handbook and other specification of Division or as directed.

નોંધ બધુ જ કામ બાંધકામ વિભાગની પુસ્તિકા અને ડીવીઝનની બી ખાસ વિગત મુજબ અથવા સુચના પ્રમાણે કરી આપવાનું રહેશે.

:- ૧

Note :- All the columns in schedule should be filled in ink or ballpen and the total of the entries in last column should be struck by the contractor under his signature.

નોંધ અનસૂચિમાં બધા ખાનાની વિગતો શાહીથી ભરવી અને છેલ્લા ખાનાની નોંધનો સરવાળો કરી કોન્ટ્રાક્ટરે પોતાની સહી કરવી.

:- ૨

Note :- Rate quoted include clearance of site (Prior commencement of work and at its close) in all respects and hold good for work under all conditions,site moisture, weather etc.

નોંધ ટાંકેલા દરમાં,સ્થળની (કામનાં આરંભે અને પુરૂ થાય તે વખતે) દરેક રીતે સાફ સુકી કરવાનું સમાવેશ થાય છે અને તે દર તમામ પરિસ્થિતી , સ્થળ ,ભેજ , હવામાન વિગેરે હેઠળ કામ માટે અમલમાં રહેશે.

:- ૩

Note :- To be continued on additional sheet,if found necessary.

નોંધ જરૂર જણાય વધારાના કાગળો જોડી ચાલુ રાખવું

:- ૪

Signature of the contractor

Executive Engineer
Panchayat (R & B) Division
Surat