

**AHMEDABAD MUNICIPAL CORPORATION**  
**SOUTH WEST ZONE**



Tender Notice No : 05/2026-27

Tender No : 29

**Road Grouting work in different TP Roads and Breakdown site in  
jodhpur ward, South west zone AMC.(Reinvite)**

Download Tender Document	:	From website on <a href="http://nprocure.com">http://nprocure.com</a> and <a href="http://amc.nprocure.com.in">http://amc.nprocure.com.in</a>
Last Date of online Tender Submission	:	<b>Dt. 29.06.2026 up to 18:00 Hrs.</b>
Last Date of submission of blank tender Document, EMD & Tender Fee and Other Documents	:	<b>Dt. 30.06.2026 up to 16:00 Hrs.</b> by Speed post AD, courier or Hand delivery.
Date of Tender Opening	:	<b>Dt. 30.06.2026 at 17:00 Hrs.</b>

**Dy. Municipal Commissioner**  
Ahmedabad Municipal Corporation.  
South Zone West Zonal Office, Late Shri Tushar bhavan, Near Shelby Hospital, Jodhpur,  
AHMEDABAD

## AHMEDABAD MUNICIPAL CORPORATION

### Invitation for Bid (IFB)

1. The AHMEDABAD MUNICIPAL CORPORATION, (Hereinafter called "the Employer") invites sealed Tender document from reputed and qualified bidders for the construction of Works detailed in the Table below:-

Sr. No.	Name of Works	Approximate value of works (Rs.)	Bid Security (Rs.)	Completion Period
1	Road Grouting work in different TP Roads and Breakdown site in jodhpur ward, South west zone AMC.(Reinvite)	Rs. 9,98,562.00 Class E2 or Above	Rs.9986.00	12 months(Excluding Monsoon)

2. Tender (a complete set of bidding document) fee shall be Rs. 900/- in the form of Demand Draft / Pay Order from any Nationalized Bank in favor of MUNICIPAL COMMISSIONER, Ahmedabad, payable at Ahmedabad, which shall be non refundable. The fees shall be paid at the time of submitting the tender.
3. Interested bidders shall download the tender documents from website up to Dt.29.06.2026 at 18:00 Hrs tender fee as mentioned in clause 2 above shall be paid by the bidder at the time of bid submission.
4. All bids must be accompanied by Bid Security of the amount specified for the Works in the above Table payable at Ahmedabad and drawn in favor of AHMEDABAD MUNICIPAL CORPORATION, Ahmedabad. Bid Security will have to be in any one of the forms as specified in Clause of ITB (Instructions to Bidders).
5. All Bids must be delivered to Assistant Manager "South West Zone, Zonal Office", Late Shri Tushar bhavan, Near Shelby Hospital, Jodhpur, Ahmedabad-380015 Not later than 16:00 hrs on Dt.30.06.2026

Contractor's Signature  
& Stamp

Addl. City Engineer  
(South West Zone)

Mobile No

Department name	Engineering Department
<b>Circle/Division</b>	South west Zone
IFB No/Tender Notice No.	05/2026-27
Name of Work	<b>Road Grouting work in different TP Roads and Breakdown site in jodhpur ward, South west zone AMC.(Reinvite)</b>
Estimate contract value(INR)	<b>Rs. 9,98,562.00</b>
Period of Completion	<b>12 months(Excluding Monsoon)</b>
Bidding Type	pen/Limited
Bid Call(Nos)	1
Tender Currency Type	-----
Tender Currency Settings	-----
Joint venture	Applicable/Not Applicable
Rebate	Applicable/Not Applicable

Amount Details:	
Bid Document Fee:	<b>Rs.900.00</b>
Bid Document Fee Payable to:	Municipal Commissioner, Ahmedabad
Bid Security/ EMD (INR)	<b>Rs.9985.00</b>
Bid Security/ EMD In Favor of	Municipal Commissioner, Ahmedabad

Tender Dates

Bid Document Downloading Start Dates	<b>Dt. 29.06.2026 upto 18:00 Hrs.</b>
Pre Bid Meeting	N/A
Last Date & Time for Receipt of Bids	<b>Dt. 30.06.2026 upto 16:00 hrs</b> (including addendum if any)
Bid Validity Period	<b>120 Days</b>
Remaks	Submission of EMD Tender fee and Other Documents during office hours : <b>On date 30.06.2026 &amp; 16:00 hrs in</b> the Office of Assistant Manager (South West Zone Office, Late Shri Tushar bhavan, Near Shelby Hospital, Jodhpur, Ahmedabad-380015
Bid Opening Date	<b>Dt.30.06.2026 at 17:00 hrs</b>
Other Details	
Officer Inviting Bids:	Assistant Manager(South West Zone)
Bid Opening Authority:	Assistant Manager(South West Zone)
Address:	Late Shri Tushar bhavan, Near Shelby Hospital, Jodhpur, Ahmedabad-380015
Contact details:	<b>079-32981396</b>

# MEMORANDUM OF WORKS IN BRIEF

**Tender Notice No : 05/2026-27**

**Tender No : 29**

Municipal Commissioner invites Percentage Rate sealed tenders from interested contractors.

1	Name of work	<b>Footpath and Central verge Repairing Work of Differen T.P.Roads in Jodhpur Ward in South West Zone in AMC.(Reinvite)</b>
2	Time Limit	<b>12 months(Excluding Monsoon)</b>
3	Eligibility Criteria	Register “E2”or Above class in PWD in Govt. R&B/CPWD/AMC or equivalent registration with any other state Govt. or institutions.
4	Estimated Cost put to tender	<b>Rs. 9,50,000.00</b>
5	Earnest Money Deposit	<b>Rs.9985.00Demand</b> Draft, Pay order, or Cheque ,Bank Guarantee (As per finance circular no. 12 Dt.14/06/2021 in favour of Municipal Commissioner, Ahmedabad) To be submitted as prescribed below. Demand Draft or Bank Guarantee shall be from Nationalized Bank and valid for 120 days.
6	(A) Security Deposit:	<b>5% of Tender Amount</b>
	(B) Retention	2% of the value of work done will be deducted from each RA bill. It will be released along with release of payment of Final Bill.
7	Tender fees (Non refundable)	<b>Rs.900/-</b> Demand Draft / Pay order in favour of Municipal Commissioner, Ahmedabad)
8	Submission of EMD and Tender Fees	In separate sealed cover each for EMD and Tender Fees along with Tender as described in the invitation of tender and submitted to Office of Assistant Manager (South West Zone) Office, <b>Late Shri Tushar Bhavan, Near Shelby Hospital, Jodhpur, Ahmedabad-380015.</b>
9	Tenders issue date	Tenders from the website <a href="http://amc.nprocure.com">http://amc.nprocure.com</a> & <a href="http://nprocure.com">http://nprocure.com</a> shall be down loaded.
10	Last date of receiving Tenders.	<b>Dt. 29.06.2026 up to 18;00 hrs</b> The tenders received after this date and time will not be entertained under any circumstances.
11	Date of Opening	<b>Dt.30.06.2026 at 17;00 hrs</b> to Assistant Manager "South West Zone Office", Late Shri Tushar bhavan, Near Shelby Hospital, Jodhpur, Ahmedabad-380015
12	Mode of sending the Tender Documents	Document shall be submitted in sealed envelope systems By RPAD/ Speed post/ Hand Delivery/ Courier in sealed covers as described in submission of the tender.
13	Terms, Condition, & Specification	All general condition of contract of Form B1 condition of contract shall be applicable.

Conditional tenders will not be accepted. Municipal Commissioner reserves the rights to reject any or all the tenders without assigning any reasons thereof.

Contractor's Signature  
& Stamp  
Mobile

Addl. City Engineer  
(South West Zone)



**અમદાવાદ મ્યુનિસિપલ કોર્પોરેશન**  
**મહાનગર સેવાસદન - દક્ષિણ પશ્ચિમ ઝોન**

દક્ષિણ પશ્ચિમ ઝોન ઝોનલ ઓફીસ,  
સ્વ. શ્રી તુષાર દેશમુખ ભવન, શેલ્બી હોસ્પિટલ પાસે, જોધપુર, અમદાવાદ-૩૮૦૦૧૫

**દક્ષિણ પશ્ચિમ ઝોન ટેન્ડર નોટીસ નં-૦૫/૨૦૨૬-૨૭ માં આવરી લેવાયેલ કામોની વિગતો / શરતો:-**

૧. ઉપરોક્ત ટેન્ડરો જે તે વર્ગમાં માન્ય રજીસ્ટ્રેશન ધરાવતા કોન્ટ્રાક્ટરશ્રીઓએ ભરવા.
૨. ટેન્ડરની નિયત ટેન્ડર ફી તથા ઇ.એમ.ડી. બંધ કવરમાં ઉપર ના સરનામે રૂબરૂ / રજીસ્ટર એ.ડી./ સ્પીડપોસ્ટ/ કુરીયરથી નિયત સમયમાં મોકલવાના રહેશે.
૩. કોન્ટ્રાક્ટરશ્રીઓએ ટેન્ડરની સાથે મ્યુનિસિપલ માન્ય રજીસ્ટ્રેશનની/ ગવર્નમેન્ટ રજીસ્ટ્રેશનની કોપી, (ટેન્ડર કોપી તથા અન્ય પુરાવા સાથે) અચૂક સામેલ કરવાની રહેશે અને કવર ઉપર ટેન્ડર નંબર તથા કોન્ટેક્ટ નંબર જરૂર સ્પષ્ટ દર્શાવવાનો રહેશે. બંધ કરવર ઉપર ટેન્ડર નોટીસ નંબર, ટેન્ડર નંબર, કામનું નામ તથા, કોન્ટ્રાક્ટરની સંસ્થાનું નામ તથા કોન્ટેક્ટ નંબર અવશ્ય દર્શાવવાના રહેશે. જે કોન્ટ્રાક્ટરશ્રીઓએ રજીસ્ટ્રેશન રીન્યુ કરાવેલ ન હોય તે કોન્ટ્રાક્ટરશ્રીએ ટેન્ડર ભરવા નહીં.
૪. કોન્ટ્રાક્ટરોએ ટેન્ડરમા બેંકનું નામ, ખાતા નંબર, માર્ઈકર નંબર અને સરનામુ સ્પષ્ટ અક્ષરોમાં લખવુ.
૫. ટેન્ડર ફી પે ઓર્ડર / ડિમાન્ડ ડ્રાફ્ટથી ચૂકવવાની રહેશે. દરેક ટેન્ડર દીઠ અલગ ટેન્ડર ટેન્ડરફી ભરવાની રહેશે.
૬. ઓછી રકમની ટેન્ડર ફી, ઇ.એમ.ડી. કે ટેન્ડર ફી, ઇ.એમ.ડી. વિનાના ટેન્ડરો રદબાતલ (કેન્સલ) ગણાશે.
૭. ટેન્ડર સાથે મુકવામાં આવતી અર્નેસ્ટમની, ટેન્ડરની રકમના ૧% પ્રમાણે બેંક ગેરંટી / ડિમાન્ડ ડ્રાફ્ટ / પે ઓર્ડર / લોકલ માર્ઈકર ચેકથી જ સ્વીકારવામાં આવશે. દરેક ટેન્ડર દીઠ અલગ ઇ.એમ.ડી. ભરવાની રહેશે. ઇ.એમ.ડી. રકમ રૂ. એક કરોડ સુધીની અંદાજીત રકમના કામ માટે રોકડા, લોકલ માર્ઈકર ચેક, ડિમાન્ડ ડ્રાફ્ટ, પે ઓર્ડર કે બેંક ગેરંટીના સ્વરૂપમાં તથા રૂ. એક કરોડથી ઉપરની અંદાજીત રકમના કામ માટે ઇ.એમ.ડી.ની રકમ માત્ર ડિમાન્ડ ડ્રાફ્ટ, પે ઓર્ડર કે બેંક ગેરંટીના સ્વરૂપમાં આપવાની રહેશે.
૮. બેંક ગેરંટી માત્ર અમદાવાદ શહેરની જ સ્વીકારવામાં આવશે.
૯. ટેન્ડર ફી તથા ઇ.એમ.ડી.ની રકમના ડી.ડી./ ચેકની પાછળ કોન્ટ્રાક્ટરશ્રીએ પોતાની સંસ્થાનું નામ તથા મોબાઈલ નંબર અવશ્ય લખવાનો રહેશે.
૧૦. શરતી ટેન્ડરો રદ બાતલ ગણાશે.
૧૧. જો ટેન્ડરમાં સ્પષ્ટ ઉલ્લેખ કરાયેલ હોય તો ચોમાસાને કારણે ખાતાકીય સૂચના અન્વયે જ્યારે જ્યારે કામ બંધ રાખવાનું થાય તે સમયને કામની મુદતમાં મજરે આપવામાં આવશે. પરંતુ આ અન્વયે કોઈ ભાવ વધારો આપવામાં આવશે નહીં. જેની નોંધ ટેન્ડરે લેવી.
૧૨. ટેન્ડરો કોઈપણ કારણ આપ્યા સિવાય સ્વીકારવા કે નહિ સ્વીકારવા તેની સંપૂર્ણ સત્તા મ્યુનિસિપલ કમિશનરશ્રીની રહેશે.
૧૩. ટેન્ડરમાં જો કોઈ સુધારા વધારા હોય તો તે અંગે ટેન્ડર ભરતા પહેલા છોલ્લે દિવસે નિયત વેબસાઈટ અથવા કચેરીએ જરૂરી તપાસ કરીને જ ટેન્ડર મોકલવુ.
૧૪. સીક્યોરીટી ડીપોઝીટ/ પરફોર્મન્સ ગેરંટીની રકમ રૂ. એક કરોડ સુધીની અંદાજીત રકમના કામ માટે રોકડા, લોકલ માર્ઈકર ચેક, ડિમાન્ડ ડ્રાફ્ટ, પે ઓર્ડર કે બેંક ગેરંટીના સ્વરૂપમાં તથા રૂ. એક કરોડથી ઉપરની અંદાજીત રકમના કામ માટે સીક્યોરીટી ડીપોઝીટ/ પરફોર્મન્સ ગેરંટીની રકમ માત્ર ડિમાન્ડ ડ્રાફ્ટ, પે ઓર્ડર કે બેંક ગેરંટીના સ્વરૂપમાં આપવાની રહેશે.
૧૫. ઓનલાઈન એન-પ્રોક્યુર વેબસાઈટ પરથી ભરવાના થતા ટેન્ડરમાં કોન્ટ્રાક્ટર/ એજન્સીએ ટેન્ડરની હાર્ડ કોપીમાં ભાવ ભર્યા વગરની સહી સીકકા કરી સબમીટ કરવાની રહેશે. જો તેમાં ભાવ ભરેલ હશે તો તેવા ટેન્ડર રદ કરવામાં આવશે.
૧૬. સદર ટેન્ડરની આઈટમોના ભાવો નાણા ખાતા ના સરકયુલર નં.૩૮, તા.૨૧/૧૧/૨૨ તથા સક્ષમ સત્તાની મળેલ મંજૂરી મુજબ GST સિવાય ગણતરીમાં લેવામા આવેલ તથા પ્રવર્તમાન નિયમ મુજબ GST ચૂકવવા પાત્ર થશે જેથી તમામ બીડસે તે મુજબ ગણતરી કરી ટેન્ડરો ભરવાના રહેશે.
૧૭. સદર ટેન્ડર અંતર્ગતના કામ સંલગ્ન અ.મ્યુ.કો.માં પ્રવર્તમાન તમામ નિયમો/સરકયુલરો લાગુ પડશે તેમજ વખતો વખત થનાર સુધારાઓ પણ લાગુ પડશે. જેની નોંધ લઈ ટેન્ડરો ભરવાના રહેશે.

ડિમાન્ડ ડ્રાફ્ટ / ચેક “મ્યુનિસિપલ કમિશ્નર, અમદાવાદ” ના નામનો કઢાવવો.

૧૮. દક્ષિણ પશ્ચિમ ઝોનનાં વાર્ષિક રેઈટ ટેન્ડરમાં મરામત-નિભાવનાં ડ્રેનેજ, પાણી, રોડ, બિલ્ડીંગના જુદા જુદા કામો તથા સ્ટે.ક.ઠ.નં. ૯૩૯ તા.૨૭.૦૭.૨૦૧૨ થી વાલ્મીકી સમાજની મંડળીઓને આપવામાં આવતા ડ્રેનેજ ડીસીલ્ટીંગના કામો માટે નાગરિક અધિકાર પત્રકમાં જણાવેલ સમય મર્યાદામાં ફરિયાદનો નિકાલ કરવા તેમજ સેવાકીય કામગીરી સમય મર્યાદામાં પુર્ણ થાય તે માટે ઇ-ગર્વનન્સ સી.સી.આર.એસ. પ્રોજેક્ટ અંતર્ગતતા.૨૧.૦૮.૨૦૨૧ના સરકયુલર તથા સીટી ઇજનેર ખાતુ પરિપત્ર નં.૨ તા. ૦૭.૧૦.૨૦૨૩ ના પરિપત્ર,મ્યુ.કમિ.શ્રીની તારીખ ૨૩.૦૪.૨૦૨૬ ની મીનીટસ ઓફ મીટીંગ નાં મુદ્દા નં.૨૧ અનુસંધાને ડ્રાફ્ટ માં સામેલ પેનલ્ટી શરતો ટેન્ડરમાં રાખવાની અને તે મુજબ ની પેનલ્ટી વસુલવાની ટેન્ડર શરતો નીચે મુજબ છે.

૧. સી.સી.આર.એસ.માં નોંધાતી ફરિયાદ વોર્ડનાં ઇજનેર સ્ટાફ દ્વારા કોન્ટ્રાક્ટર/એજન્સીને વોટસએપ/ટેલીફોનિક માધ્યમથી અથવા રૂબરૂ લેખીતમાં ફરિયાદ આપવામાં આવશે.સદર ફરિયાદની કામગીરી એસ.એલ.એ. ની સમય મર્યાદામાં કરવાની રહેશે.
૨. કામગીરી પુર્ણ થયા બાદ તેના ફોટોગ્રાફ,સર્ટીફિકેટ અને કામગીરી પુર્ણ થયા ની જાણ એસ.એલ.એ. સમય મર્યાદામાં વોર્ડના સ્ટાફને કરવાની રહેશે.
૩. જો આપને આપેલ ફરિયાદ એસ.એલ.એ. સમય મર્યાદામાં પુર્ણ નહી થાય તો આ સામેલ કોષ્ટક મુજબની પેનલ્ટી ની રકમ આપનાં બીલ માંથી વસુલ કરવામાં આવશે.
૪. આપને સોંપવામાં આવેલ સી.સી.આર.એસ. ફરિયાદો નો રીપોર્ટ અઠવાડીક ધોરણે નિયત ફોર્મટમાં પ્રમાણીત કરી વોર્ડ ઓફિસે રજુ કરવાનો રહેશે.
૫. કોન્ટ્રાક્ટર દ્વારા અરજદાર ને ફોન કર્યા બાદ સદર ફરિયાદ અન્ય વોર્ડ કે અન્ય ડિપાર્ટમેન્ટ કે અ.મ્યુ.કોર્પોરેશન ના કાર્યક્ષેત્ર માં ન આવતી હોઈ તેની જાણ વોર્ડ સ્ટાફ ને તાત્કાલિક કરવાની રહેશે.

➤ સી.સી.આર.એસ ફરિયાદ સમય મર્યાદા માં નિકાલ ન થવાના સંજોગો માં કરવાની થતી પેનેલ્ટી ની વિગત નીચે મુજબ છે.

Sr. No.	Department	Category	Problem	SLA	Penalty per one Problem per day in Rs.
1	Engineering	Water>>Engineering	Inadequate water or low inflow pressure - Eng	240 Hours	500
2	Engineering	Water>>Engineering	Leakage In Pipe Line - Eng	48 Hours	500
3	Engineering	Water>>Engineering	Water quality-Polluted water - Eng	24 Hours	500
4	Engineering	Water>>Engineering	No Water - Eng	240 Hours	500
5	Engineering	Drainage>>Engineering	Drain Blockage or Choking on TP road - Eng	48 Hours	500
6	Engineering	Drainage>>Engineering	Overflowing of main line and distribution line on road - Eng	48 Hours	1000
7	Engineering	Drainage>>Engineering	No Drainage Manhole cover - Eng	24 Hours	1000
8	Engineering	Drainage>>Engineering	Frequent Breakdown & Blockage of Drain - Eng	96 Hours	500
9	Engineering	Road	Pot holes on the Road	24 Hours	500
10	Engineering	Road	Patch work Relaying of a portion of road	72 Hours	500

11	Engineering	Road	Deep Pit - Large settlement of road	48 Hours	1000
12	Engineering	Road	Removal of waste-Dust Lying on both side of the road after re surfacing	72 Hours	500
13	Engineering	Footpath	Footpath Repairing Required	168 Hours	500
14	Engineering	Public Building	No Water Supply In A Public Building	24 Hours	500
15	Engineering	Public Building	Public Toilets and Urinals - Repairing of Doors, Windows, Tiles or Sheets	360 Hours	1000
16	Engineering	Public Building	Other Maintenance	168 Hours	500
17	Engineering	Drainage>>Engineering	Contractor Had not disposed off the Manhole Silt Properly - Eng	48 Hours	500
18	Engineering	Drainage>>Engineering	Raising the Manhole Cover & Catch Pit Up To the Road Level - Eng	168 Hours	500
19	Engineering	Drainage>>Engineering	Lowering the Manhole cover & Catch pit - Eng	168 Hours	500
20	Engineering	Drainage>>Engineering	Public Toilets and Urinals - Drainage Line Blockage or Choking	72 Hours	500
21	Engineering	Drainage>>Engineering	Public Toilets and Urinals - Drainage Line Breakage	168 Hours	500
22	Engineering	Water>>Engineering	Public Toilets and Urinals - Non-Availability of Water/Cleaning of Water Tank/Broken Tank Cover	168 Hours	500

Contractor's Signature  
& Stamp

Addl. City Engineer  
(South West Zone)

Mobile No

**AHMEDABAD MUNICIPAL CORPORATION  
ENGINEERING DEPARTMENT  
GENERAL CONDITION**

1. Contractor shall produce the relevant registration certificate of AMC / State Govt /Central Govt.
2. Contractor shall register the work to labour commissioner as per labour act.
3. Contractor shall not sub-let the work without permission of the authority
4. Contractor should have sufficient skilled and unskilled laborers so that he shall start work at different sites simultaneously. Contractor's having labour force available during festivals shall only apply. Contractor cannot stop the work due to non availability of labour force.  
**In case progress is delayed, contractor shall be penalized 0.10% of Tender amount per day for work done after time limit, maximum up to 10% for remaining value of work.**
6. Advance payment / machinery advance will not be paid.
7. Payment of running bill will be made as per recent A.M.C. policy in force.
8. No extra payment will be made due to increase of central / state Govt. Taxes.
9. If the work is not completed within time limit the penalty will be recovered from immediate bills of Contractors.
10. If the material i.e. MH cover C.C block etc. supplied from Municipal Corporation store then contractor shall not claim for any extra rate for non execution of such item, partly/fully.
11. In the specifications, "as directed"/"Approved" shall be taken to mean, "as directed"/approved" by the Engineer-in-charge.
12. Wherever a reference to any Indian Standard appears in the specifications, it shall be taken to mean as a reference to the latest edition of the same in force on the date of agreement.
13. In "Mode of Measurement" in the specifications wherever a dispute arises in the absence of specific mention of a particular point or aspect, the provisions on these particular points, or aspects in the relevant Indian Standards shall be referred to.
14. All measurements and computations, unless otherwise specified, shall be carried out nearest to the following limits:
  - (i) Length, width and depth (height)----- 0.01 Meter. (RMT)
  - (ii) Areas -----0.01 Sq. Mt. (SMT)
  - (iii) Cubic Contents -----0.01 Cu.Mt. (CMT)
19. The distance, which constitutes lead, shall be determined along the shortest practical route and not necessarily the route actually taken. The decision of the Engineer-in-charge in this regard shall be taken as final.
16. Where no lead is specified, it shall mean "all leads"
17. Lift shall be measured from plinth level.
18. Definite particulars covered in the items of work, though not mentioned or elucidated in it, specifications shall be deemed to be included there in.
19. Reference to specifications of materials as made in the detailed specification of the items of work is in the form of a designation containing the number of the specification of the material and prefix 'M' e.g. 'M-5'.
20. Approval to the samples of various materials given by the Engineer-in-charge shall not absolve the contractor from the responsibility of replacing defective material brought on site or materials used in the work found defective at a later date.



21. The contract rate of the item of work shall be for the work completed in all respects.
22. No collection of materials shall be made before it is got approved from the Engineer-in-charge.
23. Collection of approved materials shall be done at site of work in a systematic manner. Materials shall be stored at site of work in a systematic manner. Materials shall be stored in such a manner as to prevent damage, deterioration or intrusion of foreign matter and to ensure the preservation of their quality and fitness for the work.
24. Materials, if and when rejected by the Engineer-in-charge, shall be immediately removed from the site of work within 24 hours.
25. No materials shall be stored prior to, during and after execution shall be kept in sufficient numbers and in good working condition on the site of the work.
26. All works shall be carried out in workmanlike manners per the best techniques for the particular item.
27. All tools, templates, machinery and equipment for correct execution of the work as well as for checking lines, levels, alignment of the works during execution shall be kept in sufficient numbers and in good working condition on the site of the work.
28. The mode, procedure and manner of execution shall be such that it does not cause damage or over loading of the various components of the structure during execution or after completion of the structure.
29. All necessary safety measures and precaution (including those laid down in the various relevant Indian Standards) shall be taken to ensure the safety of men, materials and machinery on the works as also of the work itself.
30. The testing charges of all materials shall be borne by the Contractor unless recovery at one percent towards testing charges is separately made.
31. The tenderer is required to check the web site for Addendum if any, before 48 hours of tender submission date and time. The tenderer who quotes the tender without attaching the addendum will be rejected.
32. As per City Engineer's circular no.-6/2011-12 Dt.24.6.2011 all terms & conditions will be applied.
33. Contractor has to follow Planning Department Circular No 10 Dt. 07/09/2018 strictly.
34. As per AMC's Finance department circular no.38/ Dt.21/11/022 and approval of competent authority, rate of all the items are taken without GST and prevailing GST will be payable.
35. All the relevant prevailing AMC circulars/ its time to time revisions are applicable for this work and all the bidders are bound to follow the same, so the bidder must check before applying for the tender.

#### INSTRUCTION TO TENDERERS

##### TENDER VALIDITY PERIOD:

The tender shall be kept valid for acceptance for a period of One Hundred Twenty Calendar days (90) from opening of price bids.

##### SECURITY DEPOSIT

Within 10 days of receipt of Acceptance from the Corporation, the successful tender shall furnish to the Corporation Security Deposit of 5% (Five percent) of the contract price Cheque or Bank Guarantee, pay order, or demand draft of Nationalized Banks and Schedule Banks only.

Contractor's Signature  
& Stamp

Addl. City Engineer  
(South West Zone)

**AHMEDABAD MUNICIPAL CORPORATION**  
**ENGINEERING DEPARTMENT**  
**GENERAL SPECIFICATION**

Time limit for the work shall be **12 Month (Excluding Monsoon)** after the order to start the works. Progress of work should be in proportion to time limit.

The contractor shall remain responsible for Workmen's compensation if any accident. The contractor shall arrange for barricading at night and arrangement of Pagi at night to direct the traffic. He shall be responsible for any damage to public, If any incident happen, during the execution of work. In case of dispute for unseen or overlooked items the decision of the Dy.City Engineer shall be final. The contractor shall have to give site clean of all rubbish during the work and at the time of completion of work and hand over the site with final finishing of the work as directed. All the rejected materials shall be removed from site within 24 hours by contractor at this risk and cost. Debris shall have to cart daily from site.

If any extra item crops up during the progress of work the same shall be carried out by the contractor and he shall be paid at the rate fixed by Add.C.E. as per the rate analysis based on latest SOR or if item is not available in SOR than based on current market rates. In case of extra item decision of Add. City Engg. shall remain final regarding rate.

If in the interest of the Corporation it is necessary to change either any site or the design of the propose work the contractor shall carry out the same at his quoted rates without charges any extra and the contractor will have to carry out the works and he will be paid at the rate quoted by him. No claim for extra rate for subsequent changes in site and design is entertained.

Octroi exemption passes shall not be given for any materials required for the work. Contractor will be fully responsible for compliance of the various provisions under contract Act. 1970 and the Rules framed the to under.

The tender for the work shall remain open for a period (120) days from the date of opening of the tenders for this work and that the tenderer shall not be allowed to withdraw or modify the offer on his own during the period. If any tenderer withdraw or makes any modifications or addition in the terms and conditions of his tender not acceptable to the Municipal Corporation the Municipal Corporation shall without prejudice to any right or remedy be at liberty to forfeit in full the said earnest money and black list the contractor.

If the work is not carried out within the specified time limit. from the date of order to start the work the penalty of Rs.- ( As per Form - B1) per day of delay shall be recovered from the immediate bills payable to the contractor. Contractor has to make his own arrangement for procurement of steel and cement.

**Contractors should note the following conditions carefully:-**

- i) Conditional tender shall not be accepted.
- ii) All tenders are to be submitted in duplicate without which the tenders are liable to be rejected.
- iii) In case of tender downloaded from website, tender fee & EMD should be submitted in form of demand draft or in cash.
- iv) Condition of Form - B1 Standard Specification of material & code of practice will be applicable. Form B1 can be is available in website. Specification shall be as per ' R & B Dept. - Govt. of Gujarat booklets of Building Works & and Road Works Specifications published by Gujarat Book Depot, Sector-21. Gandhinagar.

Contractor's Signature  
& Stamp

Addl. City Engineer  
(South West Zone)

Mobile No



અમદાવાદ મ્યુનિસિપલ કોર્પોરેશન  
નાણાંખાતું,  
બી-બ્લોક, પહેલો માળ, સરદાર પટેલ ભવન, દાણાપીઠ, અમદાવાદ.



નાણાં ખાતું  
સરકયુલર નં.: ૦૬  
તા.: ૧૨/૦૫/૨૦૨૫

### બેંક ગેરંટી સરકયુલર

સંદર્ભ:- નાણાં ખાતાના સરકયુલર નં. ૪૮ તા.૨૯/૦૧/૨૦૧૨,૫૮ તા.૧૬/૦૩/૨૦૧૨,૧૪ તા.૦૪/૦૬/૨૦૧૩, ૦૩ તા.૧૩/૦૫/૨૦૧૪, ૨૧ તા.૨૯/૦૫/૨૦૧૫, ૫૬ તા.૧૯/૦૯/૨૦૧૬, ૧૮ તા.૨૩/૦૫/૨૦૧૭, ૧૮ તા.૨૯/૦૫/૨૦૧૮, ૧૨તા.૨૨/૦૭/૨૦૧૯,૨૬ તા.૨૫/૧૧/૨૦૧૯ ,૨૧તા.૧૯/૦૬/૨૦૨૦,૪૦ તા.૦૫/૧૧/૨૦૨૦,૧૨ તા.૧૪/૦૯/૨૦૨૧,૨૩ તા. ૨૦/૦૯/૨૦૨૧ , ૪૧ તા.૦૮/૦૨/૨૦૨૨, ૦૩ તા.૨૮/૦૪/૨૦૨૪, તથા ૧૦ તા. ૦૫/૦૮/૨૦૨૪

આથી તમામ ખાતાના વડા અધિકારીશ્રીઓ/એકાઉન્ટશ્રી તથા બિલકલાર્કશ્રીને જણાવવામાં આવે છે કે, સિક્યુરિટી ડીપોઝીટ તેમજ અર્નેસ્ટમની ડીપોઝીટ સ્વીકારવા બાબતે રાજ્ય સરકારશ્રી દ્વારા મંજૂર થયેલ બેંકોની યાદીમાં નાણાં વિભાગના જી.આર. નં. **FD/MSM/e-file/4/2024/4020/2859 D.M.O. Date: 01/05/2025** મુજબ સુધારો કરી નવી યાદી બહાર પાડવામાં આવેલ છે.

રાજ્ય સરકારશ્રીના નાણા વિભાગનાં જી.આર. નં . **FD/MSM/e-file/4/2023/4020 / 2859 D.M.O. Date: 01/05/2025** દ્વારા સિક્યુરિટી ડિપોઝીટ તેમજ અર્નેસ્ટમની ડીપોઝીટ માટે મંજૂર થયેલ બેંકોની યાદી અંગે ડે.મ્યુનિ.કમિશનરશ્રી(નાણાં)ની મળેલ મંજૂરી ઠ.નં ૩૯ તા ૧૨/૦૫/૨૦૨૫ મુજબના સદરહુ પરિપત્ર પ્રસિધ્ધ થયા તારીખ બાદથી તા.૩૧/૦૩/૨૦૨૬ સુધી અથવા રાજ્ય સરકારશ્રી દ્વારા આ બાબતે અન્ય જી.આર પ્રસિદ્ધ કરવામાં આવે ત્યાં સુધી એનેક્ષર-૧ માં જણાવેલ બેંકોની બેંકગેરંટી સીક્યુરિટી ડીપોઝીટ તથા ઈ.એમ.ડી. સ્વરૂપમાં સ્વીકારવામાં આવશે.

અમદાવાદ મ્યુનિસિપલ કોર્પોરેશનના તમામ ખાતાઓ દ્વારા મેળવવામાં / સ્વીકારવામાં આવતી બેંક ગેરંટીની ઓથેન્ટીસીટીની અધિકૃત ચકાસણી કરીને / કરાવીને જરૂરિયાત મુજબના કન્ટ્રોલ પ્રોસીજર સેટઅપ કરવાના રહેશે. તેમજ સરકારશ્રીના જી.આર અન્વયે ડે. મ્યુનિસિપલ કમિશનરશ્રી (ફાયનાન્સ) ની મળેલ મંજૂરી મુજબ માત્ર અમદાવાદ શહેરની તથા અમદાવાદ સિવાયના અન્ય શહેરની હોય અને તે બેંક ગેરંટી અમદાવાદ સ્થિત સંબંધિત બેંકની શાખા દ્વારા અધિકૃત કરાયેલ હોય તો નીચે જણાવેલ બેંકોની શાખાઓની બેંક ગેરંટી સ્વીકારવામાં આવશે. નાણાંખાતા દ્વારા ઉપરોક્ત સંદર્ભમાં જણાવેલ પરિપત્રોની અન્ય તમામ શરતો યથાવત રહેશે.

### **ANNEXURE – I**

**A. Guarantees issued by following banks will be accepted as SD/EMD on permanent basis.**

❖ **All nationalized Banks**

**B. Guarantees issued by following banks will be accepted as SD/EMD for the period up to March- 31, 2026. The validity cut-off date in the GR is with respect to the date of issue of Bank Guarantee irrespective of the date of termination of Bank Guarantee.**

#### **1. Commercial Banks :-**

1. Axis Bank
2. A U Small Finance Bank
3. Bandhan Bank
4. Barclays Bank
5. City Union Bank
6. CSB Bank
7. DBS Bank India Limited
8. DCB Bank
9. Equitas Small Finance Bank
10. ESAF Small Finance Bank
11. Federal Bank

- 12.HDFC Bank
- 13.HSBC Bank
- 14.ICICI Bank
- 15.IDBI Bank
- 16.IDFC First Bank
- 17.Jammu and Kashmir Bank
- 18.Jana Small Finance Bank
- 19.Karnataka Bank
- 20.Karur Vysya Bank
- 21.Kotak Mahindra Bank
22. South Indian Bank
23. Standard Chartered Bank
- 24.Tamilnadu Mercantile Bank
- 25.Utkarsh Small Finance Bank
- 26. YES Bank**

## **2. Co-operative and Rural Banks Of Gujarat :-**

1. The Ahmedabad Mercantile Co-operative Bank Limited
2. Nutan nagrik Sahakari Bank Limited
3. Rajkot Nagarik Sahakari Bank Limited
4. Saraswat Co-operative Bank
5. SBPP Co-operative Bank
6. SVC Co-operative Bank
7. The Cosmos co-opretive Bank
8. The Gujarat State Co-Operative Bank
9. The Mehsana Urban Co-operative Bank Limited
10. The Surat District Co-operative Bank
11. The Surat Peoples Co-operative Bank
12. The Kalupur Commerical Co-operative Bank Limited
13. The Panchmahal District Co-operative Bank
14. The Baroda District Co-operative Bank
- 15.Baroda Gujarat Gramin Bank
- 16.Saurashtra Gramin Bank**

ચીફ એકાઉન્ટન્ટ

સરકયુલર નં.-૮૧

મે.મ્યુનિ. કમિશ્નરશ્રી, અમદાવાદ મ્યુનિ. કોર્પોરેશનના સરકયુલર નં.-૮૧, તા.૨૬.૦૨.૨૦૧૫ મુજબ તમામ પ્રકારની કન્સ્ટ્રક્શનની એક્ટીવીટીમાં મુખ્ય કોન્ટ્રાક્ટર, સબ કોન્ટ્રાક્ટરના જે મજુરો કામગીરી કરતા હોય તે તમામ મજુરોનું ગુજરાત બિલ્ડીંગ એન્ડ અધર કન્સ્ટ્રક્શન વર્ક્સમાં રજીસ્ટ્રેશન કરાવવું ફરજિયાત છે.

Contractor's Signature  
& Stamp

Addl. City Engineer  
(South West Zone)

Mobile No

**DETAILS OF BANK ACCOUNT**

1	Contractor's name	
2	Address	
3	Telephone/ mobile no.	
4	Permanent account no. (PAN no.)	
5	Name of the bank	
6	Branch name and address	
7	Account type	
8	Account no.	
9	MICR no.	
10	IFS CODE	
11	Contractor/ supplier's  signature and stamp	

**AHMEDABAD MUNICIPAL CORPORATION  
ENGINEERING DEPARTMENT**

**PERCENTAGE RATE TENDER AND CONTRACT FOR WORKS ADDITIONAL INSTRUCTIONS TO PERSONS  
TENDERING**

1. Competency of Tendered: No contract will be awarded except to responsible bidder capable for performing the class of work completed. Before the award of the contract, any bidder may be required to show that he has the necessary facilities, experience, ability and financial resources to perform the work in satisfactory manner within the time stipulated. Contractor may be required to furnish the department with the statement as to their experience and their financial status.
2. Tenderer will be deemed to have inspected the site and to have satisfied himself as to the nature of all works, all existing roads water - way and other means of communication and access to and from the site of work and the building that may be required for temporary purpose in connection with the construction, completion and maintenance of the works and must make his own enquiries as to work yard, sites, depot and dumps and as to the acquisition of such additional sites and areas as may be necessary for temporary purpose for constructing, completing and maintaining the works.
3. Payment: - The tenderer must understand clearly the rates quoted are for completed works and include all cost due to labour, scaffolding plant, supervision, service work, power, royalties and octroi etc. and include all extras to cover the cost of night work if and when required. No claim for additional payment beyond the prices or rates quoted will be entertained and the tender will not be entitled subsequently to make any claim on the ground of misrepresentation or on the ground that he was supplied with information given by any person (whether the member is the employee of Engineering Department of Corporation or not). Any failure on his part to obtain all necessary information for the purpose of making his tender and filling the several prices and rates therein shall not relieve him from any risks or liabilities arising out of, or consequent upon the submission of the tender.
4. Tender Forms: - the tenderer must fill up every blank in the form of tender and in the schedule and he must return the documents sent here with.
5. Erasures: - Persons tendering are informed that no erasures or alternations by them in the text of the documents sent herewith will be allowed and any such erasures or alternations will be disregarded. If there is any error in writing no over-writing should be done, the wrong words or a figure should be struck out and the correct one written above or near it in unambiguous way, each correction should be initialed.



### CONTRACTORS TO PLEASE READ THIS CAREFULLY

1. The rate for items must be given in words and figures. Amount of each item must also be entered in columns and the tenderer must strike out grand total of the amount.
2. If the tender is taken in favor of the company, a power of attorney in favour of the person who may have signed the tender for the company must accompany the tender.
3. Solvency Certificate of a Bank or a Revenue Officer of an amount upto 20% of the tendered cost plus the amount of works on hand still to be executed will have to be reduced by the Contractor.
4. Challan for earnest money must accompany the tender. Tenderer may pay earnest money in the form of CROSSED Demand Draft in favour of the Municipal Commissioner of Municipal Corporation, Ahmedabad. Earnest money in cash or by cheque shall not be accepted.
5. The Contractor shall have to furnish Income Tax Clearance Certificate before tender is accepted and intimate assessment number and ward under which is assessed.
6. Copies of certificate as regards previous experience if any must accompany the tender.
7. Declaration showing all works on hand with the Contractor and the value of works that remain to be executed in each case must accompany tender.
8. All pages should be initial
9. The Contractor should initial all corrections, erasures and over writing.
10. Discrepancies and Adjustment of Errors: Any error in quantity or amount in schedule 'B' showing items of works to be carried out shall be adjusted in accordance with the following rules :
  - (a) In the event of a discrepancy between description in words and figures quoted by a tenderer in the 'rates' column, the description in words shall prevail.
  - (b) In the event of an error occurring in the 'amount' column of the schedule 'B' showing items of work, as a result of wrong multiplication of the unit- rate and quantity, the units - rate shall be regarded as firm and multiplication shall be amended on the basis of the rates.
  - (c) All errors in totaling in amount column and in carry forward totals shall be corrected.
  - (d) Any rounding off of amounts against 'items' or 'totals' shall be ignored.
11. (i) It may please be noted that tender will be considered as invalid especially, if the requirements as per instruction. No. 1 to 10 above is not complied with before submitting the tender. Also please read carefully the face-sheet and General Rules and Directions for the guidance of Contractors of this form.  
(ii) Right is reserved to reject any or all tender (s) without assigning any reason(s) thereof.  
10A. The tender will be liable to be rejected outright if the tenderer has filled in tender documents by ball pen instead in ink.  
11. In addition to the above the tender will also be liable to be rejected outright if:
  - (i) The tenderer proposes any alternation in the works specified or in the time allowed for carrying the work or any condition or correction made in any code or mode of schedule 'B' or specifications.
  - (ii) Any of the page / pages of the tender is / are removed or replaced.
  - (iii) The tenderer does not initial all corrections, additions or pasted slips.
  - (iv) He makes any erasure in the tender. And
  - (v) The tenderer or in the case of a firm, each partner or the person holding the power of attorney there of does not sign or the signatures is / are not attested by a witness the tender in the space provided for the purpose.
12. A certificate of registration as approved Contractor should be attached with the tender.  
12A. In respect of the tenders from the Co-operative Society, a solvency, certificate of an amount equal to 20% of the amount of the work put to tender will have to be produced along with the tender or a certificate regarding the borrowing capacity of the society issued by the Legal Assistant, Directorate Cottage industries will have to be produced along with the tender.
13. (1) The several documents forming the contract are the essential parts of the contract a requirement occurring in one is as binding as though occurring in all they are intended to be mutually explanatory and complementary and to described and provide for a complete work.

(2) In the event of any discrepancy, the several documents forming the contract or in any one document the following order or precedence should apply:

(a) Dimension and quantities: -

(i) Schedule 'B' of the tender form.

(ii) Specification.

On drawing, figured, dimensions, unless obviously, incorrect will be followed in preference to scaled dimension.

(b) Description:

(i) Schedule 'B' of the tender form.

(ii) Specifications.

In case of defective description or ambiguity, the Engineer-in-Charge should issue further instructions directing in what manner the work is to be carried out, it being understood that the best modern practice is to be followed. The Contractor should forthwith comply with such instructions.

14. The Contractor should take no advantage of any apparent error or omission in drawings or specifications and the Engineer-in-Charge shall make such corrections and interpretations as necessary to fulfill the intent of the plants and specification.

15. All the materials to be used in the work may be from time to time subject to tests as per relevant I.S. as decided by the Engineer .

16. The board stating the detailed specifications and details of work as per Current circular of AMC/Government Circular No.TNC-1090-24-S, Dated 17-08-2002, should be erected as directed on the site of work by the contractor without claiming extra for the same.

17. Action in case of disproportionate progress:

In case of extremely poor progress of the work or any item at any stage of work which in the opinion of the Engineer, cannot be made good by the contractor considering his available resources, the Engineer will get it accelerated to make up the lost time through any other agency and recover the additional cost incurred, if any, in getting the work done from the contractor after informing him in writing about the action envisaged by him. The action may include blacklisting of the contractor based on the works and severity and decision of Municipal Commissioner shall be binding in this condition.

**18. Footpath Paver Block, Footpath curb, Central verge curb - Successful bidder of this tenders shall have to purchase 50% of total quantity of Paver Blocks/ footpath curbs/Central verge curbs from Amdavad Enviro Projects Pvt. Ltd. directly. If quantity of 50% of Paver block/Footpath curbs/Central verge curbs are not available Amdavad Enviro Projects Pvt. Ltd within stipulated period of time, contractor has to take prior permission for use of other than from Amdavad Enviro Projects Pvt. Ltd. Paver blocks/Footpath curbs/Central verge curbs.**

Contractor's Signature  
& Stamp

Addl. City Engineer  
(South West Zone)

Mobile No

**Name of work: Road Grouting work in different TP Roads and Breakdown site in jodhpur ward, South west zone AMC.(Reinvite)**

**DECLARATION FORM**

1. I/We hereby declare that I/We have visited the and fully acquainted myself / ourselves with the local regarding materials, labour and other factors pertaining to the work before submitting this tender.
2. I/We hereby declare that I/We have carefully studied the conditions of contract, specification and other tender documents of this work and agree to execute the same accordingly.

.....  
**Signature of the Contractor**

**GENERAL RULES AND DIRECTION FOR THE GUIDANCE OF CONTRACTORS :**

1. All works proposed to be executed by contract shall be notified in a form of invitation to tender pasted on a board hung up in the Addl. City Engineer and signed by the Addl. City Engineer. This form will state the work to be carried out, as well as the date for submitting and opening tenders and the time allowed for carrying out the work, also the amount of earnest money to be deposited with the tender and the amount of the security deposit to be paid by the successful tenderer and the percentage, if any, to be deducted from bills, it will also state whether a refund of quarry fees, royalties, octroi dues and ground-rent will be granted, copies of the specifications designs and drawings and estimated rates, scheduled rates and any other documents required in connection with also be open for inspection by Contractors at the office of the Addl. City Engineer during office hours. Where the works are proposed to be executed according to the specifications recommended by a Contractor and approved by a competent authority on behalf of the Municipal Corporation such specification with designs and drawings shall form part of the accepted tender.
2. In the event of the tender being submitted by a firm, it must be signed on his behalf by a person holding a power-of-attorney authorizing him to do so.
3. Receipts for payments made on account of any work, when executed by firm, shall also be signed by all the partners, except where the Contractors are described in their tender as a firm, in which case the receipt shall be signed in the name of the firm by one of the partners or by some other person having authority to give effectual receipt for the firm.
4. Any person who submits a tender, shall fill up the usual printed form including the 'column' total according to estimated quantities, stating at what rate he is willing to undertake each item of the work, Tenders which purpose any alteration in the works specified in the said form of invitation to tender or in the time allowed for carrying out the work or which contain any other conditions of any sort, will liable to rejection. No single tender include more than one work, but Contractors who wish to tender for two or more works, shall submit a separate tender for each. Tenders. shall have the name and the number of the work (to which they refer) written outside the envelope.
5. The Addl. City Engineer or his duly authorized Assistant shall open tenders in the presence of any intending Contractors who have submitted tenders or their representatives who may be present at the time and he will enter the amounts of the several tenders in a comparative statement in a suitable form. In the event of a tender being accepted, the Contractor, shall thereupon for the purpose of identification, sign copies of the specifications and other documents mentioned in this

tender in the event of a tender being accepted the contractor, shall thereupon for the purpose of indication, sign copies of the specifications and other documents mentioned in this tender in the event of a tender being rejected, the Municipal Commissioner shall authorize the officer concerned to refund the amount of the earnest money deposited to the Contractor making the tender on his giving a receipt for the return of the money.

6. The officer competent to dispose of the tenders shall have the right of rejecting all or any of the tenders.
7. No receipt for any payment alleged to have been made by a Contractor in regard to any matter relating to this tender or the contract shall be valid and binding on Municipal Corporation unless it is signed by the Addl. City Engineer.
8. The memorandum of work to be tendered for any schedule of materials to be supplied by the Municipal Corporation and their rates shall be filled in and completed by the office of the Addl. City Engineer before the tender form is issued. If a form issued to an intending tenderer has not been so filled in and completed, he shall request the said office to have this done before he completes and delivers his tender.
9. All works shall be measured not by standard measure and according to the rules and customs of the Municipal Corporation without reference to any local custom.
10. Under no circumstances shall any Contractor be entitled to claim enhanced rates for any item in this contract.
11. Every Contractor shall, unless exempted in writing by the Addl. City Engineer concerned, produce along with this tender, a solvency certificate of his financial stability from the collector of the District within which he resides or a Bank's certificate. If he fails to produce such a certificate his tender will not be considered.
12. All corrections and additions or pasted slips should be initialed.
13. All measurement of work will be taken according to the usual method in use in the Municipal Corporation and as per I.S. code for general practice and no proposals to adopt alternative methods will be accepted. The Addl. City Engineer's decision as to what is 'the usual method in use in the Municipal Corporation' will be final.
14. The Contractor shall have to attach to his tender, Income-Tax Clearance certificate to be obtained from the Income-Tax Officer.
15. The Contractor will have to construct a shed for storing controlled and valuable materials issued to him under schedule A' of the agreement at work-site having double locking arrangement. The materials will then be taken for use in the presence of the Departmental person. No material will be allowed to be removed from the site of work.
16. No foreign exchange will be released by the Department for the purpose of plant and machinery required for the execution of the work contracted for.
17. Controlled materials (Essentially Certificate)
  - (i) As regards controlled materials, the Municipal Corporation will help to arrange for the permit as far as possible and help the Contractor in securing the same. All incidental charges met with in procuring these materials shall be borne by the Contractor himself. Though the Municipal Corporation will help to arrange for the permit as far as possible and help the Contractor in obtaining materials, it shall not accept any responsibility for any delay or loss on account of delay caused to the contractor while obtaining the same.

- (ii) The contractor shall submit to. Addl. City Engineer on close of every calendar month, the monthly returns in the prescribed forms as to the receipts and actual use of the controlled materials during the month.
  - (iii) The Contractor shall permit the Addl. City Engineer or his representatives to inspect the stock of the controlled materials stored by him at any time whenever the Addl. City Engineer or his representative(s) so desire (s).
18. The tender for the work shall remain open for a period of (120 days) from the date of opening of the tenders for this work and the tenderer shall not be allowed to withdraw or modify the offer on his own during this period. If any tenderer withdraws or marks any modifications or additions in the terms and conditions of his tender, not acceptable to the Municipal Corporation, then Municipal Corporation shall, without prejudice to any right or remedy, be at liberty to forfeit in full the said earnest money.
19. The Contractor shall employ only such labour that shall produce a valid certificate of having been vaccinated against small - pox within a period of last three years.
20. Footpath Paver Block, Footpath curb, Central verge curb - Successful bidder of this tendershall have to purchase 50% of total quantity of Paver Blocks/ footpath curbs/Central verge curbs from Amdavad Enviro Projects Pvt. Ltd. directly. If quantity of 50% ofPaverblock/Footpath curbs/Central verge curbs are not availableAmdavad Enviro Projects Pvt. Ltd within stipulated period of time, contractor has to take priorpermission for use of other than from Amdavad EnviroProjects Pvt. Ltd.Paver blocks/Footpath curbs/Central verge curbs.

#### TENDER FOR WORKS.

<p>I/We hereby tender for the execution for the Municipal Corporation of Ahmedabad (herein before and herein after referred to as 'Corporation') of the work specified in the under written memorandum within the time specified in such memorandum at *</p> <p>..... Percent below /</p> <p>above the estimated rates specified schedule 'B' (memorandum showing item of works to be carried out) and in accordance in all respects with the specifications, designs, drawings and instructions in writing referred to in this tender and in Clause 13 of the annexed conditions of contract and agree that when materials for the work are provided by Corporation, such materials and the rates to be paid for them shall be as provided in schedule 'A' hereto.</p>	<p>* In Figures as well in words.</p>
<p><b>MEMORANDUM</b></p>	
<p>(a)General Description. <b>Road Grouting work in different TP Roads and Breakdown site in jodhpur ward, South west zone AMC.(Reinvite)</b></p> <p>(b) Estimate Cost: <b>Rs. 9,98,562/-</b></p>	<p>(a) If several sub works are included the should be detailed in a separate list. The amount of earnest money to be deposited shall be in accordance with instruction no. 4</p>

(c) Earnest Money: 1% of the estimated amount of tendered work. <b>Rs.9986.00</b>	
---	--

**(D) SECURITY DEPOSIT**

- (i) 5% of the contract value cost paid in cash if the contract value is less than Rs. 5000/-
- (ii) (a) 1% of the estimated cost paid as earnest money along with the tender.  
(b) Security Deposit is equal to 5% of the sectioned tender cost in form DD or Bank Guarantee.
- (iii) Bank Guarantee from a Nationalized Bank or Bank approved by the Municipal Corporation for an amount equal to 5% of sectioned tender cost

Note – 1. All work shall be carried out as per Public Works Department Handbook and other specifications of Ahmedabad Municipal Corporation or as directed.

Note – 2. Rates quoted include clearance of site (prior of commencement of work and at its close) in all respects and hold good for work under all condition, site moisture weather etc

Contractor's Signature  
& Stamp

Addl. City Engineer  
(South West Zone)

Mobile No

## **SPECIFICATIONS OF MATERIALS**

**This section gives detail specifications for mainly used materials, for other materials refer Building Specifications. For materials relevant specification of Building Specification shall apply.**

## **TECHNICAL SPECIFICATIONS**

**Name of Work : Road Grouting work in different TP Roads and Breakdown site in jodhpur ward, South west zone AMC.(Reinvite)**

**Item No.1 : Box cutting the road surface to proper slope and camber for making a base for road work including removing the excavated stuff and depositing on the road side slope as directed upto 200 Mt.lead.**

Any soil which generally yields to the application of pickaxes and shovels, spades, rakes or any such ordinary excavating implement or organic soil, gravel, silt, sand turf loam, clay, peat etc. falls under this category. For materials and workmanship for earthwork and excavation, relevant specification IS: 3764 & IS 1200 (Part I) shall be followed.

The depth of the excavation shall be as per the item description.

Clearing the Site:

The site where the Development has to be carried out shall be cleared and all obstructions, loose stones, materials and rubbish of all kind, bush; wood and all type trees shall be removed, as directed.

The materials so obtained shall be the property of the Client and shall be conveyed and stacked as directed, within 50-m. lead. The roots of the trees coming in the sides of the trenches shall be cut and coated with hot Bitumen.

All types of trees, woods etc. which requires prior permission of Govt./ Forest Authority / Municipal Commissioner, before cutting shall be cut after obtaining such permission from them. It shall be the Client's responsibility to obtain such permission from the respective authorities.

The rate of site clearance is deemed to be included in the rate of earthwork, for which no extra will be paid.

Setting out:

After cleaning the site, the centerline of the central verge & other constructions will be given by the Engineer-in-charge. The Contractor shall assume full responsibility for alignment, elevation and dimension of each and all parts of the work. Contractor shall supply labours, materials, etc. required for

setting out the reference marks and bench marks made of MS angle iron and embedded in 1:2:4 CC.



They shall maintain the same as long as required and directed.

**Excavation:**

The excavation shall be carried out in true line and level and shall have the width and depth, as shown

in the drawings or as directed. The Contractor shall do the necessary shoring and strutting or shall provide necessary slopes to a safe angle or steps, as required or directed, at his own cost. No extra payment shall be made for such precautionary measures, taken. The bottom of the excavated area shall be leveled both longitudinally and transversely, as directed, by removing excess soil and watering, as required. No earth filling will be allowed for bringing it to level, if by mistake or any other reason,

excavation is made deeper or wider than shown on the drawings or as directed. The extra depth or width shall be made up with sand filling, as specified for the bottom level of the subsequent finishing at the cost of the Contractor or as directed by Engineer-In-Charge.

The Contractor shall at his own expense and without extra charge make provision of supporting all utility services, lighting the excavated areas, separating and stacking serviceable materials neatly, shoring, timbering, strutting, bailing out water either sub-soil or rainwater, including pumping at any stage of the work. Excavated areas shall be kept free of water while masonry or concrete or relevant base works are in progress and till the Engineer-in-charge considers it necessary.

**Disposal of the Excavated Stuff:**

The excavated stuff of the selected type shall be used in filling the excavated areas wherever required in layers, including ramming and watering, ensuring proper compaction etc. complete.

The Contractor shall remove the balance of the excavated quantity from the site of work, to a place, as directed and for all lift.

The lead is the shortest practical route and not necessarily the route actually taken. The decision of Engineer-In-charge shall be final in this regard.

**Mode of Measurement and Payment:**

The measurement of excavation of excavated area shall be made according to the sections shown on the drawing or as per sections given by the Engineer-in-charge. No payment shall be made for surplus excavation made in excess of above requirements or due to stepping and sloping back as found necessary, on account of conditions of soil and requirements of safety.

The rate shall include for clearing the site, surface dressing, making layout for road, fixing permanent grid points with MS iron posts, embedded in C.C. 1:2:4, placed sufficiently away from the existing traffic lines and establishing bench marks etc.

The rates shall include for necessary shoring, timbering and strutting for protection of sides of the excavated area, pumping out rain or surface water at any stage of construction so as to keep the

excavated area dry, to the satisfaction of the /Engineer-in-charge.

The rate shall include leveling and ramming the bottoms of excavations to receive concrete, etc.

including trimming to slope wherever necessary etc. complete.

In filling clods bigger than 50 mm. shall not be allowed. Only consolidated measurements of filling shall be paid. Consolidation to be done by mechanical compactor as per relevant item.

**Item No.2 : Extra rate over item of excavation of earth for excavation of asphalt pavement / RCC of thickness up to 0.20 meter including demolishing the asphalt carpet, metal, s oiling/cutting Reinforcement etc.comp. with stacking the material as directed. (Based on Previously approved rate by C E sir ) a) up to 0.20 meter thickness (By Manual) b) 0.20 to 0.30 meter (By any type of Breaker Machine or R.C.C.Cutter machine including cost of operator, fuel, & transportation etc complete. C) 0.30 meter & above (By any type of Breaker Machine or R.C.C.Cutter machine including cost of operator, fuel, & transportation etc complete.**

Extra rate for excavation of asphalt pavement for thickness Upto 0.20 Meter including demolishing the asphalt carpet, metal, soiling etc. complete by Manually And For thickness from 0.20 Meter to 0.30 Meter By Breaker Machine with stacking the materials as directed. Cost of operator, Fuel, & Transportation Etc is Included for Asphalt Cutting By Breaker Machine. The road surface of asphalt shall carefully be opened to full width as directed by the Engineer in charge Asphalt, popada's spouls, metals etc shall be separately deposited in such places as may be determined by the Engineer-in-charge. In case above materials not being so deposited or being mixed up with the excavated materials will not be allowed for refilling. The cost of materials shall be charged from the contractor. The decision of the Addl.C.E. Shall be final and binding to the contractor.

The rate per sq.mt. in this item shall be paid extra addition to the rate for excavation

Mode of measurement: The rate shall be for a unit of Smt. Basis..

**Item No.3 : Demolition incl. staking of serviceable materials & Disposal of Unserviceable materials with all lead & lift .a) Demolition of brick work & stone masonry including stacking of serviceable materials and disposal of unserviceable materials with all lead and lift (1) In cement mortar.(R&B SOR 2021-22 ITEM CODE 20003B Item no.as per NBO 20.11) b) Demolition & disposal of unservisable material with all lead and lift for unreinforced concrete. (AMC sor) c) Demolition including stacking of serviceable materials and disposal of unserviceable materials with all lead and lift. (I) R.C.C work.(R&B SOR 2021-22 ITEM CODE 20002 Item no.as per NBO 20.3) d) central verge -kerb stone**

Demolition incl. staking of serviceable materials & Disposal of Unserviceable materials with all lead & lift .a) Demolition of brick work & stone masonry including stacking of serviceable materials and disposal of unserviceable materials with all lead and lift (1) In cement mortar.(R&B SOR 2021-22 ITEM CODE 20003B Item no.as per NBO 20.11) b) Demolition &

disposal of unserviceable material with all lead and lift for unreinforced concrete. (AMC sor) c) Demolition including stacking of serviceable materials and disposal of unserviceable materials with all lead and lift. (I) R.C.C work.(R&B SOR 2021-22 ITEM CODE 20002 Item no.as per NBO 20.3) d) central verge -kerb stone (AMC sor)

The rate shall be for a unit of one cmt and E is in rmt.

**Item No.4 : Conveyance charge of earth, lime, murrum, building rubbish, manure, garbage, sludge, excavated rock, fly ash, aggregates of any kind executed outside the road site. Rate also includes spreading & levelling etc complete. Internal conveyance above 50 mt done within the work site is not payable.**

The surplus earth, which is left on site after refilling and proper watering of the trenches, shall be carted away up to a distance within lead upon kmts. All surplus earth should be carted away immediately after the instruction or orders of the engineer in charge within 24 hours. The surplus earth shall be spread at the site shown where it is carried. If the work is not carried out by the contractor as above AMC may carry out the same at the risk and cost of contractor and the same may be deducted from the dues to the contractor in any form.

The measurement of the surplus earth shall be paid for as per arithmetical calculations. Nothing extra shall be paid for the bulk age of the excavated earth

The rate shall be for a unit of Cmt.

**Item No.5 : Providing and laying cement concrete 1:5:10 (1- Cement : 5- fine sand : 10- graded brick bat aggregates 40mm nominal size) and curing complete.**

Materials :-

**1.1** Water shall conform to M-1, Cement shall conform to M-3. Sand shall conform to M-6. Stone aggregate 40 mm. Nominal size shall conform to M-12.

**2.0** Workmanship :

**2.1** The relevant specification of item No 5.3.2.(A) shall be followed for the work except that the work is to be carried out in cement concrete 1:5:10.

**3.0** Mode of measurement and payment :

**3.1** The concrete shall be measured for its length, breadth and depth. Limiting dimensions to those specified on plans or as directed.

The rate shall be for a unit of one cubic meter.

**Item No.6 : Providing, laying, spreading and compacting graded stone aggregate to wet mix macadam specification including premixing the Material with water at OMC in mechanical mix plant carriage of mixed Material by tipper to site, laying in uniform layers in sub- base / base course on well prepared surface and compacting with vibratory roller to achieve the desired density as per Codal Provision.**

Wet Mix Macadam :- This item is for Providing, laying, spreading and compacting graded stone aggregate to wet mix macadam specification including premixing the Material with water at OMC in

mechanical mix plant or at any convenient place and carriage of mixed Material by tipper / tractor or by any other means to site, laying in uniform layers with paver / grader / tractor paver in sub- base / base course on well prepared surface and compacting with vibratory / static roller to achieve the desired density as directed by engineer in charge of work.

(A) Supply of WMM

(B) Laying of WMM

**Item No.7 : Providing and Laying of Rubber Moulded Paver Block Grey/Coloured 60 mm thick, M-35 Grade of any size ; shape (Usually Uni-Paver Blocks) using black trap good quality aggregate of 20 mm nominal size for footpath, parking areas, service lanes and other areas as mentioned in the drawing / instruction of engineer in charge. Cost includes formworks using rubber mould, Rate providing and laying paver blocks as per required grading and specification. The paver block shall be mechanically compacted. The work of paving blocks shall be executed in line and level by skill mason of flooring work only. It should be laid in such a way that the no cutting of the paver block to be necessary. if cutting of paver block necessary then it should be cut by machine only and carting. The finished surface of the paver block shall have reasonably good, plain finished. Paver blocks shall be compacted and shall be relaid if necessary. Gravel or such type of materials shall not be allowed for production. Laying on 5cms thick sand bedding.**

**(Footpath Paver Block, Footpath curb, Central verge curb - Successful bidder of this tender shall have to purchase 50% of total quantity of Paver Blocks/ footpath curbs/Central verge curbs from Amdavad Enviro Projects Pvt. Ltd. directly. If quantity of 50% of Paverblock/Footpath curbs/Central verge curbs are not available Amdavad Enviro Projects Pvt. Ltd within stipulated period of time, contractor has to take prior permission for use of other than from Amdavad Enviro Projects Pvt. Ltd.Paver blocks/Footpath curbs/Central verge curbs. )**

The scope of work includes manufacturing, supplying and laying of precast paver blocks at various Retail outlets. The work includes :Verification of the existing site condition and advising our project in charge to lay suitable base course if required.

Contractors are required to satisfy themselves with quality of sub grade, sub -base course before the paver blocks are laid and suggest strengthening if required.

Clearing the site by removing all obstacles such as stones, debris etc. for laying of paver blocks.Manufacturing of paver blocks in your plant as per requirements in technical specification enclosed.Supplying of paver blocks at site, including handling at both ends.

Laying of paver blocks at site as per requirement in technical specification, within shortest possible time the site is public place hence care should be taken to ensure that the routine activities shall not be disturbed. The job of laying may required to be carried out during night also.

Testing of paver blocks through reputed Govt./Non Govt. Test house and submission of test results as per requirements in Technical Specifications. AMC reserves the right to carryout test at random. Cost for such tests to be borne by party.The contractor shall guarantee that all material and components designed, fabricated, supplied and laid by him shall be free from any type of defect due to faulty material and/or workmanship/erection for a period of One year from the date of completion of work. However, the contractor One years shall render free maintenance.

TECHNICAL SPECIFICATIONS :

## I) Paver Block Manufacturing Facilities :

The Paver Block shall be made in factory with following minimum facilities :

### 1.1 Concrete Block making Machines :

The machine should be capable of producing high quality Paver Blocks by obtaining high level of compaction by application of hydraulic compaction and also by high intensity vibration to the moulds. The machine should have automatic control panel for uniformity in strength.

### 1.2 Concrete Batching & Mixing Plant : (Not essential)

The concrete Mix Design should be followed for each batch of materials. The concrete ingredient should be mixed in concrete Batching & Mixing plant with minimum capacity of 30 cum/hour. The plant should be equipped with automatic control panel for maintaining water cement ratio from batch to batch to obtain concrete of uniform quality and strength.

The plant should be equipped with adequate mechanism for mechanized loading of raw materials into mixer and conveyor belt for transportation of concrete from mixer to concrete block making machine to maintain quality of wet cement.

Curing:

The factory should have well designed curing area to ensure adequate curing of paver blocks.

### 1.4 Laboratory (Desirable but not essential) :

The factory should have the following:

Compression testing machine of adequate capacity.

Other tools and equipment for testing raw materials and paver blocks.

(1). Systematic record of test results of various paver blocks manufactured in the factory.

(2). Concrete Mix Design for various grade of concrete used for making of paver blocks.

## II) SPECIFICATIONS FOR COLOURED PAVER BLOCKS :

Coloured concrete paver blocks shall be manufactured as per attached specifications using approved colour Pigment of "BAYER" Make "BAYFERROX IRONOXIDE PIGMENTS" with minimum colour pigment of 3% by weight of cement. The colour shade shall be "RED" as selected by AMC before commencement of the work. White cement shall be used for colored pavers to obtain the desired colour shade. The job also includes providing 50 mm thick sand bedding to match the shade of the paver block.

The colour of the paver block shall be guaranteed against fading of colour for period of 12 months from the date of laying of the same at site.

All other technical specifications & Procedure for testing, laying & sampling of coloured pavers will be as per attachment.

## III) PAVERS BLOCK CHARACTERISTICS :

The concrete pavers should have perpendicularities after release from the mould and the same should be retained until the laying.

The surface should be reasonably smooth and of anti skid and anti glare type.

The paver should have uniform chamfers to facilitate easy drainage surface run off.

The pavers should have uniform interlocking space of 2mm to 3mm to ensure compacted sand filling after vibration on the paver surface.

The concrete mix design should be followed for each batch of materials separately and automatic batching plant is to be used to achieve uniformity in strength and quality.

The pavers shall be manufactured in single layer only.

Skilled labour should be employed for laying blocks to ensure line and level of laying, desired shape of the surface and adequate compaction of the sand in the joints.

The pavers shall be of cement grey colour without any pigment & for coloured pavers refer "specifications for coloured pavers."

The pavers are to be skirted all round with kerbing using solid concrete blocks of size 150mm X 250mm X 380mm. The kerbing should be embedded for 100mm depth. The concrete used for kerbing shall be cured properly for 7 days minimum.

#### IV) Paver Block Dimensions :

Thickness 60mm Shape Unirregular (Uniform Shape with no Hollow Or Cracks) Uni, I shape, tri hex or directed by Addl .C.E.

Chamfer 4mm to 6mm along top edges Colour Natural cement grey colour without use of any pigment.

For coloured pavers refer "specifications for coloured pavers"

Dimensional

Tolerance

(+/-) 2mm for length & width,

(+/-) 3mm for Height (Thickness)

#### V) Testing of Paver Blocks :

SR.

NO.

\* TEST

#### SPECIFICATION

Average Values

(Average of Minimum

Five Samples/Site)

1. Compressive Strength Min. 35 N/Sqmm for 60mm

thick

2. Flexural Strength Minimum 4.5 N/Sqmm

3. Abrasion Resistance Maximum 1.5

4. Water Absorption Maximum 5.80%

5. Minimum Cement Content 380 Kg/Cum (Not Essential)

\* Sampling and Testing procedure as per enclosed specifications

## SAMPLING AND TESTING PROCEDURES FOR PAVER BLOCKS.

Sample Size :

INTERNAL – Average of minimum 3 samples per 5000 Blocks.

Essential – Minimum 2 Blocks per 10000 blocks..

### 1. Sampling For Testing

Sampling for testing of paver blocks shall be done in accordance with Appendix-A.

#### Compressive Strength

Testing for compressive strength shall be undertaken in accordance with Appendix-B.

The average compressive strength of the blocks tested shall be Min. 35 N/Sqmm.

#### Abrasion Resistance

Testing for abrasion shall be in accordance with IS 1237 (Specifications for Cement Concrete Floor Tiles) – Appendix C.

#### Flexural Strength

Testing for flexural shall be in accordance with IS 1237 (Specifications for Cement Concrete Floor Tiles) – Appendix D.

#### Water Absorption

Testing for water absorption shall be in accordance with IS 2185:1979 : Part I (Specifications for Concrete Masonry Units) – Appendix E.

### Appendix – A

Sampling of Paver blocks.

#### Method of sampling :

Before laying paver blocks, each designated section comprising not more than 50000 blocks, shall be divided into ten approximately equal groups. Three blocks shall be drawn from each group.

#### Marking and identification :

All samples shall be clearly marked at the time of sampling in such a way that the designated section of part thereof, and the consignment represented by the sample, are clearly defined.

The sample shall be dispatched to the approved test laboratory taking precaution to avoid damage to the paving in transit. Protect the paving from damage and contamination until they have been tested. The testing shall be carried as soon as possible, after the sample has been taken. As soon as practicable after sampling. The samples shall be stored in

water at 20 degree C  $\pm$  5 degree C for 24 hours prior to testing.

The mode of measurement shall be on Smt. basis.

**Item No.8 : Removing any kind of pavement incl. Stacking of serviceable material disposal of unserviceable material with 50 meter lead and lift.**

Removing any kind of pavement incl. Stacking of serviceable material disposal of unserviceable material with 50 meter lead and lift.

The mode of measurement shall be on Smt. basis.

**Item No.9 : Labour work for fixing any kind of paving with cement pointing in CM 1:2, including watering, ramming etc comp. as directed For pavement.**

Labour work for fixing any kind of paving with cement pointing in CM 1:2, including watering, ramming etc comp. as directed For pavement

(A) Laying on Sand bedding as per requirement to fix the C.C.Block / Nibhada Stone in Line & Level.

The mode of measurement shall be on smt. basis.

(B) For Water Table & Kerb on Sand bedding as per requirement to fix the C.C.Block / Nibhada Stone in Line & Level.

The mode of measurement shall be on Rmt. basis.

**Item No.10 : Supplying and fixing of 300 mm-L x 150 mm-B x 380 mm-H Kerb block for Footpath in M-20 grade using 20 mm nominal size black trap aggregate of Sevaliya/Timba or equivalent quality for pre-cast blocks, reasonably exposed finish/ formwork , mould with well equipped with vibratory system for kerb stones of approved design including curing, etc. complete, including the cost of formwork etc. complete. The rate shall also include necessary cutting of asphalt, fixing the Kerb stones in line and level on 5 cm thick sand bedding with necessary equipments and materials. The rate shall also include the flush pointing in CM (1:3) for all joints of the kerbstones. Filling of zari along the sides of the kerb stone fixed with Bituminous concrete mixed in proper position as directed by Engineer in charge to form a portable mixture. In any case Gravel or such type of materials shall not be allowed for production.a) Laying on 5 cm thick Sand Bedding.**

Trenches of specified width and depth shall first be made along the edges of the wearing course of the road or along the line of pave block flooring to receive the restraint block.

The bed of the trenches shall be compacted manually with steel rammers or a firm and even surface and then stones shall be set in sand bedding

The edge restraint blocks shall be laid with their length running parallel to the paving edge, true in line and gradient.

The joints of blocks shall be not more than 2 mm and filled with the CM 1:2 (1 cement : 2 fine sand/) which shall be cured for 7 days.

Finishing

The edge shall be restored and all surplus earth including rubbish etc. disposed off as directed by the engineer in charge.

Measurement



Length of the finished work shall be measured in running meter along the edge of the paving correct to a cm. Rate The rate shall include the cost of the materials and labour including stone of specified materials involved in all the operation described above.

**Item No.11 : Supplying and fixing of 380 mm H x 300 mm L x 200 mm B Kerb block for Central Verge in M-20 grade using 20 mm nominal size black trap aggregate of Sevaliya/Timba or equivalent quality for pre-cast blocks, reasonably exposed finish/ formwork, mould with well equipped with vibratory system for kerb stones of approved design including curing, etc. complete, including the cost of formwork etc. complete. The rate shall also include necessary cutting of asphalt, fixing the Kerb stones in line and level on 5 cm thick sand bedding with necessary equipments and materials. The rate shall also include the flush pointing in CM (1:3) for all joints of the kerbstones. Filling of zari along the sides of the kerb stone fixed with Bituminous concrete mixed in proper position as directed by Engineer in change to form a portable mixture. In any case Gravel or such type of materials shall not be allowed for production.(AMC approved Rate )a) Laying on 5 cm thick Sand Bedding.**

Supplying and fixing M-20 grade using black trap aggregate of Sevaliya/Timba or equivalent quality 20 mm. nominal size for pre-cast reasonably exposed finish/, formwork using mould with well equipped with vibratory system for kerb stones of approved design including curing, etc. complete, including the cost of formwork etc. complete. The rate shall also include excavation and erecting and fixing the kerbs in position with necessary equipments and materials. The rate shall also include the flush pointing in CM (1:3) for all joints including kerb stones of approval design (Sample must be got approved). In any case Gravel or such type of materials shall not be allowed for production .a) Laying on 5 Cms thick Sand Bedding Kerb Stone Fixing 300mm-L x 150mm-B x 380mm-H :-

Supplying and fixing M-20 grade using black trap aggregate of Sevaliya/Timba or equivalent quality 20 mm. nominal size for pre-cast reasonably exposed finish/, formwork using mould with well equipped with vibratory system for kerb stones of approved design including curing, etc. complete, including the cost of formwork etc. complete. The rate shall also include excavation and erecting and fixing the kerbs in position with necessary equipments and materials. The rate shall also include the flush pointing in CM (1:3) for all joints including kerb stones of approval design (Sample must be got approved). In any case Gravel or such type of materials shall not be allowed for production. a) Laying on 5 Cms thick Sand Bedding

Materials :

Water shall conform to M-1. Cement to M-2. Sand to M-5. Grit to M-7. Graded stone aggregate 20 mm. nominal size to M-10

**General :**

Contractor shall have to manufacture the blocks as per the dimensions given in the drawing. Specific machineries shall be used to manufacture the Precast blocks. These machineries should be compatible to produce blocks of required strength and dimensions. The machine shall contain hydraulic Press or advanced equipment to generate required compaction & Grade and finish. Moulds/ Steel Plates/ Dies of the machine shall be dimensionally checked & to be got approved before commencing the production. Contractor shall prepare proper Drying Yard for keeping the blocks before curing. The drying yard shall be levelled and covered so that no shrinkage cracks are formed. Contractor shall prepare adequate size curing pond to cure the blocks for not less than 21 Days. No other means of curing shall be allowed. The technical specification of concrete shall confirm to IS 456-2000. The concrete mix is not required to be designed and only nominal mix as per IS : 456-2000 shall be followed. The proportion of the concrete mix shall be 1:1.5:3 (1 cement : 1.5 coarse sand : 3

graded stone aggregate 20 mm. nominal size) by volume. Concrete work shall have fairly exposed concrete surface or as specified in the item. The designation ordinary M-10, M-15, M-20, M-25 specified as per I.S. corresponds approximately to 1:3:6, 1:2:4, 1:1.5:3 and 1:1:2 nominal mix of ordinary concrete, by volume respectively. The ingredients required for ordinary concrete containing one bag of cement of 50 Kg. by weight (0.0342 m<sup>3</sup>.) for different proportions of mix shall be as per IS 456-2000. The proportion of the aggregate for the kerb stone shall be modified as per the approval of the engineer-in-charge. The water cement ratios shall not be more than those specified as per IS. The cement of the mix shall be increased, if the quantity of water in a mix has to be increased to overcome the difficulties of placement and compaction so that the water cement ratio specified in the table is not exceeded. The maximum size of coarse aggregate shall be as large as possible within the limits specified but in no case greater than 1/4th of the minimum thickness of the member, provided that the concrete can be placed without difficulty so as to surround all reinforcement thoroughly and to fill the corners of the form. For reinforced concrete work, coarse aggregates having a nominal size of 20 mm. are generally considered satisfactory. Admixture shall be used in concrete only with approval of the Engineer-in-charge based upon the evidence that with the passage of time, neither the compressive strength of concrete is reduced nor are other requisite qualities of concrete impaired by the use of such admixtures.

#### Proportioning:

Proportioning shall be done by volume, except cement which shall be measured in terms of bags of 50 Kg. weight. The volume of one such bag being taken as 0.0342 m<sup>3</sup>. Boxes of suitable sizes shall be used for measuring sand and aggregate. The size of the boxes (internal) shall be 30cm. x 30 cm. and 38 cm. deep. While measuring the aggregate and sand, the box shall be filled without shaking ramming or hammering. The proportioning of sand shall be on the basis of its dry volume and in case of damp sand, allowances for bulk age shall be made.

#### Mixing :

For all work, concrete shall be mixed in a mechanical mixer which along with other accessories shall be kept in first class working condition and maintained throughout the construction. Measured quantity of aggregate, sand and cement required for each batch shall be poured into the drum of the mechanical mixer while it is continuously running. After about half a minute of dry-mixing, measured quantity of water required for each batch of concrete mix shall be added gradually and mixing continued for another one and a half minute. Mixing shall be continued till materials are uniformly distributed and uniform colour of the entire mass is obtained and each individual particle of the coarse aggregate shows complete coating of mortar containing its proportionate amount of cement. In no case shall the mixing be done for less than 2 minutes after all ingredients have been put into the mixer. Mixers which have been out of use for more than 30 minutes shall be thoroughly cleaned before putting in a new batch. Unless otherwise agreed to by the Engineer-in-charge, the first batch of concrete from the mixture shall contain only 2/3rds of normal quantity of coarse aggregate. Mixing plant shall be thoroughly cleaned before changing from one type of cement to another.

#### Consistency :

The degree of consistency which shall depend upon the nature of the work and methods of vibration of concrete, shall be determined by regular slump tests in accordance with IS : 1199-1959. The slump of 10 mm. to 25 mm. shall be adopted when vibrators are used.

#### Inspection :

All Moulds shall be cleaned and made free from standing water, dust, snow or ice immediately before placing of concrete.

Formwork/Metal Mould for exposed concrete surface (If indicated):

All the moulds shall be checked for exact dimensions of the Precast blocks. All the edges of the Precast blocks shall confirm the profile of the final drawing & edges/ curvatures of the moulds shall be checked accordingly. Moulds shall be regularly checked for correctness of dimensions of Blocks, twists, bends due to handling, etc.. before starting every days work.

Care shall be taken to set all formwork/Mould in perfect line, level (or in required camber or slope as specified) and plumb. Formwork/Mould propping shall be strong, rigid and sturdy. The formwork/Mould shall be as per pattern & design shown in drawings. Formwork/Mould shall be done accurately and precisely so as to achieve neat, clean and smooth concrete surface, in line, level and plumb. Clinks, twists, offsets, warps, riveting etc. in plates or forms shall not be allowed. Before placing concrete, forms shall be thoroughly cleaned off of all rust, dust and loose materials. Colorless oil or grease of approved quality shall be applied before placing steel. Also the formwork material will be of wood/plywood/steel or any sort of such material, as approved by the Engineer in charge, so that all exposed concrete surfaces have uniform colour.

For all kind of exposed concrete work only one brand (to be approved by the Engineer-in charge) of cement shall be used.

Removal of Moulds: Specific time shall be identified for removal of moulds, such that the concrete of the Precast blocks shall gain strength to withstand the stresses generated due to self weight and handling to drying yards without any deformation to shape/ dimensions/ edges.

Drying Period: Sufficient time shall be given to the block after it is removed from the mould so that it can gain strength and dry in shade to prevent any cracks due to shrinkage. This shall be done in drying yards.

#### Curing Period:

Curing of block shall be done only in curing pond and curing shall be done for minimum 14 days.

Drying period after removing from pond & before delivery to site:

Water should be drained off from the block before it is actually sent to the site. Time should be provided for proper draining of water which may be present in the block kept for curing in the pond.

#### Precautions:

Precaution shall be taken while transporting of the blocks to site.

The blocks should be loaded and unloaded with due care so as to avoid generation of stresses leading to breaking of block. Care should be taken to prevent the block from breaking during transporting.

#### Fixing:

The pits of the size 0.15 M in width and required depth shall first be excavated, true to line and level. The relevant specifications of item A- 1 shall be followed for excavation work. The pits shall be filled with a layer of 0.05 M. thick sand bedding. The curbs then shall be placed in position of which 50mm. shall be below road. Care should be taken to maintain proper line and level. The joints between the kerbs shall be pointed with C.M. 1:2 and cured for minimum seven days.

#### Sampling and testing of concrete:

Samples from fresh concrete shall be taken as per IS : 1199-1959 and cubes shall be made, cured and tested at 7 days or 28 days as per requirements in accordance with IS : 516-1959. A random sampling procedure shall be adopted to ensure that each concrete batch shall have a reasonable chance of being tested i.e. the sampling should be spread over the entire period of concreting and cover all mixing units.

#### NOTE:

At least 1 sample shall be taken from each shift. Ten test specimens shall be made from each sample, 5 for testing at 7 days and the remaining 5 at 28 days. The samples of concrete shall be taken on each day of the concreting as per above frequency. The number of specimens may be suitably increased as deemed necessary by the Engineer-in-charge when procedure of tests given above reveals a poor quality of concrete and in other special cases. The average strength of the group of cubes cast for each day shall not be less than the specified cube strength of 200 Kg/cm<sup>2</sup>. at 28 days. 20% of the cubes cast for each day may have value less than the specified strength provided the lowest value is not less than 85% of the specified strength. If the concrete made in accordance with the proportions given for a particular grade, does not yield the specified strength, such concrete shall be classified as belonging to the appropriate lower grade. Concrete made in accordance with the proportions given for a particular grade shall not, however, be placed in a higher grade on the ground that the test strength are higher than the minimum specified. If rock pockets/honeycombs in the opinion of Engineer-in-charge are of such an extent or character so as to effect the strength of the structure, materially or to endanger the life of the steel reinforcement, he may declare the concrete defective and require the removal and replacement of the portion of the structure affected.

#### Precast Kerb Stones :

The relevant specifications of concreting as per item above shall be followed except that work shall be carried out for precast concrete kerb stones as specified in the item. All Precast members shall be cast at workshop. Sufficient curing shall be done before placement of the same. The method of transporting and placing the precast members shall be as approved by the Engineer-in-charge. Members shall be so transported that no breakage or undue stresses are induced in them. If required, all members shall have a key provided on both the faces i.e. top and bottom surfaces, of adequate size so as to fill the same with concrete while laying. The function of this key is to avoid the leakage through the joint between the precast member and the member on which it is laid.

Mode of Measurements and Payment :

The rate shall include cost of formwork but exclude the cost of reinforcement. The volume occupied by reinforcement shall not be deducted from R.C.C. work.

Mode of measurements and payment: The rate shall be for a unit of Rmt.

**Item No.12 : Providing and laying cement concrete 1:2:4 (1-Cement: 2-Coarsesand :4-graded stone aggregates 20 mm nominal size) for reinforced concrete including finishing the exposed surfaces with cement mortar 1:3 (1-cement, 3 Finesand) to give a smooth and even surface centering and formwork and curing complete excluding cost of reinforcement.(upto10 ton)**

Providing and laying cement concrete 1:2:4 (1-Cement: 2-Coarsesand :4-graded stone aggregates 20 mm nominal size) for reinforced concrete including finishing the exposed surfaces with cement mortar 1:3 (1-cement, 3 Finesand) to give a smooth and even surface centering and formwork and curing complete excluding cost of reinforcement.(upto10 ton)

The mode of measurement shall be on Cmt. basis.

**Item No.14 : Providing & Fixing M.S.grill, gate, elevation element of Decorative pattern with M.S.Channel, flat, medium grade m.s.pipe, square or round bars with round headed bolts, nuts or by screw.incl. applying one coat zinc primer and two coat of oil paint etc.comp.**

Providing & Fixing M.S.grill, gate, elevation element of Decorative pattern with M.S.Channel, flat, medium grade m.s.pipe, square or round bars with round headed bolts, nuts or by screw.incl. applying one coat zinc primer and two coat of oil paint etc.comp.

The mode of measurement shall be on Kg. basis.

**Item No.15 : Providing & Supplying JCB Machine on rental basis in case of emergency situation and break down type work & also during unavoidable condition as per instruction of engg.incharge, rate includes all nece. shifting, fuel and operating charges and stacking of useful & non-useful materials separately up to store. (No payment should be allowed for non working condition of machinery and for pipe line excavation and laying work)**

Providing & Supplying JCB Machine on rental basis in case of emergency situation and break down type work & also during unavoidable condition as per instruction of engg.incharge, rate includes all nece. shifting, fuel and operating charges and stacking of useful & non-useful materials separately up to store. (No payment should be allowed for non working condition of machinery and for pipe line excavation and laying work) ( Based on Previously approved rate by C E sir )

The mode of measurement shall be on Hr. basis.

**Item No.16 : Supplying Pneumatic Breaker Machine for RCC Slab or Asphalt Demolishing Work on site by using Operator, fuel, power Supply etc. Complete as Directed. (No payment should be allowed for non working condition of machinery and for pipe line excavation and M.H. work. Allowed only for break down work)**

Supplying Pneumatic Breaker Machine for RCC Slab or Asphalt Demolishing Work on site by using Operator, fuel, power Supply etc. Complete as Directed. (No payment should be allowed for non working condition of machinery and for pipe line excavation and M.H. work. Allowed only for break down work)

The mode of measurement shall be on Hr. basis.

**Item No.-17 Reinstatement work for Central verge and footpath Kerb Stone**

Reinstatement work for Central verge and footpath Kerb Stone

The M/s shall be on RMT. Basis

**Item No -18 Providing, supplying and fixing precast C.C. blocks (M-20) edge kerb having size of 75 x 300 x 300 mm depth and as per design conveying it to the site, jointing into C:M 1:3 and racking out the joints incl. necessary excavation of asphalt, soil etc. completed.**

Providing, supplying and fixing precast C.C. blocks (M-20) edge kerb having size of 75 x 300 x 300 mm depth and as per design conveying it to the site, jointing into C:M 1:3 and racking out the joints incl. necessary excavation of asphalt, soil etc. completed.

The M/s shall be Rmt. basis.

In Case Of Where is no technical specification for the any Items available follow specification as per MORTH and Engi.Incharge shallbe followed and for the same I agree to abide by them

**Item No -19 Painting Two Coats on divider and footpath curb surface / New Concrete Surface ( Painting two coats after filling the surface with synthetic enamel paint in all shades on new plastered concrete surfaces)**

Painting Two Coats on divider and footpath curb surface / New Concrete Surface ( Painting two coats after filling the surface with synthetic enamel paint in all shades on new plastered concrete surfaces) (AMC approved Rate )

The M/s shall be on SMT. Basis

**Item No -20 Brick work using common burnt clay building bricks having crushing strength not less than 35kg./Sq.Cm. In foundation and plinth in Cement Mortar 1:5.(1-Cement: 5 -fine sand)(B) Conventional.**

Brick work using common burnt clay building bricks having crushing strength not less than 35kg./Sq.Cm. In foundation and plinth in Cement Mortar 1:5.(1-Cement: 5 -fine sand)(B) Conventional.The M/s shall be on CMT. Basis

**Item No -21 Repairing damaged M.H. and rasing M.H. up to road level incl. removing damaged brick work and repairing by brick masonry in C.M. 1:5 and plaster in C.M. 1:3 and fixing C.I. steps and existing MH sheet cover, removing the debris from MH and carting the same as directed.**

Repairing damaged M.H. and rasing M.H. up to road level incl. removing damaged brick work and repairing by brick masonry in C.M. 1:5 and plaster in C.M. 1:3 and fixing C.I. steps and existing MH sheet cover, removing the debris

from MH and carting the same as directed. (Based on Drainage SOR 2009-10)

(A) up to 0.15 mt. (@ Two Coarse)

(B) up to 0.35mt. (@ Four Coarse)

The M/s shall be on Nos. Basis

**Item No -22 Providing & laying Mountable type Central Verge including casting of Kerb of size 15.00 x 32.50 Cm by mechanical Kerb casting machinery and oil paint colour to Center verge (Kerb) by Yellow/white and Black patta (Three Coat) one coat of priming & two coat of oil Paint including**

**cost of material required for paint and all labourworketc complete as per direction, detailed drawing and instruction of engineer incharge .(Including Epoxy Piant of Approved Quality) (Central Verge)**

Providing & laying Mountable type Central Verge including casting of Kerb of size 15.00 x 32.50 Cm by mechanical Kerb casting machinery and oil paint colour to Center verge (Kerb) by Yellow/white and Black patta (Three Coat) one coat of priming & two coat of oil Paint including cost of material required for paint and all labourworketc complete as per direction, detailed drawing and instruction of engineer incharge .(Including Epoxy Piant of Approved Quality) (Central Verge) Rate Anlaysis as per AUDA tender.

The M/s shall be on Rmt. Basis

**Item No -23 Excavation of asphalt pavement etc. in line and level of any thickness with all sub layer including demolishing the asphalt carpet, metal, soiling etc. Rate is inclusive of Cutting the periphery of the area for patchwork using any type of road cutter Maschine & removing asphalt or sub layer within the area of patchwork using Breaker Maschine & Making the Surface ready for Patchwork. The rate includes of Operator, fuel, transportation & Maintenance of Machine (cutter & Breaker) etc complete. The item Shall be executed as perinstruction. as per engg.in Charge.**

Excavation of asphalt pavement etc. in line and level of any thickness with all sub layer including demolishing the asphalt carpet, metal, soiling etc. Rate is inclusive of Cutting the periphery of the area for patchwork using any type of road cutter Maschine & removing asphalt or sub layer within the area of patchwork using Breaker Maschine & Making the Surface ready for Patchwork. The rate includes of Operator, fuel, transportation & Maintenance of Machine (cutter & Breaker) etc complete. The item Shall be executed as perinstruction. as per engg.in Charge.

The M/s shall be on Smt. Basis

**I HAVE ALSO GONE THROUGH TECHNICAL SPECIFICATIONS FOR THE ITEMS (AS PER STANDARD**

**P.W.D. TECHNICAL SPECIFICATIONS FOR THE ITEMS AND ALSO I HAVE THE BOOK OF THE SAME )**

**AND AGREE TO ABIDE BY THEM.**

**INCASE OF WHERE IS NO TECHNICAL SPECIFICATION FOR THE ANY ITEMS AVAILABLE ,  
SPECIFICATION GIVEN BY THE ENGINEER IN CHARGE SHALL BE FOLOWED AND FOR THE  
SAME I AGREE TO ABIDE BY THEM.**

**Contractor's Signature  
& Stamp**

**Addl. City Engineer  
(South West Zone)**

**Mobile No**

Tender No : 29

Tender Notice No : 05/2026-27

## PRICE QUOTATION SHEET

Earnet Money Rs. : 9986.00

Date of Submission of Tender : Dt. 29.06.2026, Time : 18:00 Hrs.

Tender Fee Rs. 900.00

Date of Opening of Tender : Dt. 30.06.2026, Time : 17:00 Hrs.

Tender Class E2 or Above

**Name of Work : Road Grouting work in different TP Roads and Breakdown site in jodhpur ward, South west zone AMC.(Reinvite)**

**Estimated Tender Amount Rs. 9,98,562.00**

I / We am / are willing to carry out work at \_\_\_\_\_ % above / below\* percent (should be written in figures and words) of the estimated cost, as mentioned above. Amount of my / our tender works out for Rs. \_\_\_\_\_ (in figures)  
Rupees \_\_\_\_\_ (in words)

Note : \* Please strike out above or below, whichever is not applicable.

Contractor's Signature  
& Stamp

Addl. City Engineer  
(South West Zone)

Mobile No



AHMEDABAD MUNICIPAL CORPORATION					
MAHANAGAR SEVA SADAN					
SOUTH WEST ZONE					
ABSTRACT SHEET					
<b>Name of work :</b> Road Grouting work in different TP Roads and Breakdown site in jodhpur ward, South west zone AMC					
Sr.	Quantity	Item Description	Rate in Rs.	Per	Amount in Rs.
1	420	Box cutting the road surface in all sorts of soil, murrum to proper slope & camber for making a base for road work including removing the excavated stuff & depositing on the road side as directed upto 50.00 mt. Lead.	205.4	Cmt.	86247
2		Extra rate over item of excavation of earth for excavation of asphalt pavement / RCC of thickness up to 0.20 meter including demolishing the asphalt carpet, metal,s oiling/cutting Reinforcement etc.comp. with stacking the material as directed.			
	25	up to 0.20 meter thickness (By Manual)	71.1	Smt	1777.5
3		Conveyance charge of earth, lime, murrum, building rubbish, manure, garbage, sludge, excavated rock, fly ash, aggregates of any kind Including spreading & levelling etc. complete.			
	50	a) Lead from 4 Km.to 5 km	100.4	Cmt	5022
	250	b) Lead from 5 Km.to 10 km	146.7	Cmt	36685
	167.139	c) Lead from 10 Km.to 15 km	187.7	Cmt	31378.59889
4	260	Rolling of Earth Work in layers with power roller including filling in depressions which occurs during the process.	13.27	Cmt	3450.2
5	260	Watering of Earth as Directed.	8.99	Cmt	2337.4
6	260	Supplying of graded hand broken stone size of 90 mm to 127 mm at site (Rubble or Spoul)	983.9	Cmt	255821.8

7	2100	Labour charges for spreading the spouls 127 mm thick layer good earth filling in voids correcting the grade & camber comp. with rolling, watering, incl. preparing the surface by brushing for removing all loose or dirt ect.comp.	26.79	Smt	56259
8	170	Supply of graded machine cut black trap stone aggregate (metal) of Sevaliya / Tima or equivalent quality metal of size 25 mm to 40 mm.	981.3	Cmt	166812.5
9	2100	Labour work for spreading the metal 85 mm thick in single layer, incl. providing & applying bitumen for semi grouting 2.5 kgs/sqm. & Providing & spreading the key black trap aggregate of good quality on top at the rate of 0.013 cmt. per sq.m. of size 18 mm passing in 9.5 mm retain rolling with 10 tonne roller etc. comp. as directed.	158.4	Smt	332619
10		Repairing damaged M.H. and rasing M.H. up to road level incl. removing damaged brick work and repairing by brick masonry in C.M. 1:5 and plaster in C.M. 1:3 and fixing C.I. steps and existing MH sheet cover, removing the debris from MH and carting the same as directed.			
	20	(A) up to 0.15 mt. (@ Two Coarse)	721.6	No.	14432
	5	(B) up to 0.35mt. (@ Four Coarse)	1144	No.	5720
		<b>Total Rs.</b>		<b>:-</b>	<b>998562.00</b>

**I/We am/are willing to carry out the work at \_\_\_\_\_% above/below \_\_\_\_\_% (should be written in figures and words below/above the estimated rates mentioned above. Amount of my/our tender works out as under:**

**Notes :**

- 1) % above / below is to be submitted online only.**
- 2) All work shall be carried out as per the specifications or as directed.**
- 3) Rates quoted include cleaning of site (prior to commencement of work and at its close) in all respects and hold formwork under all conditions, site moisture, weather, etc..**

- 4) All the item rate are considering excluding cost of GST as per Government of Gujarat Road And Building Dept. Reso. No. TNC/102022/457/C Dt.05/04/2022. So, bidder shall be consider this change in BOQ

**Seal and Signature of the Bidder**

**Addl. City Engineer**

**(SOUTH WEST ZONE)**