

Name of work :- Construction of Different Anganwadi Centre /PKG-06/at Ta.Mansa, Dist.Gandhinagar (1) Aluva-2 (Varshoda) (2) Indrapura-1 (Itadra) (3) Itadra-7 (Itadra)

Bill Of Quantities

Memorandum showing items works to be carried out :

Item No	Description of Item (with brief specification and reference to book of specifications)	Quantity	Unit	Rate In figures	Amount
1	2	3	4	5	6
1	Excavation for foundation upto 1.50mt.Depth including sorting out and stacking of useful materials and disposing of the excavated stuff as directed with in all lead & Lift (A) Loose or Soft soil.	99.00	Cu.m	123.13	12189.87
2	Excavation for foundation upto 1.50mt.Depth including sorting out and stacking of useful materials and disposing of the excavated stuff as directed with in all lead & Lift (B) Dense or Hard soil.	26.10	Cu.m	157.16	4101.88
3	Filling foundation and plinth with sand under floors including watering, ramming and consolidating dressing etc, comp.	27.00	Cu.m	481.70	13005.90
4	Filling available excavated earth excluding rock in trenches plinth side of foundation etc. in layer not exceeding 20cm. In depth consolidation each deposited layer by ramming and watering.	75.06	Cu.m	136.92	10277.22
5	Filling foundation and plinth with murrum or selected soil in layers of 20 cm. thickness including watering, ramming and consolidating etc. comp.	48.00	Cu.m	277.14	13302.72
6	Applying general insecticide pest control treatment to floors, cupboards etc including labour materials etc. complete. Using Imidacloprid 30.5 SCas Per IS 6313 part - II((0.075% concentration by mass) is recommended 10.5ml chemical diluted with 5 liters of water application 0.5 litre chemical /Sqm of surface is recommended as per I.S	129.00	Sqm	91.63	11820.27
7	Providing and laying cement concrete 1:2:4 (1- Cement : 2- Coarse sand : 4- graded stone aggregates 20 mm nominal size) and curing complete including cost of formwork in (A) Foundation and Plinth	7.80	Cu.m	4365.22	34048.72
8	Providing and laying cement concret 1:1.5:3 (1 Cement : 1.5 coarse sand : 3 graded stone aggregate 20mm nominal size) and curing complete excludng cost of form work and reinforcement for reinforced cement concrete work in (a) Foundation footing base of column and mass concrete	8.70	Cu.m	5457.03	47476.16
9	Providing and laying nominal cement concrete M-200 in R.C.C. 1:1 1/2 :3 (1 cement :1 1/2 coarse sand : 3 graded stone aggregate 20 mm. Nominal size) including finishing smooth with curing complete including the cost of form work but excluding the cost of reinforcement for R.C.C. work in column Upto plinth level.	6.00	Cu.m	8445.62	50673.72
10	Providing & laying cement concrete 1: 3 : 6 (1 Cement : 3 Coarse sand : 6 graded B.T stone aggregate 20mm nominal size) Curing comp. including cost of form work in foundation and plinth.	36.00	Cu.m	3396.68	122280.48
11	Providing and laying nominal cement concrete M-200 in R.C.C. 1:1 1/2 :3 (1 cement :1 1/2 coarse sand : 3 graded stone agregate 20 mm. Nominal size) including finishing smooth with curing complete including the cost of form work but excluding the cost of reinforcement for R.C.C. work in column for All Floor	6.90	Cu.m	10331.36	71286.38
12	Providing and laying nominal cement concrete M-200 in R.C.C. 1:1 1/2 :3 (1 cement :1 1/2 coarse sand : 3 graded stone aggregate 20 mm. Nominal size) including finishing smooth with curing complete including the cost of form work but excluding the cost of reinforcement for R.C.C. work (c) PLINTH BEAM	9.30	Cu.m	6285.23	58452.64
13	Providing and laying nominal cement concrete M-150 in R.C.C. 1:2 :4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm. Nominal size) including finishing smooth with curing complete including the cost of form work but excluding the cost of reinforcement for R.C.C. work PLINTH Slab	9.60	Cu.m	4499.55	43195.68
14	Providing and laying nominal cement concrete M-200 in R.C.C. 1: 1 1/2 : 3 (1 cement :1/2 coarse sand : 3 graded stone agregate 20 mm. Nominal size) including finishing smooth with curing complete including the cost of form work but excluding the cost of reinforcement for R.C.C. work in BEAMS For All Floor.	9.30	Cu.m	6964.03	64765.48
15	Providing and laying nominal cement concrete M-200 in R.C.C. 1: 1 1/2 : 3 (1 cement :1/2 coarse sand : 3 graded stone agregate 20 mm. Nominal size) including finishing smooth with curing complete including the cost of form work but excluding the cost of reinforcement for R.C.C. work in LINTELS All Floor.	3.90	Cu.m	7643.22	29808.56
16	Providing and laying nominal cement concrete M-200 in R.C.C. 1: 1 1/2 : 3 (1 cement :1 1/2 coarse sand : 3 graded stone agregate 20 mm. Nominal size) including finishing smooth with curing complete including the cost of form work but excluding the cost of reinforcement for R.C.C. work in CHHAJJAS All Floor.	0.90	Cu.m	6862.33	6176.10
17	Providing and laying nominal cement concrete M-200 in R.C.C. 1: 1 1/2 : 3 (1 cement :1 1/2 coarse sand : 3 graded stone agregate 20 mm. Nominal size) including finishing smooth with curing complete including the cost of form work but excluding the cost of reinforcement for R.C.C. work in slabs for All Floor.	27.00	Cu.m	6508.30	175724.10
18	Providing T.M.T. bar FE500/500D reinforcement confirmed to for R.C.C. work including bending, binding, and placing. In position comp. Up to floor two level. For All Floor	9090.00	Kg	77.29	702566.10
19	Brick work using common burnt clay building bricks having crushing strength not less than 35 Kg./Sq.m. in foundation and plinth in cement mortar 1:6 (1 cement:6 fine sand) (b) Conventional.	33.00	Cu.m	4214.09	139064.97
20	Brick work using common burnt clay building bricks having crushing strength not less than 35 Kg./Sqm. in cement mortar 1:6 (1 cement : 6 Fine sand) in super structure above plinth level upto floor two level (for G.F) Conventional	63.00	Cu.m	4502.81	283677.03
21	Half brick masonry in common burnt clay building bricks having crushing strength not less than 35kg./sq.cm. in cement mortar 1:3 (1 cement : 3 coarse sand) with 2nos. of 6mm dia mild steel round bars every three coarse embedded in cement mortar in superstructure for Ground floor (Conventional)	18.00	Sqm	752.30	13541.40

Item No	Description of Item (with brief specification and reference to book of specifications)	Quantity	Unit	Rate In figures	Amount
1	2	3	4	5	6
22	Providing and fixing door Single shutter having factory fabricated std. Extruded aluminium colour anodized hollow section {Section 63.50 x 38 mm x 2.50 mm thick } for door frame, hollow portion of door frame shall be filled with wood to be insert for durable grip of door hinges, with factory made 38 mm.thick flush door both side pre laminated with 6 Lever Mortice lock , SS Aldrop 30cm long, SS Handle size 15 Cm Long, Tower Bolt size 20 cm etc. as per detail colour & pattern approved by this office including necessary anodized alluminum fixtures and fastenings.	17.10	Sqm	6386.23	109204.53
23	Providing and fixing Anodized Alluminum Section Jindal Deluxe Sliding Window System C (20mm) series sction memebers THREE track window section bottom track 21651, frame top & side 21650, shutter frame top rail 20530, bottom rail 20529, side rail 20544, lock rail 20531 with 5mm thick transparent plain float glass, with transparent silicon sealant with allu. anosized coated fittings and fixture etc complete	14.40	Sqm	3903.65	56212.56
24	Providing and fixing standared extruded of alluminium section of size 63mm x 38.10mm x 1.2mm @ Wt. 0.643 Kg/mt) with colour anodized alluminium frame for ventilation with 5 mm thick frosted glass as details etc complete for Ventilation { Colour as directed by Engineer in charge except black & Alluminum section and glass	12.60	Sqm	1175.56	14812.06
25	Providing and fixing Safty grills of required pattern for windows 12mm dia M.S. round Bar at required spacing M.S. Flat 25mm x 5mm thick as per design and hold fasting with coach bolts including one coat of primer and Shall be Painting with Enamel Paint and Colour approved by as per site Engineer etc complete.	540.00	Kgs	111.40	60156.00
26	Providing and laying Machine cut, Free edges, Machine polished Granite stone slab 18 mm thick {Single piece not more than 150 cm } for stair steps and riser as per design incl. full moulded round front edge & 1 cm nosing & necessary groove on trade of steps laid on 20 mm thick cement mortar 1:6 (1 -cement : 6 coarse sand) jointed with grey cement slurry including rubbing and polishing etc. complete	39.00	Sqm	3280.48	127938.72
27	Providing and laying Both side mirror polished Granite stone slab 18 mm (Average) thick of approved quality incl. full moulded round front edge fixed in wall for Shalves and jointed with grey cement slurry including rubbing and polishing etc. complete	18.00	Sqm	1968.49	35432.82
28	Providing and laying 60 x 60cm Soluble Salt Vitrified tiles 8 to 10 mm thick with pattern colour & Shade as detailed approve by architect (10% Dark colour tiles Pattern) in flooring treads of steps and landing laid on a bed of 12mm thick cement mortar 1:3 (1-cement : 3-coarse sand) finishing with flush pointing in white cement.	204.00	Sqm	1120.36	228553.44
29	Providing and laying 60 x 60cm Soluble salt Vitrified tiles 8 to 10 mm thick with pattern colour & Shade as detailed approve by architect (10% Dark colour tiles Pattern) in skirting risers of steps and dedo on 10mm thick cement plaster 1:3 (1-cement : 3-coarse sand) and jointed with white cement slurry	15.00	Sqm	1114.09	16711.35
30	Providing and laying 30cm x 30cm in size Ceramic tiles 6mm thick in flooring treads of steps and landing laid on a bed of 12mm thick cement mortar 1:3 (1-cement : 3-coarse sand) finishing with flush pointing in white cement	6.00	Sqm	1017.30	6103.80
31	Providing and laying 30 x 60Cm size premium printed glazed tiles 6mm thick in skirting risers of steps and dedo on 10mm thick cement plaster 1:3 (1-cement : 3-coarse sand) and jointed with white cement slurry	36.00	Sqm	1074.00	38664.00
32	Providing and filling the joint with epoxy grout 3 mm width and 8 to 10 mm deep, including cost of necessary materials, PVC spacers, filling grout and cleaning etc complete as directed by engineer in charge. { Colour and Pattern as Directed by engineer in charge. }	42.00	Sqm	40.40	1696.80
33	Providing and fixing pre-cast Rubber Dye / steel Dye inter locking concrete block 60mm thick with grade of concrete M300 pneumatic compressed / vibrated mechanically and as per approved design Confirming to IS 15658 : 2006 including 35 mm Sand layer for levelling and filling the joint with sand in proper line and level as per guidelines of IRC : SP 63-2018 etc. Complete	48.00	Sqm	706.90	33931.20
34	Providing and laying water proofing tretment with chaina mosaic tiles flooring over avg 40 mm C.C. 1:2:4 (1 Cement, 2 sand, 1 Kapchi 20mm + 3 grit 6mm to 10mm) bedding for maintaining slope for plain and curve surface & 12 mm to 20 mm of broken piece of ceramic / glazed tiles (one or more color as directed) to be laid over cement mortar bedding of C M 1:3 (1 cement : 3 sand) containg one Kg. of water proofing materials per bag of O P C at plain or / and slops and to be tempered to bring mortar ceramic up to surface with using white cement and colour pigment including rounding of junctions and extending them up to 15 cm along the wall and curing with bends any pattens or design as per drawing and cleaning by using oxalic acid etc complete.	195.00	Sqm	1102.92	215069.40
35	Providing and laying Mirror polished Machine polished Grenite stone slab 18mm (Average) thick for doors & windows sill & Jams clading as per design including full moulded round front steps & 1cm nosing & necessary groove on trades of steps ;laid on 20mm thick cement mortar 1:6 (1 cement : 6 coarse sand) jointed with gray cement slurry including rubbing and polsihing etc. complete.for Doors / windows sill & jams clading.	24.00	Sqm	3395.62	81494.88
36	Providing 20 mm thick double coat mala cement plaster on interior brick / concrete work for plastering comprising of base coat of 12 mm thick cement plaster in cement mortar (1 Cement : 4 coarse sand) in rough finishing and 8 mm thick top coat of cement mortar 1:2 (1 Cement : 2 Coarse sand) finished with trowel including scaffolding curing etc. complete. For Ground Floor	309.00	Sqm	286.10	88404.90
37	Providing 10mm thick cement plaster in single coat on brick/concrete walls for interior plastering upto floor two level and finished even and smooth in (i) Cement mortar 1:3 (1-cement:3-sand) including finishing with a flating coat of neat cement slurry etc. complete. for Ground Floor	132.00	Sqm	211.98	27981.36
38	Applying two coats of putty & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth.	309.00	Sqm	40.59	12542.31

Item No	Description of Item (with brief specification and reference to book of specifications)	Quantity	Unit	Rate In figures	Amount
1	2	3	4	5	6
39	Wall painting one coats of primer of approved brand (three coats) plastic emulsion paint of approved brand and manufacture on undecorated wall surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth.	309.00	Sqm	118.59	36644.31
39A	Wall painting with Applying two coats of putty & two coats of primer of approved brand & (three coats) with plastic emulsion paint of approved brand and manufacture on undecorated ceiling surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth.	132.00	Sqm	124.28	16404.96
40	20mm thick sand faced cement plaster on walls upto height 10 metres above ground level consisting of 12mm thick backing coat of C.M. 1:3 (1-cement : 3-sand) and 8mm thick finishing coat of C.M. 1:1 (1-cement : 1-sand) with 1cm x 1cm grooves as per pattern sample approved by the engineer incharge etc. complete.	354.00	Sqm	315.69	111754.26
41	Providing laying and jointing in true line and level 15mm dia. U.P.V.C. Pipe (SCH- 40) for cold water including fittings as approved by Engineer In Charge. Pipe shall be fixed on the wall with the help of clamp at every two metre C/C or shall be cancelled as directed including necessary fittings etc. including testing of pipe and joints and fixing the same with adhesive solvent, including cost of all materials.	45.00	Rmt	72.65	3269.25
42	Providing laying and jointing in true line and level 25mm dia. U.P.V.C. Pipe (SCH- 40) for cold water including fittings as approved by Engineer In Charge. Pipe shall be fixed on the wall with the help of clamp at every two metre C/C or shall be cancelled as directed including necessary fittings etc. including testing of pipe and joints and fixing the same with adhesive solvent, including cost of all materials. [B] 25mm dia.	60.00	Rmt	91.84	5510.40
43	Providing laying and jointing in true line and level 40mm dia. U.P.V.C. Pipe (SCH- 40) for cold water including fittings as approved by Engineer In Charge. Pipe shall be fixed on the wall with the help of clamp at every two metre C/C or shall be cancelled as directed including necessary fittings etc. including testing of pipe and joints and fixing the same with adhesive solvent, including cost of all materials.[D] 40 mm.	30.00	Rmt	148.12	4443.60
44	Providing and fixing uPVC Heavy Duty Handle valve of approved brand and Quality with required fitting and adhesive incl. fixing the same with new pipe line as directed by engineer in charge. (B) 25mm dia.,	3.00	Nos	469.65	1408.95
45	Providing and fixing uPVC Heavy Duty Handle valve of approved brand and Quality with required fitting and adhesive incl. fixing the same with new pipe line as directed by engineer in charge. (C) 40mm dia.,	3.00	Nos	685.79	2057.37
46	Providing, laying and jointing in true line and level 75 diameter U.P.V.C (Type B) conforming to IS 13592-1992 with one end plain and other end socketed with rubber ring, & fittings conforming to ISI 14735-1999 of approved make for drainage system pipe line, pipe shall be jointed with each other with rubber lubricant, pipe shall be fixed on wall using of PVC clamp of the size 110 mm diameter x 149 mm length x 145 mm high at every 2000 mm center to center or shall be concealed in walls as directed including necessary fittings such as bends, shoes etc. including testing of pipes and joints and jointed with adhesive solvent cement including cost of all materials.	6.00	Rmt	756.22	4537.32
47	Providing and fixing to wall ceiling and floor 10.0 Kg. F/Cm2 working pressure poluthene pipes of the following outside Dia. Low density, complete with special flange compression type fittings, wall clipsetc. including making good the wall ceiling and floor.(A) 110mm dia.	27.00	Rmt	338.95	9151.65
48	Providing, laying and jointing in true line and level 110 diameter U.P.V.C (Type B) conforming to IS 13592-1992 with one end plain and other end socketed with rubber ring, & fittings conforming to ISI 14735-1999 of approved make for drainage system pipe line, pipe shall be jointed with each other with rubber lubricant, pipe shall be fixed on wall using of PVC clamp of the size 110 mm diameter x 149 mm length x 145 mm high at every 2000 mm center to center or shall be concealed in walls as directed including necessary fittings such as bends, shoes etc. including testing of pipes and joints and jointed with adhesive solvent cement including cost of all materials.	15.00	Rmt	876.90	13153.50
49	Providing and fixing PVC SWR Nahni trap IS 14735 for drain - 100 mm diameter with jali of the following nominal diameter of self cleansing design with C.I sread down or hinged grating including the cost of cutting and making good the walls.	9.00	Nos	599.64	5396.76
50	Providing and fixing screw down quarter turn heavy duty bib taps of following size (A) Brass chromium plated screw down bib tap (i) 15mm dia. (Plumber, Mark, Escco or equivalent brand)	6.00	Nos	186.83	1120.98
51	Providing and fixing CP brass Quarter turn pillar tap, capstan head screw down high pressure with screw, shanks and back nuts (A) 15 mm dia {Jaquar< Plumber, Mark Long pipe or equivalent brand }	6.00	Nos	308.73	1852.38
52	Providing and fixing wash basin with pedestal of std. Height with single hole for pillar tap with C.I or M.S brackets painted white including cutting cutting holes and making good the same including C.P. brass waste and waste pipes and bottal trap (A) Vitreous China: (ii) Flat Back washbasin 550 mm x 400mm size.In colour.	3.00	Nos	1849.31	5547.93
53	Provision and fixing water closet squatting orissa type W.C. pan size 580mm integral footrest and 100 mm P or S trap and in cluding 25 mm dia CP brass flush valve and GI inlet connection etc. comp. (A) Vitreous china long pattern white or color	3.00	Nos	1306.94	3920.82
54	Providing erecting and fixing double coated 4-layer tough virgin plast ISI water tank of required capacity each with all necessary fittings and connection etc. complete on terrace.	3000.00	Litre	10.61	31830.00
55	Providing and fixing 600mm x 450mm bevelled edge mirror of superior glass mounted on 6mm thick A.C. sheet or plywood sheet and fixing to wooden pluge with C.P. brass screws and washers.	3.00	No	859.41	2578.23
56	Providing and fixing C.P. brass towel rail complete with C.P. brass brackets fixed to wooden plugs with C.P. brass scews.(B) 600mm x 20mm size.	3.00	No	616.42	1849.26

Item No	Description of Item (with brief specification and reference to book of specifications)	Quantity	Unit	Rate In figures	Amount
1	2	3	4	5	6
57	Providing and fixing S.W. gully trap with C.I. grating brick masonry chamber and water tight C.I. cover with frame of 300mm x 300mm size (inside) with standard weight.(i) Square mouth traps.(B) 150mm x 100mm size P of R type	3.00	No	1246.92	3740.76
58	Providing and fixing CP brass screw down stop cock of approved quality 15mm size with adjustable wall flange..or as per instruction of engineer incharge.	12.00	No	205.83	2469.96
59	Constructing brick masonry chamber for underground C.I. Inspection chamber and bends with bricks having crushing strength not less than 35Kg. Cm2 in C.M. 1:5 C.I. cover with frame (Light duty) 455mm x 610mm intenal dimensions, total weight of cover with frame to be not less than 38Kg. (Wt. of cover 23 Kg.) and Wt. of frame 15Kg.) (R.C.C. top slab with 1:2:4 mix (1-cement :2- coarse sand :4-graded stone aggregate 20mm size) foundation concrete 1:5:10 inside plaster 15mm thick with cement mortar 1:3 finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete.(i) Inside dimensions 455mmx 610mm and 450mm deep for single pipe line.	9.00	No	2932.93	26396.37
60	Constructing brick masonry chamber for underground C.I. Inspection chamber and bends with bricks having crushing strength not less than 35Kg. Cm2 in C.M. 1:5 C.I. cover with frame (Light duty) 455mm x 610mm intenal dimensions total weight of cover with frame to be not less than 38Kg. (Wt. of cover 23 Kg.) and Wt. of frame 15Kg.) (R.C.C. top slab with 1:2:4 mix (1-cement :2- coarse sand :4-graded stone aggregate 20mm size) foundation concrete 1:5:10 inside plaster 15mm thick with cement mortar 1:3 finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete.(ii) Inside dimensions 500mm x 700 mm and 450mm deep for pipe line with one or two inlets.	3.00	No	3660.76	10982.28
61	Providing sock pit of 8.00 Cmt. Volume including excavating and filling brickbats with dry masonry work at top for 45cm. height including covering the top with stone including providing vatas in C.M. 1:3 with finishing curing etc. complete as directed.	3.00	No	26526.64	79579.92
62	Finishing wall with weather proof exterior emulsion paint on wall surface (two coats) to give an required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered materials.etc complete	354.00	Sqm	120.26	42572.04
63	Constructing Sandwich Platform of 18 mm thick Polished Black Granite at top and 25 mm thick Kota stone slab using cement mortar 1:3 for sandwich and fitting at bottom & edges with waterproof rigid adhesives including macking necessary grooves in walls with Vertical Kotastone 30 mm x 2 No sandwich thick every 60 cm centre to centre including all labour material of approved quality incl. full moulded round front edge fixed in wall for partition and jointed with grey cement slurry including rubbing and polishing etc. complete	9.00	Sqm	5868.10	52812.90
64	Providing and fixing stainless steel kitchen sink glossy ASIS 304 grade and 1 mm thick with overall size 510mm x 432mm x 330mm deep having bowl size 410mm x365mm x 165mm of Nirali or equivalent brand with all fittings CI or MS brackets painted white or fixing on stone base including cutting holes and making good the same brass valve and fisher union fitting including all necessary fittings	3.00	Nos	1789.72	5369.16
65	Providing thoruting or plaster drip and moulding to R.C.C. chhajja.	12.00	Rmt	43.05	516.60
66	Writing letter or figures on any surface with black Japan paint (stops, comas, hyphens and the like not to be measured and paid for separately) (ii) Indian (Letters/Figures)	9000.00	Nos	3.68	33120.00
67	Providing water harvesting pit 2.40 mt dia x 2.40 mt depth with excavation in any strata filling the pit with brick bats in 0.60 mt depth, 0.30 mt with 25mm to 40mm kapchi 0.30 mt with 10mm to 20mm kapchi & 2.00 mm depth with coarse sand in layer including maing the lines (PVC) for water inlet etc. as directed including 250mm dia bore work with 6" PVC" pipe upto 35mt etc, comp.	3.00	Nos	26189.30	78567.90
68	Supplying & installing of Dry Chemical Powder type 6 Kg. Capacity fire extinguisher as per I.S. 2171 ISI. Mark with necessary fittings etc. complete.	6.00	Nos	2626.00	15756.00
69	Providing and fixing 90 cm high Stainless steel railing made from anticorrocive S S pipe of 50 mm dia (16Gauge) as hand rail with S S 38 mm dia (16Gauge) as a vertical support fixed in RCC slab at 1.2m c/c including three horizontal S S pipes of 25 mm dia (16Gauge) at equal distance fixed by 18.75 mm dia (16Gauge) S S pipe including accessories as per detailed drawing as directed etc. complete.	10.20	Rmt	3245.13	33100.33
70	Point wiring for Light / Bell with 2-1.5 sq.mm & earth wire of 1.5 sq.mm (Green) both are of ISI marked 1.1 KV grade FRLS PVC insulated multi strand copper wires up to 10 mtr length , in below type of pipe erected with 6A Modular type switch / bell push & accessories and earth continuity of following type, erected on PVC / Metallic/ Wooden box, single mounting base frame covered with extured/ metallic/ white front plate modules erected on / in wall / ceiling as per pipe erected, with necessary Lamp holder/ceiling rose / H.D.Connector as directed. (a) with medium class Rigid PVC pipe and accessories erected flushed on wall/ceiling complete	75.00	Pt.	419.15	31436.25
71	Point wiring for FAN with 2-1.5 sq.mm & earth wire of 1.5 sq.mm (Green) both are of .ISI marked 1.1 KV Grade FRLS PVC insulated multi strand copper wires up to 10 mtr length, in below type of pipe erected with 6A Modular type switch and hum free EME step type electronic fan regulator mounted and accessories with earth continuity of following type erected on PVC / Metallic/Wooden box, single mounting base frame covered with textured/metallic/white front plate modules erected on / in wall / ceiling as per pipe erected. with necessary ceiling rose / H.D.Connector as directed. (a) with medium class Rigid PVC pipe and accessories erected flushed on wall/ceiling complete	9.00	Pt.	598.93	5390.37
72	Point wiring for Individual Plug with & earth wire of 1.5 sq.mm (Green) both are of ISI marked 1.1 KV grade FRLS PVC insulated multi strand copper wires up to 10 mtr length, in below type of pipe erected complete with Modular type switch & 5 pin Plug erected on PVC / Metallic/Wooden box covered with appropriate front plate modules erected on / in wall / ceiling as per pipe erected with following type of accessories. [I] For 6A Plug and 6 a switch with 2-1.5 sq.mm Cu. Wire from nearby switchboard/mcb db board (a) with medium class Rigid PVC pipe and accessories erected flushed on wall/ceiling complete	6.00	Pt.	445.41	2672.46

Item No	Description of Item (with brief specification and reference to book of specifications)	Quantity	Unit	Rate In figures	Amount
1	2	3	4	5	6
73	Point wiring for on board Looped Plug with 6A Modular type switch & 5 pin socket erected on PVC / Metallic/Wooden box, single mounting base frame covered with textured / metallic/white front plate modules erected on / in wall / ceiling with following type accessories , Cat. III.	6.00	Pt.	241.39	1448.34
74	Providing and erecting ISI mark Medium class RIGID PVC PIPES of following size complete to be erected on/in wall or ceiling erected with necessary PVC fittings & Junction boxes fixed with adhesive solution & Clamps with following dia of pipes, in approved manner as directed (A) 20 mm	240.00	Meter	23.23	5575.20
75	Providing and erecting Mains with 1.1 KV grade FRLS PVC insulated ISI marked stranded Copper conductor wire in following type of pipe to be erected concealed in /flushed on wall/ceiling, with 1.5 sq. mm copper conductor FRLS PVC insulated stranded wire of green colour for earth continuity of following size (A) With medium class Rigid PVC pipe and accessories. (b) 2 wire 2.5 sq. mm	150.00	Meter	78.78	11817.00
76	Providing and erecting Mains with 1.1 KV grade FRLS PVC insulated ISI marked stranded Copper conductor wire in following type of pipe to be erected in / on wall / ceiling with 2.5 sq. mm copper conductor FRLS PVC insulated stranded wire of green colour for earth continuity of following size (A) with medium class Rigid PVC pipe and accessories (a) 2 wire 4 sq. mm	90.00	Meter	107.06	9635.40
77	Providing & erecting Sheet Steel Powder Coated MCB Distribution Board Flush/Surface Mounted Fitted With Busbar Natural Link Earth Bar and Din Rail Confirming to BS: 5486-1986 without MCB to House Appropriate Nos of MCBs. (F) Single Phase 8 Way Double Door CAT-III	3.00	Each	326.23	978.69
78	Providing and erecting Miniature circuit breaker single pole 6A to 25A suitable to operate on 240 V A.C. system and having breaking capacity 10 KA to be erected in existing box. conforming to IS 8828/1996 with ISI Mark (A) 6 to 32 Amp. CAT-III	6.00	Each	299.97	1799.82
79	PROVIDING AND ERECTING DOUBLE POLE MCB ISOLATOR A.C.22 DUTY CONFIRMS TO IS13947-3 240V 40 IN EXISTING BOX. CAT-III	3.00	Each	313.10	939.30
80	Approved Make ELCBs/RCCBs Conforming to IS12640 and Having Sensitivity of 30Ma and Short Circuit Withstand Capacity of 6KA and Suitable for Operation on Single Phase 240V Having Characteristic of Quick Action & Tripping with All Advance Feature & Do not Incorporate any electronic component for Following Max Rating Erected as Directed (ii) 40AMPS.DP CAT-III	3.00	Each	2235.13	6705.39
81	Supplying and erecting LED indoor fittings with LEDs of wattage 0.2 Watt to 0.5 Watt assembled on single MCPCB, with housing used as a heat sink shall be made of thick sheet Steel conforming to IS: 513/CRCA/ aluminium die cast powder coated and high U.V. & corrosion resistance with diffuser with company mark/name 160V to 270V, Power Factor more than 0.95, THD < 15%, CCT 3000 K to 6500K, Luminaire efficacy > 85 lumens/watt ,LED LED driver efficiency > 85 % (fitting required LM-79 & LM-80 Certificates)(NOTE: Below description have shown ranges of Wattage capacity of LED fittings.The Engineer incharge may select any wattage capacity between the ranges shown.) (A) Tube Light with integral driver (iv) 22-24 Watts, Surge - 2KV,IP-20, conventional 4 feet	18.00	Each	373.70	6726.60
82	Supplying and erecting led lamps with following wattage capacity of 220 to 240 voltage, minimum 15000 burning hours life, 500 V in built-surge protection,Polycarbonate diffuser, mounting suitable for E14 / E27 / B22 lamp holders, pf >= 0.5 (ii) 5 to 8 watts	6.00	Each	112.11	672.66
83	Providing and erecting Approved make Ceiling fan with double ball bearing ISI mark with condenser A.C. 230V.50 c/s.1200 mm. sweep complete, canopy erected on existing hook or clamp with earthing. [Make shall be approved by Engineer in charge]	9.00	Each	1596.81	14371.29
84	Providing & erecting Switch board for Computer or electric apparatus consisting of following modular type accessories mounted with PVC / Metallic concealed/open box with single mounting base frame covered with textured/metallic /white front plate,modules erected with necessary connections as directed 1 no. 6A/16A universal plug-switch combined. 3 nos. 6A Switch 3 nos. 6A 5 pin Plug For Modular Type Accessories	6.00	Each	1081.71	6490.26
85	Decorative call bell Ting-tong box type 250 volts complete erected	6.00	Each	68.68	412.08
86	Providing and erecting Pipe type earthing with 40 mm dia 2.5 mtr long 'B' grade G.I. pipe with necessary coupling buch buried in specially prepared earth pit & G.I. earth wire of 8 SWG erected & connected as directed (For panel)	3.00	Each	823.15	2469.45
87	For using salt and charcoal / coke as required for pipe type earthing.	3.00	Each	171.70	515.10

Item No	Description of Item (with brief specification and reference to book of specifications)	Quantity	Unit	Rate In figures	Amount
1	2	3	4	5	6
88	MGVC Ltd. meter connection charges	3.00	Lump	6565.00	19695.00
	Total Tender amount				3839512.32
Rupees Thirty Eight Lakh Thirty nine Thousand Five Hundred Twelve And Paise Thirty Two Only					
<p>I/am we/are willing to carry out the work at _____% above /below _____ percent (should be written in figures and words) of the estimated rates mentioned above. Amount of my/our tender works out as under.</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>* Estimated amount put to tender</p> <p>Rs. _____</p> <p>Deduct : _____ % Below Rs. _____</p> <p>Net Rs. _____</p> <p>In words _____</p> </div> <div style="width: 45%;"> <p>Rs. _____</p> <p>Add : _____ % Above Rs. _____</p> <p>Total Rs. _____</p> <p>In words _____</p> </div> </div>					
<p>Notes:-</p> <p>1. The Contractor Shall Exhibit a board with deatiled specification and details of work as directed by the Engineer-In-Charge for which no Extra Payment shall be made.</p> <p>2. The labour crss will be deducted as per prevailing Rules i.e 1% of the work done.</p> <p>3. GST and Income tax TDS will be deducted at a Source while making Payments of bills.</p> <p>4. In all RCC items in Rate Analysis Standard cement Consupcion has been taken as per Govt.G.R: PRC -10/2017 cement consumption/16/c, Date: 11/05/2017 as stated i. S.O.R therefor in RCC Items where there is a changed as per actual mix design the cost of diffrence of cement consumption have been deduvted from the rate of orignal item at the rate of input rate mentioned in all the tender.</p> <p style="text-align: center;">Above all items of " Schedule-B" with iem Description,Unit,Rate & Amount Have verified by me and found Order.</p> <div style="display: flex; justify-content: space-between; margin-top: 100px;"> <div style="width: 45%; text-align: center;"> <p>Deputy Executive Engineer R & B (Pan) Sub Division Gandhinagar</p> </div> <div style="width: 45%; text-align: center;"> <p>Executive Engineer R & B (Pan) Division Gandhinagar</p> </div> </div>					