

Name of work : S.R. to New Seva Sadan-1 (PWD) Office, Dist. Bharuch (Repairs to Outer Plaster Work, Colour Work, Plumbing Work, Flooring Work).

APPLICABLE SPECIFICATIONS

Item No.	Item of work	Applicable specification of Government Technical Standard Building Specification Book Item No & Page No.
1	2	3
1	Removing and scraping of old deteriorated plaster of any thickness from wall / R.C.C member including stacking of serviceable material and disposal of unserviceable from site of work with all lead and lift.	As per separate sheet attached
2	Dismantling tiled of stone floors laid in mortar including stacking of serviceable materials and disposal of unserviceable materials with all lead and lift.	As per separate sheet attached
3	20mm thick sand faced cement plaster on walls upto height 10 metre above ground level consisting of 12mm thick backing coat of CM. 1:3 (1-cement : 3-sand) and 8mm thick finishing coat of CM. 1:1 (1 cement: 1-sand) etc. complete extra for scaffolding.	As per separate sheet attached
4	Applying two coats of (white cement based) or (acrylic lappy (putty) or equivalent and two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth for All floor.	As per separate sheet attached
5	Finishing wall with Weather proof exterior acrylic emulsion paint With one coat of primer on wall surface to give an required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered materials etc complete for All floor.	As per separate sheet attached
6	P & L 24" x 24" vitrified 8 mm thick tile flooring over 20 mm average) base of cement mortar 1:6 (1 cement: 6 coarse sand) on new surface or fixing on existing flooring by adhesive material including dismantling of existing flooring and jointed with color cement slurry including finished with flush pointing & cleaning the surface etc.	As per separate sheet attached

Item No.	Item of work	Applicable specification of Government Technical Standard Building Specification Book Item No & Page No.
1	2	3
7	Providing and laying BITUMAT SYNROOF HI BUILD, an elastomeric , premium quality acrylic coating on terrace in two layers total of avg. 1 mm th. waterproofing membrane finished which consist coat of SYNROOF primer and middle layer of 80 GSM geotextile with ultra violet resistance and working up to any height with the 5 ears of guaranty against New Construction and 3 years for Old buildings for any leakage etc. complete as per detail specification and as directed by Engineer In Charge.	As per separate sheet attached

Deputy Executive Engineer
City (R&B) Sub Division
Bharuch

Signature of the Contractor

Executive Engineer
Bharuch (R&B) Division
Bharuch