

**Construction of New Aganwadi Building at Chitravadi Village, Taluka: Nandod, Dist: Narmada.
(Pkg-4)**

SPECIFICATION INDEX

Item No.	Item of work	Unit	As per Building Booklet Specification / Electrical
1	2	3	4
[1]	Demolition including stacking of serviceable materials and disposal of unserviceable materials with all lead and lift. (i) R.C.C. work	Cum	As per Attached Sheet
[2]	Demolition of Brick work and stone masonry including stacking of serviceable materials and disposal of unserviceable materials with all lead and lift.(ii) In Cement Mortar.	Cum	As per Attached Sheet
[3]	Dismantling tiled of stone floors laid in mortar including stacking of serviceable materials and disposal of unserviceable materials with all lead and lift.	Sqmt	As per Attached Sheet
[4]	Dismantling doors, windows, ventilators etc. (wood or steel) shutters including chowkhats architraves, holdfasts and other attachment etc. complete and stacking them within all lead and lift.(i) Not exceeding 3 Sq.M. in area.	Each	As per Attached Sheet
[5]	Dismantling steel work including distempering and stacking the materials with all lead and lift.	Kg	As per Attached Sheet
[6]	Excavation for foundation upto 1.5 m depth including sorting out and stacking of useful materials and disposing off the excavated stuff upto 50 Meter lead. (D) Soft rock not requiring Blasting	Cum	As per Attached Sheet
[7]	Excavation for foundation for depth from 1.5 m to 3.0 m including sorting out and stacking of useful materials and disposing off the excavated stuff upto 50 Meter lead. (D) Soft rock not requiring Blasting	Cum	As per Attached Sheet
[8]	Filling in foundation and plinth with sand in layers of 20 cm. Thickness including watering ramming and consolidating etc. comp.	Cum	As per Attached Sheet
[9]	Filling foundation and plinth with murrum or selected soil in layer of 20 cm in thickness including ramming watering and consolidating etc. complete	Cum	As per Attached Sheet
[10]	Anti-Termite System: Providing and laying of permanent piping technology anti-termite treatment before flooring work by installing LLDP (Low linear density polyethylene) tube of 8 mm O.D. & 6.4 mm 1.D. with inbuilt pressure compensation chip every 30 cm interval in the tube, having working pressure of 2 Kg/cm ² and release rate of 1.9 ltr/hour fixed by P-clips and nails.The LLDP pipe shall be installed at the entire periphery of the building and at internal network of building at a depth of 20 to 200 mm under floor at every 2 to 3 mtr. c/c distance (adjusted as per building layout) & ends of loop pass through a PVC elbow of minimum 32 mm ID at junction box of wall and floor level, entering into a steel reinforced grooved flexible pipe of minimum 22 mm ID leading into junction box and the loops shall terminate in junction boxes & test every junction during injecting chemicals for termite control treatment.Providing and laying cement concrete 1:3:6 (1-Cement : 3- coarse sand : 6 machine cut stone aggregates 40 mm nominal size) and curing complete excluding cost of formwork in (A) Foundation and Plinth.	Sq.m	As per Attached Sheet
[11]	Providing and laying cement concrete 1:3:6 (1-Cement : 3- coarse sand : 6- machine cut stone aggregates 40 mm nominal size) and curing complete excluding cost of formwork in (A) Foundation and Plinth.	Cum	As per Attached Sheet
[12]	Providing and laying controlled cement concrete M.250 and curing complete including the cost of formwork and excluding reinforcement for reinforced concrete work in (A) Foundations, footings, and Mass concrete. footing	Cum	As per Attached Sheet
[13]	Providing and laying controlled cement concrete M-250 and curing complete including the cost of form work but excluding the cost of reinforcement for reinforced concrete work in (D) Columns up to Plinth Level.	Cum	As per Attached Sheet
[14]	Providing and laying controlled cement concrete M-200 and curing complete including the cost of form work but excluding the cost of reinforcement for reinforced concrete work in (D) Columns on Ground Floor.	Cum	As per Attached Sheet
[15]	Providing and laying controlled cement concrete M-200 and curing complete including the cost of form work but excluding the cost of reinforcement for reinforced concrete work in (D) Columns on Terrace Floor.	Cum	As per Attached Sheet
[16]	Providing and laying controlled cement concrete M-250 and curing complete including the cost of form work but excluding the cost of reinforcement for reinforced concrete work in (C) Ground Beam and Plinth Beam	Cum	As per Attached Sheet
[17]	Providing and laying controlled cement concrete M-150 and curing complete including the cost of form work but excluding the cost of reinforcement for reinforced concrete work in (C) Plinth Slab	Cum	As per Attached Sheet
[18]	Providing and laying controlled cement concrete M.200 and curing complete including the cost of formwork and excluding reinforcement for reinforced concrete work in (C) Beam at Ground Floor	Cum	As per Attached Sheet
[19]	Providing and laying controlled cement concrete M-200 and curing etc. complete including the cost of form work and reinforcement for reinforced concrete work in (C) Chhajja at Ground floor	Cum	As per Attached Sheet
[20]	Providing and laying controlled cement concrete M-200 and curing etc. complete including the cost of form work and reinforcement for reinforced concrete work in (C) Lintel at Ground floor	Cum	As per Attached Sheet

Item No.	Item of work	Unit	As per Building Booklet Specification / Electrical
1	2	3	4
[21]	Providing and laying controlled cement concrete M.200 and curing complete including the cost of formwork and excluding reinforcement for reinforced concrete work in (C) Ground floor Slab	Cum	As per Attached Sheet
[22]	Providing TMT Bar FE 500D reinforcement with fusion bonded Epoxy coating not less than 175 micron thickness and up to 300 micron to reinforcement bars as per IS-13620-1993 /ASTM-775M (including testing of coating at plant and all taxes) for R.C.C. work including bending, binding and placing in position complete upto floor two level.	kg	As per Attached Sheet
[23]	Providing TMT Bar FE 500D reinforcement with fusion bonded Epoxy coating not less than 175 micron thickness and up to 300 micron to reinforcement bars as per IS-13620-1993 /ASTM-775M (including testing of coating at plant and all taxes) for R.C.C. work including bending, binding and placing in position complete. above Floor two Level	kg	As per Attached Sheet
[24]	Steel work, welded in built up sections framed work including cutting, hoisting, fixing in position and applying a priming coat of red lead paint. (A)In beams and joists, channels angles Tees, flats, with connecting plates or angle cleats as in main and cross beams. Hip and jack rafters, purlins conneted to common rafters and the like	Quintal	As per Attached Sheet
[25]	Painting two coats (excluding priming coat) on new steel and other metal surface with enamel paint, brushing, interior to give an even shade including cleaning the surface an even shade including cleanin the surface of all dirt, dust and other foreign matter.	Sqm	As per Attached Sheet
[26]	Providing and fixing M. S. grills of required pattern to frames of windows etc. with M. S. flats at required spacings and frame alround having min. weight of Grill 25kg/sq.m, square or round bars with round headed bolts and nuts or by screws including priming coat of approved quality and two coats of enamel paint, as directed by engineer in charge (A) Plain Grill	Sqm	As per Attached Sheet
[27]	Providing and fixing 90cm high Stainless steel railing made from anti corrosive 304 grade S. S. pipe of 50mm dia. (16 Gauge) as hand rail with S. S. 304 grade Balusters / Posts of Pipe 50mm dia. (16 Gauge) as a vertical support fixed in RCC slab at 1.2m c/c including two horizontal S. S. pipes of 16mm dia. (16 Gauge) at equal Distance fixed by 18.75mm dia (16 Gauge) S. S. pipe with baluster including accessories as per Detailed Drawing as directed etc. complete.	Rmt	As per Attached Sheet
[28]	Brick work using common burnt clay building bricks having crushing strength not less than 35 kg/sq.cm. in foundation and plinth in cement mortar 1:6 (1 cement : 6 fine sand) Conventional	Cum	As per Attached Sheet
[29]	Brick work using common burnt clay building bricks having crushing strength not less than 35 Kg/Sq.cm. in super structure above plinth level upto floor two level in cement mortar 1:6 (1cement : 6 fine sand) Conventional (Ground Floor)	Cum	As per Attached Sheet
[30]	Brick work using common burnt clay building bricks having crushing strength not less than 35 Kg/Sq.cm. in super structure above plinth level upto floor two level in cement mortar 1:6 (1cement : 6 fine sand) Conventional (Terrace Floor)	Cum	As per Attached Sheet
[31]	Half brick masonry in common brunt clay building bricks having crushing strength not less than 35Kg/Sm. In C.M 1:4(1cement : 4 coarse sand) in super structure. Conventional for Ground floor..	Sqm	As per Attached Sheet
[32]	Providing and fixing 150 mm wide, approved quality chicken wire mesh at junction of brick work and RCC work or two dissimilar surfaces, at all heights fixed by nails, rowal plugs or tag by cement mortar 1:3 before applying the plaster, including curing etc. complete	Sqm	As per Attached Sheet
[33]	Providing 15mm thick cement plaster in single coat on Rough (Similar)side of single or half brick walls / concrete wall for interior plastering and finished even and smooth along with floating coat of neat cement slurry etc. comp. in (ii) Cement mortar 1:4 (1-cement :4-sand) 1) Plaster at Ground Floor	Sqm	As per Attached Sheet
[34]	Providing 15mm thick cement plaster in single coat on Rough (Similar)side of single or half brick walls / concrete wall for interior plastering and finished even and smooth along with floating coat of neat cement slurry etc. comp. in (ii) Cement mortar 1:4 (1-cement :4-sand) 2) Plaster at Terrace Floor	Sqm	As per Attached Sheet
[35]	Providing 10 mm thick smooth cement plaster in single coat for plastering on ceiling and soffits of stairs and finished even and smooth along with floating coat of neat cement slurry etc. comp. (i) Cement mortar 1:4 (1 cement: 4 sand). 1) Plaster at Ground Floor	sq.m	As per Attached Sheet
[36]	20mm thick double coat sand faced cement gutka plaster on walls upto height 10 metres above ground level consisting of 12mm thick backing coat of C.M. 1:3 (1-cement : 3-sand) and 8mm thick finishing coat of C.M. 1:1 (1-cement : 1-sand) including 1cm x 1cm grooves etc. complete.	sq.m	As per Attached Sheet
[37]	Providing throating or plaster drip and moulding to R.C.C. Chhajja..	Rmt	As per Attached Sheet
[38]	Applying two coats of (white cement based) or (acrylic lappy (putty)) or equivalent and two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. for All floor.	sq.m	As per Attached Sheet
[39]	Wall painting (three coats) with plastic emulsion paint of approved brand and manufacture on undecorated wall surface to give an even shade including throughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth.	sq.m	As per Attached Sheet

Item No.	Item of work	Unit	As per Building Booklet Specification / Electrical
1	2	3	4
[40]	Wall painting (two coats) with plastic emulsion paint of approved brand and manufacture on undecorated ceiling surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth.	sq.m	As per Attached Sheet
[41]	Finishing wall with Weather proof exterior 100% acrylic emulsion paint With one coat of primer on wall surface to give an required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered materials.etc complete for All floor	sq.m	As per Attached Sheet
[42]	Providing And filling with good quality cinder(steam coal) as directed by engineer in charge in sunks in layers of 15 cm thick,including watering,placing ,ramming well etc as directed, for all floor.	Cum	As per Attached Sheet
[43]	Providing and fixing flush door shutters, solid core construction with frame of first class hardwood with cross board and face veneer or plywood face panels, including anodised alluminium butt hinges with necessary screws. (B) Non-decorative type and block board core anodised alluminium butt hinges in flush door shutters (2) 35 mm thick.	sq.m	As per Attached Sheet
[44]	Providing and fixing FRP frame size 100x50 mm and 28mm thick FRP depress panel shutter having extra reinforcement on sides & edges in Gel coat finish. The core of the shutter & frame is to be filed up with injected fire retardant grade polyurethane foam done in situ alongwith embedded wooden pieces for stiffening & also taking hinges & finitues. The whole FRP frame & shutter is to be water proof weather proof, termite proof & resistance to mild acid/alkali. Rates are to be inclusive of S.S hinges with necessary screws & alluminium fixtures & fastenings & fastener sleeve.	sq.m	As per Attached Sheet
[45]	Providing and fixing window having extruded aluminum Colour anodized section frame main outer size 95mm x 24mm x 1.17mm @ wt.of 0.738 Kg/mt , horizontal Three track member size 92mm x 31.75mm x 1.30mm,@ Wt.1.07 Kg/mt , vertical member of size 92mm x 31.75mm x 1.50mm @ Wt. 1.06 Kg/mt with sliding shutters of horizontal member size 40 mmx18mm x1.29mm @ wt.of 0.456 Kg/mt, vertical member of size 40mm x 18mm x 1.29 mm @ wt.of 0.456Kg/mt/ with 5 mm thick transparent bronze colour tinted float glass with powder coated aluminum fittings and fixtures and transparent silicon sealant glass fixing to frame as per details etc	sq.m	As per Attached Sheet
[46]	Providing and fixing standared extruded of alluminium section of size 63mm x 38.10mm x 1.2mm @ Wt. 0.643 Kg/mt with colour anodized alluminium frame for ventilation with 5 mm thick frosted glass as details etc complete for Ventilation	Sq.m	As per Attached Sheet
[47]	P & L 24" x 24" vitrified 8 mm thick tile flooring over 20 mm (average) base of cement mortar 1:6 (1 cement: 6 coarse sand) on new surface or fixing on existing flooring by adhesive material including dismantling of existing flooring and jointed with color cement slurry including finised with flush pointing & cleaning the surface etc. complete for antiskit	Sq.m	As per Attached Sheet
[48]	Providing and laying Vitrified tiles 8 to 10 mm thick , in skirting risers of steps and dedo on 10mm thick cement plaster 1:3 (1-cement : 3-coarse sand) and jointed with white cement slurry	Sq.m	As per Attached Sheet
[49]	Providing and laying Machine cut, free edges, mirror polished Granite Slab flooring over 18mm (Average) thick base of cement mortar 1:6 (1-cement : 6-coarse sand) laid over and jointed with grey cement slurry mixed with pigment to match the shade of slab including rubbing and polishing etc. complete. (A) 18mm thick	Sq.m	As per Attached Sheet
[50]	Providing and laying Machine cut, free edges, mirror polished Granite Slab 18mm thick in risers of steps,skirting Dedo and pillars laid on 10mm thick cement mortar 1:3 (1-Cement : 3 coarse sand) and jointed with gray cement slury mixed with pigment to match the shade of slab including rubbing and polishing etc. complete	Sq.m	As per Attached Sheet
[51]	Providing and laying Ceramic tiles 6mm thick in flooring treads of steps and landing laid on a bed of 12mm thick cement mortar 1:3 (1-cement : 3-coarse sand) finishing with flush pointing in white cement.	Sq.m	As per Attached Sheet
[52]	Providing and laying Ceramic tiles 6mm thick in flooring treads of steps and landing laid on a bed of 12mm thick cement mortar 1:3 (1-cement : 3-coarse sand) finishing with flush pointing in white cement.	Sq.m	As per Attached Sheet
[53]	Providing and laying polished Kota stone slab flooring over 20mm (Average) thick base of cement mortar 1:6 (1-cement : 6-coarse sand) or L.M. 1.1.5 laid over and jointed with grey cement slurry including rubbing and polishing etc. complete. (B) 30 mm thick	Sqm	As per Attached Sheet
[54]	Providing and laying Ceramic tiles 6mm thick in skirting risers of steps and dedo on 10mm thick cement plaster 1:3 (1-cement : 3-coarse sand) and jointed with white cement slurry	Sqm	As per Attached Sheet
[55]	Providing and fixing mirror polished 18 mm thick Granite with full round edge and polished of approved quality in clading on sill and around the doors/ windows/ ventilation with 20 mm thick cement plaster CM (1:4) and fixing with cement slurry & adhesive including moulding of exposed edges as directed by engineering in charge etc. complete.	Sqm	As per Attached Sheet

Item No.	Item of work	Unit	As per Building Booklet Specification / Electrical
1	2	3	4
[56]	Providing and laying 40 mm thick IPS (Indian Patent Stone) flooring in cement concrete 1:2:4 (1-cement : 2-coarse sand : 4-graded stone aggregate of 20 mm nominal size) laid in one layer over prepared base and finished with a smooth floating coat of neat cement mixed with approved yellow colour pigment of required shade at 0.35 kg/Sq.m to obtain uniform colour and finish, including surface preparation, compacting, trowel finishing, curing and complete as directed by Engineer-in-Charge.	Sqm	As per Attached Sheet
[57]	Providing and laying tactile tile (for vision impaired persons as per standards) of size 300x300x9.8 mm having with water absorption less than 0.5% and conforming to IS:15622 of approved make in all colours and shades in for outdoor floors such as footpath, court yard, multi modals location etc., laid on 20 mm thick base of cement mortar 1:4 (1 cement: 4 coarse sand) in all shapes & patterns including grouting the joints with white cement mixed with matching pigments etc. complete as per direction of Engineer-in-Charge.	Sqm	As per Attached Sheet
[58]	Providing and laying broken chine mosaic flooring for terrace using 12 mm to 20 mm broken pieces of glazed tiles to be laid over cement mortar 1:3 to plain or slope and to be tempered to bring mortar creme out upto surface using white cement including rounding off junctions and extending them upto 15 cm along the wall,clearing with water and oxalic acid etc. as directed	Sqm	As per Attached Sheet
[59]	Providing erecting and fixing double coated Syntex PVC. (ISI) water tank of required capacity each with all necessary fittings and connection etc. complete on terrace.	Litre	As per Attached Sheet
[60]	Providing laying and jointing in true line and level 40mm dia. U.P.V.C. Pipe (SCH- 40) for cold water including fittings make as approved by Engineer In Charge. Pipe shall be fixed on the wall with the help of clamp at every two metre C/C or shall be cancelled as directed including necessary fittings etc. including testing of pipe and joints and fixing the same with adhesive solvent, including cost of all materials.	Rmt	As per Attached Sheet
[61]	Providing laying and jointing in true line and level 25mm dia. U.P.V.C. Pipe (SCH- 40) for cold water including fittings make as approved by Engineer In Charge. Pipe shall be fixed on the wall with the help of clamp at every two metre C/C or shall be cancelled as directed including necessary fittings etc. including testing of pipe and joints and fixing the same with adhesive solvent, including cost of all materials.	Rmt	As per Attached Sheet
[62]	Providing laying and jointing in true line and level 15mm dia. U.P.V.C. Pipe (SCH- 40) for cold water including fittings make as approved by Engineer In Charge. Pipe shall be fixed on the wall with the help of clamp at every two metre C/C or shall be cancelled as directed including necessary fittings etc. including testing of pipe and joints and fixing the same with adhesive solvent, including cost of all materials.	Rmt	As per Attached Sheet
[63]	Providing and fixing concealed center point to wall ceiling & floor CPVC (SDR 13.5) PIPE having National Sanitation Foundation (NSF) seal for potable water of following dia. nominal bore tube fittings and clamps including making good the wall, ceiling and floor etc. complete. [E] 40mm.	Rmt	As per Attached Sheet
[64]	Providing and fixing concealed center point to wall ceiling & floor CPVC (SDR 13.5) PIPE having National Sanitation Foundation (NSF) seal for potable water of following dia. nominal bore tube fittings and clamps including making good the wall, ceiling and floor etc. complete. [C] 25mm.	Rmt	As per Attached Sheet
[65]	Providing and fixing concealed center point to wall ceiling & floor CPVC (SDR 13.5) PIPE having National Sanitation Foundation (NSF) seal for potable water of following dia. nominal bore tube fittings and clamps including making good the wall, ceiling and floor etc. complete. [A] 15mm.	Rmt	As per Attached Sheet
[66]	Providing laying (to level or slopes) and jointing reinforced concrete Light duty non-pressure pipes I.S. class NP2 of the following internal diameter with collars and butt ends prepared for collar joints including testing of joints complete.(D) 300mm	Rmt	As per Attached Sheet
[67]	Providing and erecting Approved make RCCBs conforming to IS: 12640 and having sensitivity of 30 mA and Short Circuit withstand capacity of 10 KA and suitable for operation on single phase 240 V,50Hz. having characteristic of quick action & tripping with all advance feature & do not incorporate any electronic component. for following Max. rating erected as directed (ii) 40 Amps. DP Cat-III	Rmt	As per Attached Sheet
[68]	Providing and fixing PVC SWR Nahni trap IS 14735 for drain - 100 mm diameter with jali of the following nominal diameter of self cleansing design with C.I scread down or hinged grating including the cost of cutting and making good the walls.	No	As per Attached Sheet
[69]	Provision, Supplying and fixing White vitrious ching W.C. squatting pan Orrisa type 580 x 400 size with 100mm P or S trap, 25mm dia. C. P. Brass flush valve and G. I. inlet connection etc. comp. (A) Vitreous ching long pattern white or color.	No	As per Attached Sheet
[70]	Providing and fixing brass screw down stop tap.(A) 15mm dia.	Each	As per Attached Sheet
[71]	Providing and fixing ball cock of approved. quality as directed.(A) Copper Metal (ii) 50mm dia.	Each	As per Attached Sheet
[72]	Providing and fixing washbasin with single hole for pillar tap with C.I. or M.S. brackets painted white including sutting holes and making good the same but excluding fittings.(A) Vitreous China:(ii) Flat Back washbasin 550 mm x v 400mm size. (i) In white colour.	Each	As per Attached Sheet
[73]	Providing and fixing C.P. brass waste for washbasin or sink. (A) 32mm dia.	Each	As per Attached Sheet
[74]	Providing and fixing M.I. fisher union for washbasin or sink. (A) 32mm dia.	Each	As per Attached Sheet

Item No.	Item of work	Unit	As per Building Booklet Specification / Electrical
1	2	3	4
[75]	Providing and fixing 600mm x 450mm bevelled edge mirror of superior glass mounted on 6mm thick A.C. sheet or plywood sheet and fixing to wooden plug with C.P. brass screws and washers.	Each	As per Attached Sheet
[76]	Providing and fixing screw down bib taps of following size.(A) Brass screw down bib tap polished bright. (i) 20mm dia.	Each	As per Attached Sheet
[77]	Providing and fixing screw down bib taps of following size.(A) Brass screw down bib tap polished bright. (i) 20mm dia.	Each	As per Attached Sheet
[78]	Providing and fixing Rubber plug for sink or wash basin.	Each	As per Attached Sheet
[79]	Providing and fixing S.W. gully trap with C.I. grating brick masonry chamber and water tight C.I. cover with frame of 300mm x 300mm size (inside) with standard weight (i) Square mouth traps (B) 150mm x 100mm size P or R type	Each	As per Electric Booklet Attached
[80]	Constructing brick masonry chamber for underground C.I. Inspection chamber and bends with bricks having crushing strength not less than 35Kg/Cm ² in C.M. 1:5 C.I. cover with frame (Light duty) 455mm x 610mm internal dimensions total weight of cover with frame to be not less than 38Kg. (Wt. of cover 23 Kg.) and Wt. of frame 15Kg.) (R.C.C. top slab with 1:2:4 mix (1-cement :2- coarse sand :4-graded stone aggregate 20mm size) foundation concrete 1:5:10 inside plaster 15mm thick with cement mortar 1:3 finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete.(i) Inside dimensions 455mmx 610mm and 450mm deep for single pipe line.	Each	As per Electric Booklet Attached
[81]	Constructing brick masonry chamber for underground C.I. Inspection chamber and bends with bricks having crushing strength not less than 35Kg/Cm ² in C.M. 1:5 C.I. cover with frame (Light duty) 455mm x 610mm internal dimensions total weight of cover with frame to be not less than 38Kg. (Wt. of cover 23 Kg.) and Wt. of frame 15Kg.) (R.C.C. top slab with 1:2:4 mix (1-cement :2- coarse sand :4-graded stone aggregate 20mm size) foundation concrete 1:5:10 inside plaster 15mm thick with cement mortar 1:3 finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete.(ii) Inside dimensions 500mm x 700 mm and 450mm deep for pipe line with one or two inlets.	Each	As per Electric Booklet Attached
[82]	(B) Providing sock pit of 5.00 Cu.M. Volume including excavating and filling brickbats with dry masonry work at top for 45cm. height including covering the top with stone including providing vatas in C.M. 1:3 with finishing curing etc. complete as directed.	Each	As per Electric Booklet Attached
[83]	Constructing a cooking platform 60 cm. width and 70 cm high resting on B.B.Masonry walls 23 cm.thick in C.M.(1:6) with (ii) Fixing black kadappa stone 30mm thick laid on precast R.C.C. (1:2:4) slab with plastering on exposed faces of wall in C.M. (1:4) etc complete.	Rmt	As per Electric Booklet Attached
[84]	Point wiring for Light / Bell with 2-1.5 sq.mm & earth wire of 1.5 sq.mm (Green) both are of ISI marked 1.1 KV grade FRLS PVC insulated multi strand copper wires up to 10 mtr length , in below type of pipe erected with 6A Modular type switch / bell push & accessories and earth continuity of following type, erected on PVC / Metallic/Wooden box, single mounting base frame covered with textured/metallic/white front plate modules erected on / in wall / ceiling as per pipe erected, with necessary Lamp holder/ceiling rose / H.D.Connector as directed. (c) with oval conduit /PVC casing capping double lock type erected flushed on wall/ceiling complete. iii) Cat: III	Pt	As per Electric Booklet Attached
[85]	Point wiring for FAN with 2-1.5 sq.mm & earth wire of 1.5 sq.mm (Green) both are of ISI marked 1.1 KV Grade FRLS PVC insulated multi strand copper wires up to 10 mtr length, in below type of pipe erected with 6A Modular type switch and hum free EME step type electronic fan regulator mounted and accessories with earth continuity of following type erected on PVC / Metallic/Wooden box, single mounting base frame covered with textured/metallic/white front plate modules erected on / in wall / ceiling as per pipe erected. with necessary ceiling rose / H.D.Connector as directed. (c) with oval conduit /PVC casing capping double lock type erected flushed on wall/ceiling complete. iii) Cat: III	Pt	As per Electric Booklet Attached
[86]	Point wiring for Individual Plug with & earth wire of 1.5 sq.mm (Green) both are of ISI marked 1.1 KV grade FRLS PVC insulated multi strand copper wires up to 10 mtr length, in below type of pipe erected complete with Modular type switch & 5 pin Plug erected on PVC / Metallic/Wooden box covered with appropriate front plate modules erected on / in wall / ceiling as per pipe erected with following type of accessories. [I] For 6A Plug and 6 a switch with 2-1.5 sq.mm Cu. Wire from nearby switchboard / mcb db board. (c) with oval conduit /PVC casing capping double lock type erected flushed on wall/ceiling complete. iii) Cat: III	Pt	As per Electric Booklet Attached
[87]	Point wiring for Individual Plug with & earth wire of 1.5 sq.mm (Green) both are of ISI marked 1.1 KV grade FRLS PVC insulated multi strand copper wires up to 10 mtr length, in below type of pipe erected complete with Modular type switch & 5 pin Plug erected on PVC / Metallic/Wooden box covered with appropriate front plate modules erected on / in wall / ceiling as per pipe erected with following type of accessories. [II] For 16A Plug and 16 amp switch with 2-2.5 sq.mm Cu. Wire from mcb db board. (c) with oval conduit /PVC casing capping double lock type erected flushed on wall/ceiling complete. iii) Cat: III	Pt	As per Electric Booklet Attached

Item No.	Item of work	Unit	As per Building Booklet Specification / Electrical
1	2	3	4
[88]	Point wiring for on board Looped Plug with 6A Modular type switch & 5 pin socket erected on PVC / Metallic/Wooden box, single mounting base frame covered with textured / metallic/white front plate modules erected on / in wall / ceiling with following type accessories. iii) Cat.: III	Pt	As per Electric Booklet Attached
[89]	Supplying and erecting approved make of tube fitting with One no T-5 tube 24/ 28 W with Electronic ballast with each tube separately THD less than 10 & built in adaptors, GI / PVC housing & mirror optic reflector, suitable to work on 120V - 300V, A.C. supply with connector and adapter if required. [Make of fitting & tube may be differ& fitting shall be providing with tube]. ii) Cat.: III	Ea	As per Electric Booklet Attached
[90]	Providing & erecting Approved make Ceiling Fan with double ball bearing ISI mark with condenser A.C.230V 50c/s. 1400 mm. sweep complete, canopy erected on existing hook or clamp with earthing [Make shall be approved by Engineer in Charge]	Ea	As per Electric Booklet Attached
[91]	Supplying and erecting 19 / 20 mm. nominal bore Medium Class M.S. Pipe down rod erected duly painted for fan complete with proper insulation without leakage and earthing.	Mtr	As per Electric Booklet Attached
[92]	Replacing approved make fan regulator resistance type for Ceiling fan {credit of D.M. retained by Agency.}	Ea	As per Electric Booklet Attached
[93]	Supplying and erecting LED indoor fittings with LEDs of wattage 0.2 Watt to 0.5 Watt assembled on single MCPCB, with housing used as a heat sink shall be made of thick sheet Steel conforming to IS: 513/CRCA/ aluminium die cast powder coated and high U.V. & corrosion resistance with diffuser with company mark/name 160V to 270V, Power Factor more than 0.95, THD < 15%, CCT 3000 K to 6500K, Luminaire efficacy> 85 lumens/watt ,LED LED driver efficiency > 85 % (fitting required LM-79 & LM-80 Certificates)(NOTE: Below description have shown ranges of Wattage capacity of LED fittings.The Engineer incharge may select any wattage capacity between the ranges shown.) (v) 36-40 Watts, Surge-2 KV IP-20 conventional 4 feet iii) Cat.: III	Ea	As per Electric Booklet Attached
[94]	Supplying and erecting led lamps with following wattage capacity of 220 to 240 voltage, minimum 15000 burning hours life, 500 V in built-surge protection,Polycarbonate diffuser, mounting suitable for E14 / E27 / B22 lamp holders, pf >= 0.5 (A) LED Lamps integral type, with PC diffuser suitable LAMP holder (iv) 16 to 20 watts	Ea	As per Electric Booklet Attached
[95]	Providing and erecting Mains with 1.1 KV grade FRLS PVC insulated ISI marked stranded Copper conductor wire in following type of pipe to be erected concealed in /flushed on wall/ceiling, with 1.5 sq. mm copper conductor FRLS PVC insulated stranded wire of green colour for earth continuity of following size (B) With 16 swg HGS metal conduit pipe and accessories painted black. (b) 2 wire 2.5 sq. mm	Mtr	As per Electric Booklet Attached
[96]	providing and erecting Miniature circuit breaker single pole 6A to 25A suitable to operate on 240 V A.C. system and having breaking capacity 10 KA to be erected in existing box. confirming to IS 8828/1996 with ISI Mark. iii) Cat.: III	Ea	As per Attached Sheet
[97]	Providing & erecting 240 V MCB double pole switch for lighting Load (B Curve) having 10 KA breaking capacity & confirms to IS : 8828 in existing box having following capacity (B) 40 Amp. iii) Cat.: III	Ea	As per Attached Sheet
[98]	Providing and erecting Sheet Steel powder coated MCB distribution board - flush / surface mounted fitted with busbar, neutral link, earth bar and DIN rail, Conforms to IS 8623-1 & 3, IEC 61439-1 & 3 without MCB to house appropriate nos. of MCBs.(The DBs should be used of same company of MCB to be used) suitable for (A) single phase incoming and horizontal single phase outgoing (iv)12 way	Ea	As per Attached Sheet
[99]	Providing and erecting Approved make RCCBs conforming to IS: 12640 and having sensitivity of 30 mA and Short Circuit withstand capacity of 10 KA and suitable for operation on single phase 240 V,50Hz. having characteristic of quick action & tripping with all advance feature & do not incorporate any electronic component. for following Max. rating erected as directed (ii) 40Amps. DP. iii) Cat.: III	Ea	As per Attached Sheet
[100]	Providing and erecting Sheet Steel powder coated MCB distribution board - flush / surface mounted fitted with busbar, neutral link, earth bar and DIN rail, Conforms to IS 8623-1 & 3, IEC 61439-1 & 3 without MCB to house appropriate nos. of MCBs.(The DBs should be used of same company of MCB to be used) suitable for (A) single phase incoming and horizontal single phase outgoing (iv)12 way	Ea	As per Attached Sheet
[101]	Providing and fixing educational information, learning charts, child-friendly graphics, alphabet charts, number charts, village scenes, thematic illustrations, photographs and other approved designs on wall surface using printed flex material of approved quality and thickness, including providing and fixing P.V.C. border patti around the flex sheet, necessary adhesive material, cutting, alignment, fixing, finishing and all labour, materials, transportation, tools & tackles and incidental charges complete as directed by Engineer-in-Charge.	Sq.m	As per Attached Sheet

Item No.	Item of work	Unit	As per Building Booklet Specification / Electrical
1	2	3	4
[102]	Providing and fixing educational information, learning charts, child-friendly graphics, alphabet charts, number charts, village scenes, thematic illustrations, photographs and other approved designs on exterior/compound wall surfaces using weather-resistant and UV-resistant digitally printed flex material of approved quality and thickness, including providing and fixing P.V.C. border patti around the flex sheet, necessary adhesive material, cutting, alignment, proper fixing, finishing and all labour, materials, transportation, tools & tackles, scaffolding and incidental charges complete as directed by Engineer-in-Charge.	Sq.m	As per Attached Sheet
[103]	Preparing and making Scribble Wall on wall surfaces using approved green chalk paint finishing, which is suitable for writing and drawing. Cost include surface preparation, cleaning and smoothening, application of required primer or base coat when needed and finally applying the approved green chalk paint for making a smooth, durable and uniform writable surface. The above work will include finishing of border, labour, materials, tools, scaffolding, transportations, etc., all included as per directions by the Engineer-in-Charge.	Sq.m	As per Attached Sheet

Deputy Executive Engineer
Panchayat (R&B) Sub Division
Rajpipla

Executive Engineer
Panchayat (R&B) Division
Narmada