

Name of work : Repairs to Paver Block, Parking Shed and Compound Wall in Taluka Court Building at Jhagadia, Dist. Bharuch.

APPLICABLE SPECIFICATIONS

Item No.	Item of work	Applicable specification of Government Technical Standard Building Specification Book Item No & Page No.
1	2	3
1	Excavation for foundation upto 1.5 m depth including sorting out and stacking of useful materials and disposing off the excavated stuff upto 50 Meter lead.(A) Loose or soft soil.	As per separate sheet attached
2	Providing and laying cement concrete 1:3:6 (1- Cement 3- coarse sand : 6- hand broken stone aggregates 40 mm nominal size) and curing complete excluding cost of form work in (A) Foundation and Plinth.	As per separate sheet attached
3	Providing and laying cement concrete work 1:2:4 (1 -Cement: 2-Coarse sand ; 4- graded stone aggregates 20 mm nominal size) and curing complete excluding cost of Form work in (A) Foundation and Plinth.	As per separate sheet attached
4	Providing corrugated G.I Sheet of class-3 fixed with galvanised iron J or L Hooks, Bolts and nuts 8mm diameter with bitumen and G.I limpet washer or G.I limpet washer filled with white lead complete excluding the cost of purlins, Rafters and Trusses.(1) 0.80 mm thick sheet.	As per separate sheet attached
5	Steel work, welded in built up sections framed work including cutting, hoisting, fixing in position and applying a priming coat of red lead paint. (A)In beams and joists, channels angles Tees, flats, with connecting plates or angle cleats as in main and cross beams. Hip and jack rafters, purlins connected to common rafters and the like	As per separate sheet attached
6	Providing and fixing pre-cast Rubber Dye / steel Dye inter locking concrete block 60mm thick with grade of concrete M-300 pneumatic compressed / vibrated mechanically and as per approved design Confirming to IS 15658 : 2006 including 35 mm Sand layer for levelling and filling the joint with sand in proper line and level as per guidelines of IRC : SP 63-2018 etc. Complete.	As per separate sheet attached

Item No.	Item of work	Applicable specification of Government Technical Standard Building Specification Book Item No & Page No.
1	2	3
7	Brick work using common burnt clay building bricks having crushing strength not less than 35 kg./Sq.Cm. in foundation and plinth in Cement Mortar 1:6 (1- Cement: 6 -fine sand) (B) Conventional.	As per separate sheet attached
8	Providing and fixing granite stone steps of approved make and colour. IS mm thick, machine cut and polished, laid over cement mortar (1:4). including cutting, dressing, fixing tread and riser, jointing with white cement mixed with matching pigment, curing, and all labour, tools and materials, complete as per specifications and direction of Engineer-in-Charge.	As per separate sheet attached
9	Providing and fixing 35 mm thick shutters for Doors, windows and clear story windows including anodised aluminium butt hinges with necessary screws. (A) Indian Teak Wood (iii) Partly panelled and partly glazed.	As per separate sheet attached
10	Providing and fixing "Y" shape concertina razor coil roll fencing 10 mm c/c with 50 x 50 x 5 angle for "Y" and 35 x 35 x 5 angle for bottom and sides as shown in drawing & G.I. barbed roll fencing 10 cm C.C. spray and oil painting etc.	As per separate sheet attached

Deputy Executive Engineer
City (R&B) Sub Division
Bharuch

Signature of the Contractor

Executive Engineer
Bharuch (R&B) Division
Bharuch