

**Name Of Work : Paver Work Labour Charges For Laying of different types of Hot Mix
Material to Different site Prepared From Palodar Govt Hot Mix Plant
Dist. : Mehsana (annual Rate)**

SPECIFICATION

Item No.03

laying asphalt painting with VG-30 on BT surface with bitumen grade at the rate of 5 Kg /10 Sqm. By mechanical sprayer and spreading the stone dust on prepared surface at the rate of 0.03 Cum. / 10 Sqm. etc. complete

Cleaning Of Surface :

Cleaning of surface shall be As Per MoRTH 5th Revision Clause No 501 Page No 149. No extra Payment Shall be made for Cleaning.

Application of Asphalt Paint :

asphalt bitumen 5kg per 10 Sq.M. on BT surface by machine sprayer provided by R&B Department. After spreading the dust to dressed uniformly. Labours Required for Heating and Spreading shall be Provided by Contractor as Required by engineer in charge. Contractor is liable to Spread asphalt manual in case of any Fault in Mechanical Sprayer or as Required by engineer in charge without any extra cost.

Spreading of stone Dust:

Spreading of stone dust 0.03 Cu.M./10 Sq.m after applying asphalt bitumen 5kg per 10 Sq.M. on BT surface by machine sprayer. After spreading the dust to dressed uniformly.

Measurements for Payment

Asphalt painting shall be measured as finished work, for the area specified to be covered, in Sq.M.. The area shall be the net area covered, and all allowances for wastage and cutting of joints shall be deemed to be included in the rate.

Deputy Executive Engineer

R&B Sub Division

Mehsana

Executive Engineer

R&B Division

Mehsana