

JAMNAGAR MUNICIPAL CORPORATION					
BRANCH – CIVIL					
Name of work : Annual Rate Contract of Public Latrin Strengthening works under SJMMSVY					
SCHEDULE 'B'					
Sr. No.	Description of Item	Qty.	R&B SOR 2024-25		
			Unit	Rate	Amount
1	Excavation for foundation upto 1.5mt depth incl. sorting out and stacking of useful materials and disposing off excavated stuff upto 50m lead and lift. (SOR Page No. 67, Item No. 04001A to E) (EXECUTED WITH MECHANISED EFFORTS/ MACHINARIES)				
	A) Loose or Soft Soil	1.00	Cum	124.61	124.61
	B) Dense or Hard Soil	1.00	Cum	159.48	159.48
	C) Hard Murrum	1.00	Cum	270.74	270.74
	D) Soft rock	1.00	Cum	281.87	281.87
	E) Hard rock.	1.00	Cum	636.06	636.06
2	Excavation for foundation upto 1.5mt depth incl. sorting out and stacking of useful materials and disposing off excavated stuff upto 50m lead and lift. (EXECUTED WITH MANUAL LABOUR) (SOR Page No. 71, IC. No.04B001A TO 04B001E, Item No. 0.0)				0.00
	A) Loose or Soft Soil	1.00	Cum	210.42	210.42
	B) Dense or Hard Soil	1.00	Cum	269.87	269.87
	C) Hard Murrum	1.00	Cum	460.53	460.53
	D) Soft rock not requiring blasting	1.00	Cum	540.19	540.19
	E) Hard rock.	1.00	Cum	1023.21	1023.21
3	Ex.for foundation for Depth from 1.50 to 3.0m. Incl. sorting out and stacking of useful materials and disposing of excavated stuff up to 50m. Lead. (SOR Page No. 67, Item No. 04002A to E) (EXECUTED WITH MECHANISED EFFORTS/ MACHINARIES)				0.00
	A) Loose or Soft Soil	1.00	Cum	138.16	138.16
	B) Dense or Hard Soil	1.00	Cum	173.02	173.02
	C) Hard Murrum	1.00	Cum	291.14	291.14
	D) Soft rock	1.00	Cum	305.98	305.98
	E) Hard rock.	1.00	Cum	660.16	660.16
4	Ex.for foundation for Depth from 1.50 to 3.0m. Incl. sorting out and stacking of useful materials and disposing of excavated stuff up to 50m. Lead. (SOR Page No. 71, IC. No.04B002A TO 04B002E, Item No. 0.0) (EXECUTED WITH MANUAL LABOUR)				0.00
	A) Loose or Soft Soil	1.00	Cum	232.72	232.72
	B) Dense or Hard Soil	1.00	Cum	292.18	292.18
	C) Hard Murrum	1.00	Cum	493.99	493.99
	D) Soft rock not requiring blasting	1.00	Cum	563.09	563.09

	E) Hard rock.	1.00	Cum	1063.13	1063.13
5	Filling available excavated earth (excluding hard rock) in trenches, plinth, sides of foundations etc., in layers not exceeding 20CM. in depth consolidation each deposited layer by ramming end watering. (SOR Page No. 69, Item code 04006, Item No. 4.12)	1.00	Cum	136.11	136.11
6	Filling in foundation and plinth with Murrum or selected soil in layers of 20 Cm. thickness including watering, ramming and consolidation, etc. complete. (SOR Page No. 69, Item code 04008A)	1.00	Cum	301.58	301.58
7	Providing & laying cement concrete 1: 2 : 4 (1- Cement, 2- Coarse Sand, 4- graded stone aggregates 20mm nominal size) and curing complete excluding cost of from work in (SOR Page No. 74,Item Code05010AA/BA, Item No.5.3.13)				0.00
	(A) Foundation and Plinth	1.00	Cum	3765.41	3765.41
	(B) Independent piers columns and pillars up to floor two levels.	1.00	Cum	3765.41	3765.41
8	Providing & laying cement concrete 1: 3: 6 (1- cement, 3- Coarse Sand, 6- Hand broken stone aggregates 40mm nominal size) and curing complete excluding cost of from work in (SOR Page No. 73,Item Code 05003A, Item No. 5.3.2)				0.00
	(A) Foundation and Plinth	1.00	Cum	3075.91	3075.91
9	(i) Uncoursed rubble masonry with hard stone of approved quality in foundations and plinth in Cement Mortar 1:6 (1-Cement : 6-Course sand) including levelling up etc. complete..(SOR Page No. 92, Item Code 07001AA, 07001BA)				0.00
	AA (ii) -do – in C.M. 1:6	1.00	Cum.	2567.17	2567.17
	BA(ii) -do – in C.M. 1:5	1.00	Cum.	2609.05	2609.05
10	Brick works using common burnt clay building bricks having crushing strength not less than 35kg/Sq.m. in foundation and plinth in Cement mortar 1:6 (1-Cement : 6-Fine sand) S.O.R Page No 86 Item Code 06002BA)				
	(B) Conventional	1.00	Cum.	4237.60	4237.60
11	Brick works using common burnt clay building bricks having crushing strength not less than 35kg/Sq.m. in foundation and plinth in Cement mortar 1:6 (1-Cement : 6-Fine sand) (SOR Page No.86, I.C.06003CA,)				
	(C) Fly Ash Bricks	1.00	Cum.	4408.17	4408.17
12	Extra for brick work in superstructure above plinth level upto floor two level (SOR Page No. 87, Item Code.06006B,06006C)				
	(B) Conventional	1.00	Cum.	285.57	285.57

	(C) Fly Ash Bricks	1.00	Cum.	285.57	285.57
13	Half Brick masonry in common burnt clay building bricks having crushing strength not less than 35kg/Sq.Cm. in Cement Mortar 1:4 (1-Cement : 4-coarse sand) in foundation and plinth. (SOR Page No. 89, Item Code.06008A2A)				0.00
	A2A (B) Conventional	1.00	Sq.M.	634.43	634.43
14	Half Brick masonry in common burnt clay building bricks having crushing strength not less than 35kg/Sq.Cm. in Cement Mortar 1:4 (1-Cement : 4-coarse sand) in foundation and plinth. (SOR Page No.89, I.C.06008A3, Item No.6.3)				0.00
	A3 (C) Fly Ash Bricks	1.00	Sq.M.	654.71	654.71
15	Extra for half brick masonry in superstructure above plinth level upto floor two level. (SOR Page No. 90, I.C.06010B,C ,Item No.6.32)				0.00
	(B) Conventional	1.00	Sq.M.	55.17	55.17
	(C) Fly Ash Bricks	1.00	Sq.M.	55.17	55.17
16	Half brick masonry in common burnt clay building bricks having crushing strength not less than 35 Kg/Sq.Cm. in Cement Mortar 1:3 (1-Cement : 3-coarse sand) with 2 Nos of 6mm Mild steel round bars after every three course embedded in Cement Mortar in foundation and plinth (SOR Page No. 90, Item Code.06009BA,06009CA)				0.00
	(B) Conventional	1.00	Sq.Mt.	697.17	697.17
	(C) Fly Ash Bricks	1.00	Sq.Mt.	717.46	717.46
17	Providing and laying Ordinary cement concrete 1:2:4 (1-Cement, 2-coarse sand, 4-graded stone aggregate 20mm nominal size) and finishing smooth with curing etc. complete including cost of form works but excluding the cost of reinforcement for R.C.C. work in (S.O.R Page No 77 & 78 Item Coad 05026A, 05026B, 05026C, 05026D,				0.00
	A(i) Slab upto 8cm. thickness	1.00	Cum.	8272.32	8272.32
	B(ii) Slab having more than 8 cm. and upto 10cm. thickness.	1.00	Cum.	7401.59	7401.59
	C(iii) Slab having more than 10 cm. and upto 13cm. thickness.	1.00	Cum.	6819.95	6819.95
	D(iv) Slab having more than 13 cm. and upto 15 cm. thickness.	1.00	Cum.	6241.78	6241.78
18	Providing and laying controlled cement concrete M-200 exposed work with curing etc. complete including cost of formworks but excluding the cost of reinforcement for R.C.C. work in (A) BEAMS .(S.O.R Page No 79 & 80 Item Coad 05031A1, 05031A2, 05031A3, & 05031B1, 05031B2, 05031B3)				0.00
	A1(i)having cross-sectional area more than 0.05sq.m and 0.08sq.m	1.00	Cum	8508.71	8508.71
	A2(ii)having cross-sectional area more than 0.08sq.m and 0.12sq.m	1.00	Cum	7589.70	7589.70
	A3(iii)having cross-sectional area more than 0.12sq.m and 0.18sq.m	1.00	Cum	6512.94	6512.94
19	Providing and laying controlled cement concrete M-200 exposed work with curing etc. complete including cost of formworks but excluding the cost of reinforcement for R.C.C. work in (B) COLUMNS .(S.O.R Page No 80 Item Coad 05031B1, 05031B2, 05031B3)				0.00

	B1(i)having cross-sectional area more than 0.05sq.m and 0.08sq.m	1.00	Cum	11946.20	11946.20
	B2(ii)having cross-sectional area more than 0.08sq.m and 0.12sq.m	1.00	Cum	10552.63	10552.63
	B3(iii)having cross-sectional area more than 0.12sq.m and 0.18sq.m	1.00	Cum	8906.80	8906.80
20	Providing H.Y.S.D. Bar reinforcement for R.C.C. works, including bending, binding and placing in position comp. upto floor two level etc. comp. (S.O.R Page No74 Item Coad 05014AA)	1.00	Kg.	63.24	63.24
21	Providing TMT. Bar FE 415 reinforcement for R.C.C. works, including bending, binding and placing in position comp. upto floor two level etc. comp. (S.O.R Page No 75 Item Coad 05014BA)	1.00	Kg.	67.65	67.65
22	Providing 15mm thick cement plaster in single coat on brick/concrete wall for interior plastering upto floor two level finished even and smooth in (SOR Page No. 136, I.C 17002A,17002B,17002C)				0.00
	A(i) Cement mortar 1:3 (1-Cement :3 Sand)	1.00	Sq.M.	182.86	182.86
	B(ii) Cement mortar 1:4 (1-Cement:4 Sand)	1.00	Sq.M.	163.06	163.06
	C(iii) Cement mortar 1:6 (1-Cement :6 Sand)	1.00	Sq.M.	143.08	143.08
23	Extra over item..... for finishing with a floating coating of neat cement slurry(SOR Page No. 136, I.C 17004A)	1.00	Sq.M.	51.31	51.31
24	20mm thick sand faced cement plaster on walls upto 10mt. ht. above ground level consisting of 12mm thick backing coat of C.M. 1:3 (1-Cement: 3-Sand) and 8mm thick finishing coat of C.M. 1:1 (1-Cement : 1-Sand) etc. comp. (SOR Page No. 137, I.C 17009)	1.00	Sqmt.	320.01	320.01
25	Providing cement vata (10cm x 10cm size) Quarter round in cement mortar 1:1 including neat cement finishing, watering etc. comp. (SOR Page No.138, I.C 17015)	1.00	Rmt.	24.04	24.04
26	White washing with lime on wall surface (two coats) to give an even shade including thoroughly brooming the surface to remove all dirt, dust, mortar drops and other foreign matter. (SOR Page No. 140, I.C 18001)	1.00	Sqmt.	12.87	12.87
27	Finishing wall with water proofing cement paint of on wall surfaces (two coats) to give an approved brand and manufacture and of required shade even shade after thoroughly brushing the surface to remove all dirt and remains of loose powered materials. (SOR Page No. 142, I.C 18027)	1.00	Sqmt.	61.63	61.63
28	Distempeing (Two coats) with oil bound distemper of approved brand and manufacture and of required shade on wall surfaces to give an even shade, over and including a priming coat with distemper primer of approved brand and manufacture after thoroughly brushing the surface free from mortar dropping and other foreign matter and also including preparing the surface even and sand papered smooth (SOR Page No. 141, I.C 18021)	1.00	Sqmt.	77.72	77.72

29	Providing and laying cement concrete flooring 1:2:4 (1-cement : 2-coarse sand : 4-graded stone aggregate 20mm nominal size) laid in one layer and finished with a floating coat of neat cement. (SOR Page No. 129, I.C 14015AA, 14015BA)				0.00
	(A) 40mm thick	1.00	Sq.mt.	294.60	294.60
	(B) 50mm thick	1.00	Sq.mt.	343.71	343.71

30	Providing and fixing 35 mm thick shutters for Doors, windows and clear story windows including anodised alluminium butt hinges with necessary screws. (SOR Page No. 99, I.C 10004AA,10004BA,10004CA)				0.00
	A) i Fully Paneled	1.00	Sq.mt.	4060.46	4060.46
	B) ii Fully glazed	1.00	Sq.mt.	3370.07	3370.07
	C) iii Partly paneled and partly glazed.	1.00	Sq.mt.	3715.26	3715.26
31	Providing wood works in frames of doors windows clay story window and other similer works wrought framed and fixing in position (SOR Page No. 99, I.C 10001A)				0.00
	(A) Indian teak wood	1.00	Cu.m	604.19	604.19
32	Providing & laying white glazed tiles 6mm thick in flooring trades of steps and landing laid on a bed of 12mm thick cement mortar 1:3 finished with flush pointing in white cement . (SOR Page No.127, I.C 14008AA)	1.00	Sqmt.	954.93	954.93
33	Providing and laying white glazed tiles 6 mm thick in skirting, risers of steps and dedo on 10mm thick cement plaster 1:3 (1-Cement : 3-Coarse sand) and jointed with white cement slurry (SOR Page No. 128, I.C 14009AA)	1.00	Sqmt.	1116.32	1116.32
34	Providing & fixing W.C. squatting Pan (Indian types) of size 580 mm (Earthwork, bed concrete, foot rests and trap to be measured and paid for separately) (SOR Page No. 163, I.C 23009)				0.00
	(A) Vitreous China(i) Long pattern – White colour	1.00	Each	1000.64	1000.64
35	P/F. 100mm size 'P' or 'S' Trap for W.C. squatting Pan including Jointing the trap with the Pan and Soil Pipe in C.M. 1:1 (1-Cement : 1-fine sand) etc. comp. (SOR Page No. 163, I.C 23011)				0.00
	(A) Vitreous China	1.00	Each	336.94	336.94
36	Providing & fixing in C.M. 1:3 (1-Cement : 3-Coarse sand) A Pair of White vitreous China 250 x 130 x 30mm foot rest for Long Petterns squatting Pan Water closet etc. comp. (SOR Page No.163, I.C 23012)	1.00	Each Pair	118.95	118.95
37	Providing and laying (to level or slopes) and jointing with stiff mixture of Cement Mortar in proportion 1:1, Salt glazed stoneware pipes including testing of pipes and joints complete. (SOR Page No.170, I.C 24001AA, 24001BA)				0.00
	(A) 100mm dia.	1.00	Metre	223.35	223.35
	(B) 150mm dia.	1.00	Metre	314.34	314.34
38	Providing & laying, jointing & pointing with Stiff Mixture of C.M.1:1 (1-Cement : 1-fine sand) 150 mm internal diameter Salt glazed stoneware half round channels. (SOR Page No. 171, I.C 24005A)	1.00	Rmt.	185.27	185.27

39	Providing & fixing in position C.I. cowel went to pipes (SOR Page No. 163, I.C 23006B,23006C)				0.00
	B(i) 75mm dia.	1.00	Each	389.15	389.15
	C(ii) 100mm dia.	1.00	Each	500.17	500.17
40	Providing & fixing cast iron spigot and socket soil, waste and ventilating pipes of the following nominal size. (SOR Page No. 163, I.C 23005BA,23005CA)				0.00
	B(i) 75mm dia.	1.00	Metre	733.67	733.67
	C(ii) 100 mm dia.	1.00	Metre	883.55	883.55
41	Providing upto floor two level precast cement concrete Jali or grill 1:2:4 mix (1-Cement : 2-coarse sand : 4- graded stone aggregate 6mm nominal size) reinforced with 16mm dia. Mild steel wire including roughening, cleaning, fixing and finishing in cement Mortar 1:3 and curing complete. (S.O.R Page No 75 Item Coad, 05019B,)				0.00
	(B) 40mm thick	1.00	Sq.M.	707.73	707.73
42	Providing & fixing to wall, ceiling and floor galvenised mild steel tubes (Medium grade) of the following nominal bore tube fitting & claims including making good the wall, ceiling and floor (SOR Page No.161, I.C23001AA,23001CA.)				0.00
	(A) 15mm dia.	1.00	Rmt.	249.99	249.99
	(C) 25mm dia.	1.00	Rmt.	397.97	397.97
43	Providing and fixing M.S. grills of required pattern to wooden frames of windows etc. with M.S. flats at required spacings and frame alround, square or round bars with round headed bolts and nuts or by screws. (SOR Page No.102, Item Coad 10025AA ,10025BA)				0.00
	A) Plain grill	1.00	Kg.	110.57	110.57
	B)Ornamental Grill	1.00	Kg.	165.09	165.09
44	Dismantling Sennitary fitting like washbasin, W.C. pan Indian & European type, flushing tank etc. incl. stacking the material with all lead & lift. (SOR Page No. 148, I.C 20016)	1.00	Each.	419.00	419.00
45	Providing & fixing screw down bib taps of following size. (SOR Page No. 165, I.C 23028 A1,A2 & 23028B1,B2 & 23028C1, C2)				
	(A) Brass screw down bib tap polished bright.				0.00
	A1 (i) 15mm dia.	1.00	Each	184.98	184.98
	A2 (ii) 20mm dia.	1.00	Each	212.68	212.68
	(B) Brass chromium plated screws down Bib Tap.				0.00
	B1 (i) 15mm dia.	1.00	Each.	184.98	184.98
	B2 (ii) 20mm dia.	1.00	Each.	212.68	212.68
	(c) Gun metal screw down bib tap.				0.00
	C1 (i) 15mm dia.	1.00	Each	157.29	157.29
	C2 (ii) 20mm dia.	1.00	Each	176.09	176.09

46	Supplying and fixing precast R.C.C. papadi in C.C. 1:1.5:3 including cost of form work and cost of steel size L (variable) x B (variable) x t (0.08 mt) including exposed work with curing etc. complete. (R.A.No 8.)	1.00	Cum.	12587.50	12587.50
47	Providing and laying 10cm x 15cm size Precast cement concrete beam (Pidhia) as long as required as directed by Engineer-in-charge. (R.A.No 19)	1.00	Rmt.	278.00	278.00
48	Providing and fixing Gun metal check or non return fullway wheel valve (SOR Page No. 166, I.C 23031A,C)				0.00
	(A) 15mm dia	1.00	Each	184.98	184.98
	(C) 25mm dia.	1.00	Each	416.47	416.47
49	Constructing brick masonry chamber for underground C.I. Inspection chamber and bends with bricks having crushing strength not less than 35Kg/Cm ² in C.M. 1:5 C.I. cover with frame (Light duty) 455 mm x 610 mm intenal dimensions, total weight of cover with frame to be not less than 38 Kg. (Wt. of cover 23 Kg. and Wt. of frame 15 Kg) R.C.C. top slab with 1:2:4 mix (1-Cement : 2-coarse sand :4 graded stone aggregate 20mm size) foundation concrete 1:5:10 inside plaster 15mm thick with cement mortar 1:3 finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete (SOR Page No. 174&175, I.C24016AA, 24016BA 24016CA,)				0.00
	A)455 mm. X 610 mm	1.00	Each	2903.89	2903.89
	B)500 mm. X 700 mm	1.00	Each	3624.51	3624.51
	C)600 mm. X 850 mm	1.00	Each	7109.35	7109.35
50	Extra over itemsfor every additional depth of 0.1 m or part thereof beyond 450 mm depth of brick masonry chamber(SOR Page No. 175,I.C.24017A,B,C)				0.00
	A)455 mm. X 610 mm	1.00	Each	239.99	239.99
	B)500 mm. X 700 mm	1.00	Each	262.24	262.24
	C)600 mm. X 850 mm	1.00	Each	322.37	322.37
51	Providing and fixing S.W. gully trap with C.I. grating brick masonry chamber and water tight C.I. chamber and water tight C.I. cover with frame of 300 mm x 300 mm size (inside) with standard weight (i) Square mouth traps (SOR Page No. 171, I.C 24006AA, 24006B)				0.00
	A) 100mm x 100mm size P-type	1.00	Each	1279.40	1279.40
	B) 150mm x 100mm size R-type	1.00	Each	1234.57	1234.57
52	Demolition including stacking serviceable material and disposal of un-serviceable material as all lead & lift of R.C.C. works etc. comp. (SOR Page No. 147, I.C 20002)	1.00	Cum.	1097.15	1097.15
53	Demolition bricks work & stone masonry stacking of serviceable material & disposal of unserviceable material with all lead & lift. (SOR Page No. 147, I.C 20003A,20003B)				0.00
	A) In Lime mortar	1.00	Cum.	379.26	379.26
	B) In Cement Mortar	1.00	Cum.	570.59	570.59
54	Demolition door/window/ventilating shutter incl. hig. & fast etc. comp. with all lead & lift. (SOR Page No.148, I.C 20013A,20013B)				0.00
	A) Not Exceeding 3.00 Sq.Mt. in area	1.00	Each.	194.71	194.71

	B) Exceeding 3.00 Sq.Mt. in area	1.00	Each.	260.74	260.74
55	Demolition of Plaster only of brick or C.C. wall, ceiling by chaling etc. comp. removal of unserviceable material all lead and lift for all floor etc. comp. (R.A.No 18)	1.00	Sqmt.	146.11	146.11
56	PVC pipe 10 kg/ sqcm (SOR Page No.16, I.C M442 to, M448)				0.00
	(1) 20 mm dia	1.00	Rmt	22.03	22.03
	(2) 25 mm dia	1.00	Rmt	31.36	31.36
	(3) 32 mm dia	1.00	Rmt	39.83	39.83
	(4) 40 mm dia	1.00	Rmt	59.32	59.32
	(5) 50 mm dia	1.00	Rmt	57.63	57.63
	(6) 75 mm dia	1.00	Rmt	160.17	160.17
	(7) 110 mm dia	1.00	Rmt	273.73	273.73
57	RCC precast manhole frame & cover manufacture, supply & delivery at site of work precast RCC M-20 frame & cover suitable to drainage M.H. And as per type design & drawing including cost of reinforcement M.S. Angle or flat, curing mld work etc. (GWSSB-2022-23 part-1&2 (material sec) page no-16,17 Item No.10.4 A,10.4 B to 10.4 C)				0.00
	Heavy duty				
	(a) Frame suitable to 50 cm opening of MH	1.00	Nos.	1255.00	1121.00
	(b) Cover suitable to 50 cm opening of MH	1.00	Nos.	1314.00	1173.00
	Light duty				
	(a) Frame suitable to 50 cm opening of MH	1.00	Nos.	1120.00	1000.00
	(b) Cover suitable to 50 cm opening of MH	1.00	Nos.	1194.00	1066.00
	House connection Chamner light duty				
	Frame	1.00	Nos.	911.00	813.00
	Cover	1.00	Nos.	1030.00	920.00
58	P / S & fixing precast FRC - RCC manhole frame and cover in M - 25 grade square opening size 300 mm dia as per IS code 12592 / 2002 and as per drawing & design including all taxes, freight, loading unloading carting etc. comp.(R.A.-9)	1.00	nos	742.00	742.00
59	Constructing brick masonry chamber for underground Inspection chamber and bends with bricks having crushing strength not less than 35Kg/Cm2 in C.M. 1 : 6 with foundation concrete 1 : 3 : 6 inside plaster 15mm thick with cement mortar 1:3 finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete (R.A -7) (0.45 M X0.45 M X 0.45 M SIZE)	1.00	Nos	1996.00	1996.00
60	Providing corrugated G.I. sheet of class-3 roofing fixed with glavanished iron J or L Hooks, Bolts and nuts 8mm diameter with bitumen and G.I. limpet washer or G.I. limpet washer. filled with white lead complete excluding the cost of purlins, Rafters and Trusses.(1) 0.80 mm thick sheet (SOR P NO.131 IC 15001A/15.1)				0.00
	(1) 0.80 mm thick sheet	1.00	Sqmt.	726.92	726.92
61	Supplying, spreading and stacking 20 to 25 mm size crushed metal with all lead and lift (Sor P. No. 179 R.A.2)	1.00	Cum	597.00	597.00

62	Supplying and spreading soft murrum or hard murrum as per requirement and instruction of engineer-in-charge with all lead and lift including to required gradient and level (SOR P NO. 172 IC 26016B/26.13)	1.00	Cum	147.06	147.06
63	Providing laying (to level or slopes) and jointing reinforced concrete Light duty non-pressure pipes I.S. class NP2 of the following internal diameter with collars and butt ends prepared for collar joints including testing of joints complete.(SOR Page No.171&172 , I.C 24007BA, 24007CA, 24007DA,24007EA, 24007FA, 24007GA)				
	(A) 150mm	1.00	Rmt.	254.65	254.65
	(B) 250mm	1.00	Rmt.	356.29	356.29
	(C) 300mm	1.00	Rmt.	671.32	671.32
	(D) 450mm	1.00	Rmt.	1066.52	1066.52
	(E) 500mm	1.00	Rmt.	1240.10	1240.10
	(F) 600mm.	1.00	Rmt.	1387.11	1387.11
64	Providing erecting and fixing double coated ISI water tank of required capacity each with all necessary fittings and connection etc. complete on terrace (SOR Page No.158 I.C 22014)	1.00	Per Ltr.	3.91	3.91
65	Supplying Hand Bracker (M.R.)	1.00	one hours	800.00	800.00
66	Applying two coats of putty & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth.(SOR Page No.146, I.C 19032.)	1.00	sqmt.	40.19	40.19
67	Wall painting (two coats) with plastic emulsion paint of approved brand and manufacture on undecorated wall surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth. (SOR Page No.142 I.C 18031)	1.00	sqmt.	85.52	85.52
68	Plasticier liquid sikkaism chemical (M.R)	1.00	ltr.	110.00	110.00
69	Distempeing (Two coats) with oil bound distemper of approved brand and manufacture and of required shade on wall surfaces to give an even shade, over and including a priming coat with distemper primer of approved brand and manufacture after thoroughly brushing the surface free from mortar dropping and other foreign matter and also including preparing the surface even and sand papered smooth (SOR Page No. 141, I.C 18021)	1.00	sqmt.	77.72	77.72
70	Distempeing (Two coats) with oil bound washable distemper of approved brand and manufacture and of required shade on wall surfaces to give an even shade, over and including a priming coat with alkali resistance primer of approved brand after thoroughly brushing the surface and other foreign matter and also including preparing the surface even and sand papered smooth. (SOR Page No. 141, I.C 18022)	1.00	sqmt.	77.72	77.72
71	extra over item no for every subsequent coat of approved brand and manufacture (SOR Page No 142, I.C 18024)	1.00	sqmt.	31.67	31.67

72	Providing and fixing to wall ceiling and floor 6.0 Kg. F/Cm2 working pressure poluthene pipes of the following outside Dia. Low density, complete with special falnge compression type fittings, wall clipsetc. including making good the wall ceiling and floor. (SOR Page No.162, I.C 23004A, 23004B, 23004C, 23004D, 23004E)				0.00
	(A) 20 mm	1.00	Sqmt.	83.98	83.98
	(B) 25 mm	1.00	Sqmt.	108.54	108.54
	(C) 32 mm	1.00	Sqmt.	125.22	125.22
	(D) 40 mm	1.00	Sqmt.	147.82	147.82
	(E) 50 mm	1.00	Sqmt.	190.12	190.12
73	Providing & laying cement concrete work 1: 1.5 : 3 (1-cement, 1.5- Coarse Sand, 3- graded stone aggregates 20mm nominal size) and curing complete excluding cost of form work in (R.A.No 14)				0.00
	A) Foundations, footings, base or columns and mass concrete.	1.00	Cum	4323.15	4323.15
	B) Slabs, landings, sleeves, balconies lintels, beams, girders cantilever up to floor two level.	1.00	Cum	4412.10	4412.10
	C) Columns, pillars posts and struts up to floor level.	1.00	Cum	4412.10	4412.10
	D) Staircases excluding landing up to floor two level.	1.00	Cum	5171.11	5171.11
	E) Vertical and horizontal fins up to floor two levels.	1.00	Cum	4640.17	4640.17
74	Supplying Hydraulics Excavator. (Item coad H016 Pg. No. 61)	1.00	One Hours	711.86	711.86
75	Supplying JCB Bracker (M.R.)	1.00	One Hours	1500.00	1500.00
76	Providing and supplying in standard length ISI mark rigid unplasticised PVC Casing including all local and central taxes, transportation, freight charges, octroi, inspection charges, loading, unloading, conveyance to the departmental stores etc. complete. (G.W.S.S.B. S.O.R. 2022-23 Page No – 6,7 , Item No – 3.1.B,3.1.D)				
	1) 6 Kg/cm ²				
	150 mm	1.00	R.mt	511.00	511.00
	200 mm	1.00	R.mt	911.00	911.00
I / We am / are willing to carry out above work at % above / below. In words percentage above / below the tender rate, which mentioned above.					
DATE:					
			Deputy Engineer		
	Signature of Contractor		Civil..... Zone - ()		
			Jamnagar Municipal Corporation		