

**KARNATAKA POWER TRANSMISSION CORPORATION**  
**LIMITED**

**TECHNICAL SPECIFICATION**

**SECTION –  
FURNITURE**

VOLUME – IIA

TECHNICAL SPECIFICATION

SECITON - 10

FURNITURE

Sl. No.	Particulars
1.0	General
2.0	Qualifying Requirements
3.0	Standards
4.0	Steel Almirah (61/2)
5.0	Officer's Table
6.0	Steel slotted/Angle Rack (Big)
7.0	Steel slotted/Angle Rack (Small)
8.0	Steel Dust
9.0	Executive Revolving chair with full high back with Head Rest
10.0	'S' type contnous arm chair with cushion test & back
11.0	Steel folding chair wt. 3.7 kg
12.0	Establishing type of Brands



# TECHNICAL SPECIFICATION

## SECITON -

### FURNITURE

#### 1.0 GENERAL :

This specification covers design, Engineering, Manufacturing, Testing and Delivery at site of furniture required for 110 KV and 66 KV stations.

#### 2.0. QUALIFYING REQUIREMENTS:

Please refer Volume – I, Section –I - IFB.

#### 3.0. STANDARDS:

Equipments offered shall confirm to relevant Indian Standards equivalent or Higher International Standards.

#### 4.0 STEEL ALMIRAH (6 ½ INCH)

Size H 1.83 m x W 0.915 m x D 0.48 m (excluding leg of 15.24 Cms) fitted with four fixed shelves making five compartments, double door with three way locking device and duplicate keys, all joints out side and inside should be spot or arc welded and neatly finished by grinding.

The edges of doors and shelves should be properly bent to 'U' shape of 25 mm width to ensure good strength and the outer edge of U bent of the door lengthwise should be double folded and neatly finished. The shelves front side should be bent to U shape neatly and finished to avoid any possible cuts to fingers and hand when handled. Longitudinal rib of 15.24 Cms. Wide including bent to required shape should be provided and fixed to each door at the centre. The breath of the shelf in the almirah should be to the entire width leaving about 12 mm gap from the shutter when it is closed.

#### 4.1 LOCKING DEVICE:

Three way locking device with 10 guage M.S sheet for locking and level plate and with locking rod of 10 mm dia with strong bracket at top and bottom to hold the locking rod with six lever lock should

be provided 65 mm size, lever strong locks to be fixed. Handle should be made out of brass, cast alloy with nickel chromo-plated. Lock should be fixed. Handle should be made out of Brass cast alloy with chrome plated. Lock should be similar to Godrej type.

#### 4.2 STEEL ALMIRAH WITH GLASS PANEL DOORS:

Size H 1.83 m x W 0.915 m x D 0.48 m (excluding leg of 15.24 cm) fitted with four fixed shelves making five compartments doubled door with three way locking device and duplicate keys, all joints outside and inside should be spot or arc welded and neatly finished by grinding. The outside corner should be rounded off to give good appearance. The edges of doors and shelves should properly bent to U-shape of 25mm width to ensure good strength and outer edge of U-bent of the door length wise should be double folded and neatly finished. The shelves front side should be bent to U-shape neatly and finished to avoid any possible cuts to fingers and hand when handled. Longitudinal rib of 15.24 cm wide including bent to required shape should be provided and fixed to each door at the centre.

The breadth of the shelf in the Almirah should be to the entire width leaving about 12mm gap from the shutter when it is closed. But with glass door fitted with four fixed shelves making five compartments. Two-way locking systems with 100 x 37-mm brass six lever locks to be provided. The glass panels for doors shall be 4mm thick clear glass should be provided. The glass panels should be fixed with fully covered plate around both inside and outside. Handle should be made out of brass cast alloy. Locks should be similar to Godrej type with suitable locking device.

#### 5.0 OFFICER'S TABLE:

Have overall size 1.93 m W x 0.786 m H With laminated top. There shall be three drawers with automatic locking device on the right side and a cupboard with a shelf on the left side with square legs of section 25 mm x 25 mm 16 G. The top shall be of 20mm thick laminated block board with 32mm thick V-shape teakwood internal beading nicely polished with two coats of colourless polish. The table shall be confirmed to Godrej T - 102/D. The table shall be derusted. Premier coated and painted with enamel paint as per indentors choice. All components shall be made out of MS sheet of 20G.

#### 6.0 STEEL SLOTTED ANGLE RACK (BIG):

Size 1.80 m x 0.9 m x 0.375 m overall with four upright and five panels, the uprights shall be slotted angle of section 40 x 40 x 2 mm and the panels of size 900 mm x 375 mm x 20 G. The panels should be fixed to the upright by means of GI bolts of size 8 mm x 16 mm by providing 16 nos. standard gussets and corners. The rack shall be painted as per indetors choice.

#### 7.0 STEEL SLOTTED ANGLE RACK (SMALL):

Size 0.90 m x 0.9 m x 0.375 m overall with four uprights and three panels. The uprights shall be slotted angles of section 40 x 40 x 2 mm and the panels of size 900 mm x 375 mm x 20 G. The panel should be fixed to the uprights by means of G.I. bolts of size 0.079 mm x 0.158 mm by providing 16 nos. standard gussets at corners. The rack shall be painted as per indetors choice.

#### 8.0 STEEL DUST BIN:

Made out of 22G MS sheet. The size of the dustbin shall be 27.94 cm square at the top and 20.32 cm. square at the bottom with a height of 30.48 cm. A sheet leg shall be provided for a height of 5 cm. The dustbin shall derusted primer coated and painted with synthetic enamel paint as per indetors choice.

## 9.0 EXECUTIVE REVOLVING CHAIR WITH FULL HIGH BACK WITH HEAD REST

Executive revolving chair with tilting and revolving arrangement of standard size 12.7 cm thick foam for the seat and 10.2 cm thick foam for the back covered with feather touch Bohr Rexin. The chair shall be with full high back with head rest and to be fitted on the MS (tubular) revolving base with 5 frongs fitted with ball casters. The colour and shade of rexin cloth as per the indentors choice.

## 10.0 'S' TYPE CONTINUOUS ARM CHAIR WITH CUSHION SEAT AND BACK

The frame shall be made from MS tubular pipe of 16 guage and with 25 mm outer dia. The size of the chair frame shall be 89 cm. height 51 cm depth, 53 cm width properly bent to its required shape and neatly nickled chrome plated or powder coated of approved colour. The seat and back shall be 50 – mm thick foam cushioned on teak wood frame and neatly upholstered with Bohr Rexin. The arm rest also shall be cushioned and upholstered. Four rubber shoes shall be provided at the bottom of the chair frame.

## 11.0 STEEL FOLDING CHAIR Wt. 3.7 Kg (91.45)

Tubular frame sizes height 94 cm. when folded seat sizes 39.3 cm. deep and 45.7 cm high from the floor. Back rest about 20.3 cm wide. The tubular frame should be 22 mm OD (IS gauge) ERW or gas welded steel tube and cross pipe of 16mm OD (20 gauge) steel tubes. The cross pipes are fixed to the leg pipes by strong rivets. 22 G CRCA steel should be used for the seat and back plate is neatly pressed to the required contour with rounded corners and fixed on the tabular frame by self tapping services in such a way that the chair could be folded and opened easily. Connecting 4 lever plates 80 mm x 20 mm 10 gauge thick to be fixed at the top junction of the front and rear legs and top end of rear legs. Hard plastic shoes should be provided at the bottom of the front and rear legs and top end of rear legs. The chairs are finished by spray or stove enamel in standard colours.

## 12.0 Establishing type of brands: Godrej/chandan/Featherlite/reputed make.