

Name of work : - Providing Asphalt Painting on various road of Kalavad Taluka package No. JAM/ KLD/ AP /2025-26 /P-01

Testing Schedule

Sr.No.	Materials	Name of Laboratory Test	Frequency of Test	Total Nos. of Test to be carried out	Remarks
1	B.M., Carpet, Seal Coat B.M. :- Crushed aggregate 20 to 25mm 12 to 20mm 10 to 12mm Stone dust Carpet : 10 to 20mm 6 to 10mm Seal Coat :- Crushed aggregate 6mm grit 3. Asphalt	1. Aggregate Impact value 2. Flakiness Index 3. Gradation 4. Abrasion 5. Stripping value and water absorption 6. Crushing strength 7. Temperature of binder 8. Binder contents 9. Gradation at plant site 10. Rate of spreading of materials 11. Quality of binder (Asphalt) For tack coat 1- Binder temperature 2- Rate of spreading of binder	Upto 100 Cum - 1 Test 101 to 500 Cum - 3 Test 501 to 1500 Cum - 5 Test 1501 to 5000 Cum - 7 Test At regular interval Two test per day per plant Two test per day per plant Regular control thoroughly at joint on materials and layer thickness No. of Tenker No. of Test 1 to 10 1 11 to 20 2 21 to 50 3 51 to 100 4 Above 100 1 Test per Each 50 Tanker At regular close interval Two test per day	 3 Test 3 Test 3 Test 3 Test 3 Test 1 Test 3-Test 1- Test	

Signature of Contractor

Executive Engineer
Panchayat (R&B) Division
Jamnagar.