

Annexure-III

Cantilever assembly consists of following components as follows:-

RI no.	Description of Components	Qty per Unit
3020-1, 3021-1	Mast fitting for hook insulator (Forged) with 2 off bolts, nuts, lock nuts and washers of 16 dia.	1 Set
2400, 2403-2	Tubular stay arm assembly (including galvanised steel tube)	1 Set
2110/2130/2380	Catenary suspension bracket assembly or hook bracket	1 off
1160	Suspension clamp	1 Off
2120/2140, 2040, 2080	Bracket tube assembly complete with tube cap and sleeve where required (including galvanised steel tube)	1 Set
3070-1 & 2, 3073-1, 3074-1	Mast bracket fitting assembly including 2 off bolts, nuts, lock nuts and washers of 16 mm for attachment to structure or to small part steel work	1 Set
2151-2, 2152-2, 2161-2, 2162-2	Register arm hook Top & Bottom complete (Forged) with bolts, nuts and lock nuts	1 Off
2420 or 2430, 2270-4 or 5, 2422-2	Register arm assembly or raised register arm assembly (including galvanised steel tube)	1 Set
2460, style-02 or 2470- style-02	Register arm dropper assembly complete with bolts, nuts etc	1 Set
2391-1, 2540	Steady arm hook (BFB) (Forged) arm (Where required)	As required
2361-1, 2491-2, 2492-2	25mm drop bracket (Forged) with bolts & lock nuts. 25mm Steady arm clamp (Forged) with bolts & lock nuts)	--Do--
1220/1373-1	Contact wire swivel clip or raised register arm clamp	1 Off
2550-1/2	Anti-wind clamp	As required
1374	Packing Saddle (For RRA)	1 Off
1174	Packing Saddle (For Suspension bracket)	1 Off

Note: i) Materials not included in the above list are to be assessed by the tenderer duly surveying the work site and must supply it with the approval of Railway.

ii) The whole assessment of materials of cantilever assembly must suit requirement at work site or as per instruction of Railway.