



2	LAYOUT FACING POINT 1 IN 12 TURNOUT B.G. ON P.S.C. SLEEPERS FITTED WITH IRS ELECTRIC Pt M/C (60 Kg & 52 Kg)	RDSO/S 3261-62
2	LAYOUT FACING POINT B.G. FITTED WITH HIGH THRUST ROTARY LOCK TYPE POINT M/C (WITH PIN JOINT) (52 Kg & 90 R)	RDSO/S 3262-63
2	LAYOUT FACING POINT 1 IN 12 TURNOUT B.G. WITH THICK WEB TONGUE RAIL ON PSC. SLEEPERS FITTED WITH IRS POINT MACHINE 220 mm STROKE (60 Kg & 52 Kg)	RDSO/S 3465-66

NO.	DESCRIPTION	NO.
OFF.	FOR ASSEMBLY.	

R. D. S. O.

LEADING STRETCHER BAR
-INSULATING BUSH

MATL	THERMOPLASTIC
&	POLY URETHANE
	MOULDED
SPEC	INSULATION
	RDSO/SPN/S/168/02
	IRS : S 23

SCALE	MILLIMETRES
	10 0 20 40
	DO NOT SCALE

1. ALL DIMENSIONS IN MILLIMETRES.

NOTE

STAND	
CANCLD	
REVD	
S	8813