



MATL	THERMOPLASTIC
&	POLY URETHANE
SPEC	MOULDED INSULATION
	RDSO/SPN/S/168/02
	IRS : S 23
SCALE	MILLIMETRES
	10 0 10 20
	DO NOT SCALE

1. ALL DIMENSIONS IN MILLIMETRES.

NOTE

FOUR FOR EACH	LAYOUT-FACING POINT 1 IN 12 TURNOUT B.G. ON PSC. SLEEPERS FITTED WITH IRS ELECT. Pt. M/C (60 Kg & 52 Kg)	RDSO/S 3361-62
FOUR FOR EACH	LAYOUT-FACING POINT B.G FITTED WITH HIGH THRUST ROTARY LOCKING TYPE POINT Pt.M/C (WITH PIN JOINT) (52 Kg & 90 R)	RDSO/S 3262-63
FOUR FOR EACH	LAYOUT-FACING POINT 1 IN 12 TURNOUT B.G. WITH THICK WEB TONGUE RAIL ON PSC. SLEEPERS FITTED WITH IRS Pt. M/C 220 mm STROKE (60 Kg & 52 Kg)	RDSO/S 3465-66
FOUR FOR EACH	LAYOUT-1 IN 12 TURNOUT B.G. 60 Kg. (WITH ZU1-60 THICK WEB TONGUE RAIL) ON PSC SLEEPERS FITTED WITH IRS Pt M/C (220 mm STROKE) FOR INDEPENDENT SWITCH LOCKING & CLAMP POINT LOCK (160 mm THROW OF POINT)	RDSO/S 3454
FOUR FOR EACH	LAYOUT-1 IN 12 TURNOUT B.G. 52 Kg. (WITH ZU1-49 THICK WEB TONGUE RAIL) ON PSC SLEEPERS FITTED WITH IRS Pt M/C (220 mm STROKE) FOR IND. SWITCH LOCKING & CLAMP POINT LOCK (160 mm THROW OF POINT)	RDSO/S 3455
NO. OFF.	DESCRIPTION	NO.
	FOR ASSEMBLY.	

R. D. S. O.		
SWITCH EXTENSION BRACKET -INSULATION BUSH		
STAND		
CANCLD		
REVD		
S 23199		

ALT. DESCRIPTION DATE