


1. ALL DIMENSIONS IN MILLIMETRES.

NOTE

MATL	THERMOPLASTIC POLY URETHANE
&	MOULDED
SPEC	INSULATION RDSO/SPN/S/168/02 IRS : S 23
SCALE	MILLIMETRES 10 0 10 20  DO NOT SCALE

ALT.

DESCRIPTION

DATE

ONE FOR EACH	LAYOUT 1 IN 12 TURNOUT B.G. 52 Kg. (WITH ZU2- 49 THICK WEB TONGUE RAIL) ON PSC SLEEPERS FITTED WITH I.R.S. Pt M/C (220 mm STROKE) FOR INDEPENDENT SWITCH LOCKING AND CLAMP POINT LOCK (160 mm THROW OF POINT)	RDSO/S 3455
ONE FOR EACH	LAYOUT 1 IN 12 TURNOUT B.G. 60 Kg. (WITH ZU1- 60 THICK WEB TONGUE RAIL) ON PSC SLEEPERS FITTED WITH I.R.S. Pt M/C (220 mm STROKE) FOR INDEPENDENT SWITCH LOCKING AND CLAMP POINT LOCK (160 mm THROW OF POINT)	RDSO/S 3454
NO. OFF.	DESCRIPTION	NO.
FOR ASSEMBLY.		
R. D. S. O.		
DRIVE ROD LUG - BUSH (FOR THICK WEB SWITCHES)		
STAND		
CANCLD		
REVD		
RDSO/S 3463		