

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

DRM WA BRC acting for and on behalf of The President of India invites E-Tenders against Tender No **DRM-BRC-052-OF-2026-27** Closing Date/Time 02/07/2026 15:00 Hrs. Bidders will be able to submit their original/revised bids upto closing date and time only. Manual offers are not allowed against this tender, and any such manual offer received shall be ignored.

1. NIT HEADER

| | | | |
|--------------------------------------|--|--|------------------------------------|
| Name of Work | ST-BRC and AKV-Raj Section:- Extension of high-level platforms at AKV and MYG stations, provision of lifting barriers and duty bunks at level crossings in Ankleshwar - Rajpipla Section, and provision of a track circuit maintenance room at Ankleshwar. | | |
| Bidding type | Normal Tender | | |
| Tender Type | Open | Bidding System | Single Packet System |
| Tender Closing Date Time | 02/07/2026 15:00 | Date Time Of Uploading Tender | 09/06/2026 22:34 |
| Pre-Bid Conference Required | No | Pre-Bid Conference Date Time | Not Applicable |
| Advertised Value | 26053941.19 | Tendering Section | WORKS |
| Bidding Style | Single Rate for Each Schedule | Bidding Unit | |
| Earnest Money (Rs.) | 521100.00 | Validity of Offer (Days) | 60 |
| Tender Doc. Cost (Rs.) | 0.00 | Period of Completion | 9 Months |
| Contract Type | Works - General | Contract Category | Expenditure |
| Bidding Start Date | 18/06/2026 | | |
| Are JV allowed to bid | No | Number of JV Member Allowed | 0 |
| Are Consortium allowed to bid | No | Number of Consortium Member Allowed | 0 |
| Ranking Order For Bids | Lowest to Highest | Expenditure Type | Combined (Revenue + Capital Works) |

2. SCHEDULE

| S.No. | Item Code | Item Qty | Qty Unit | Unit Rate | Basic Value | Escl.(%) | Amount | Bidding Unit |
|--|--|----------|----------|-----------|-------------|-----------|-------------|---------------------|
| Schedule () A-USSOR Items Chapter 18 only | | | | | | | 2202855.97 | Above/ Below/Par |
| 01 | Please see Item Breakup for details. | | | | 2202855.97 | AT Par | 2202855.97 | |
| | Description:- USSOR Items Chapter 18 only | | | | | | | |
| S.No. | Item Code | Item Qty | Qty Unit | Unit Rate | Basic Value | Escl.(%) | Amount | Bidding Unit |
| Schedule () B-USSOR Items Chapter 21 only | | | | | | | 218840.57 | Above/ Below/Par |
| 02 | Please see Item Breakup for details. | | | | 244514.60 | (-) 10.50 | 218840.57 | |
| | Description:- USSOR Items Chapter 21 only | | | | | | | |
| S.No. | Item Code | Item Qty | Qty Unit | Unit Rate | Basic Value | Escl.(%) | Amount | Bidding Unit |
| Schedule () C-DSR 2023 Items | | | | | | | 22475863.53 | Above/ Below/Par |
| 03 | Please see Item Breakup for details. | | | | 33052740.49 | (-) 32.00 | 22475863.53 | |
| | Description:- DSR 2023 Items | | | | | | | |
| S.No. | Item Code | Item Qty | Qty Unit | Unit Rate | Basic Value | Escl.(%) | Amount | Bidding Unit |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| Schedule () D-NS Item of Tactile Tile | | | | | | | 206692.12 | Above/ Below/P ar |
|---|---|----------|----------|-----------|-------------|-----------|-----------|-------------------------|
| 04 | Please see Item Breakup for details. | | | | 229938.95 | (-) 10.11 | 206692.12 | |
| | Description:- NS Item of Tactile Tile | | | | | | | |
| S.No. | Item Code | Item Qty | Qty Unit | Unit Rate | Basic Value | Escl.(%) | Amount | Bidding Unit |
| Schedule () E-NS Item of PLATFORM WALL | | | | | | | 883614.00 | Above/ Below/P ar |
| 05 | Please see Item Breakup for details. | | | | 1311000.00 | (-) 32.60 | 883614.00 | |
| | Description:- NS Item of PLATFORM WALL | | | | | | | |
| S.No. | Item Code | Item Qty | Qty Unit | Unit Rate | Basic Value | Escl.(%) | Amount | Bidding Unit |
| Schedule () F-Power NS Items | | | | | | | 61085.00 | Above/ Below/P ar |
| 06 | Please see Item Breakup for details. | | | | 61085.00 | AT Par | 61085.00 | |
| | Description:- NS Items | | | | | | | |
| S.No. | Item Code | Item Qty | Qty Unit | Unit Rate | Basic Value | Escl.(%) | Amount | Bidding Unit |
| Schedule () G-NS Items for LED | | | | | | | 4990.00 | Above/ Below/P ar |
| 07 | Please see Item Breakup for details. | | | | 4990.00 | AT Par | 4990.00 | |
| | Description:- NS Item for LED | | | | | | | |

3. ITEM BREAKUP

| Schedule | Schedule A-USSOR Items Chapter 18 only | | | | | | |
|----------|--|--|------|------|----------|-----------|--|
| Item- 01 | USSOR Items Chapter 18 only | | | | | | |
| S No. | Item No | Description of Item | Unit | Qty | Rate | Amount | |
| 1 | 181040 | Dismantling existing lifting barrier along with winch assembly and other components like boom, fringes, locking arrangements, pedestal, boom rest, locking rods/wires, pulley stakes, turn out wheels, 'A' base and other materials connected with functioning of lifting barrier, removing engineering indicators on track and level crossing road signages without any damage including demolishing concrete base of existing structures, filling, ramming and levelling the ground disturbed during demolition, clearing debris and stacking all released material in a neat and countable manner and clear of infringements, as directed. Note: Barriers on both sides of level crossing constitute one set. | Set | 5.00 | 23293.05 | 116465.25 | |
| | | Manufacture, supply, assembly, erection, commissioning and testing of Lifting Barrier assembly, having fragmented boom, boom light boxes with suitable gate lamps, bell, boom supports (stay wires) with adjusters, counter weight, pedestal and lock posts with foundation of 'A' type as required, turn-union wheel with brackets, balance and auxiliary weights clamps etc. to approved standard drawing with all fittings and fastenings excluding fringes, complete with contractor's men, equipments and materials, as per specifications and as directed. | | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|-----------------|--|--|-------------|------------|--------------|-------------------|
| 2 | 185042 | Above 6m and up to 8m long Lifting Barrier | Set | 6.00 | 294806.54 | 1768839.24 |
| 3 | 185043 | Above 8m and up to 10m long Lifting Barrier | Set | 1.00 | 317551.48 | 317551.48 |
| | | | | | Total | 2202855.97 |
| Schedule | Schedule B-USSOR Items Chapter 21 only | | | | | |
| Item- 02 | USSOR Items Chapter 21 only | | | | | |
| S No. | Item No | Description of Item | Unit | Qty | Rate | Amount |
| | | Hiring of machinery for minor miscellaneous works for short duration including operator/driver, fuel, lubricants and consumable. The contractor shall arrange all statutory permits as required by rules and regulations prevailing in the area of work. Payment shall be made for actual working hours at site. | | | | |
| 1 | 211201 | JCB Backhoe Loaders 3DX Plus or similar with minimum 1.10 cum bucket capacity | Hour | 100.00 | 846.09 | 84609.00 |
| 2 | 211202 | Hydra or similar tyre mounted Pick-n-Carry crane of 12T capacity for misc. works of handling of material | Hour | 50.00 | 2118.40 | 105920.00 |
| 3 | 211203 | Tractor with Trolley for local transportation or other misc. works. | Hour | 90.00 | 599.84 | 53985.60 |
| | | | | | Total | 244514.60 |
| Schedule | Schedule C-DSR 2023 Items | | | | | |
| Item- 03 | DSR 2023 Items | | | | | |
| S No. | Item No | Description of Item | Unit | Qty | Rate | Amount |
| | 2.0 | EARTH WORK | | | | |
| | 2.1S | General | | | | |
| | 2.6 | Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and for all lift, as directed by Engineer-in-charge. | | | | |
| 1 | 2.6.1 | All kinds of soil | cum | 965 | 177.5 | 171287.5 |
| 2 | 2.25 | Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20 cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 and for all lift. | cum | 1540 | 196 | 301840 |
| 3 | 2.25A | Excavating, supplying and filling of local earth (including royalty) by mechanical transport upto a lead of 5km also including ramming and watering of the earth in layers not exceeding 20 cm in trenches, plinth, sides of foundation etc. complete. | cum | 452 | 700.5 | 316626 |
| | 2.26 | Extra for every additional lift of 1.5 m or part thereof in excavation / banking excavated or stacked materials. | | | | |
| 4 | 2.26.1 | All kinds of soil | cum | 177 | 126.8 | 22443.6 |
| 5 | 2.27 | Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete. | cum | 117 | 2123.75 | 248478.75 |
| | 4.0 | CONCRETE WORK | | | | |
| | 4.1S | CEMENT CONCRETE (CAST IN SITU) | | | | |
| | 4.1 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|--------|--|-----|-------|----------|-----------|
| 6 | 4.1.3 | 1:2:4 (1 cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size derived from natural sources) | cum | 153 | 7878.5 | 1205410.5 |
| 7 | 4.1.5 | 1:3:6 (1 Cement : 3 coarse sand (zone-III) derived from natural sources : 6 graded stone aggregate 20 mm nominal size derived from natural sources) | cum | 92 | 7294.7 | 671112.4 |
| | 5.0 | REINFORCEMENT CEMENT CONCRETE | | | | |
| | 5.1S | CAST IN SITU | | | | |
| | 5.1 | Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : | | | | |
| 8 | 5.1.2 | 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources) | cum | 17 | 9045.75 | 153777.75 |
| | 5.2 | Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement : | | | | |
| 9 | 5.2.2 | 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources) | cum | 17 | 10852.95 | 184500.15 |
| | 5.9S | FORM WORK | | | | |
| | 5.9 | Centering and shuttering including strutting, propping etc. and removal of form for | | | | |
| 10 | 5.9.1 | Foundations, footings, bases of columns, etc. for mass concrete | Sqm | 704 | 392.15 | 276073.6 |
| 11 | 5.9.2 | Walls (any thickness) including attached pilasters, buttresses, plinth and string courses etc. | Sqm | 324 | 842.5 | 272970 |
| 12 | 5.9.3 | Suspended floors, roofs, landings, balconies and access platform | Sqm | 409 | 927.25 | 379245.25 |
| 13 | 5.9.5 | Lintels, beams, plinth beams, girders, bressummers and cantilevers | Sqm | 333 | 736.4 | 245221.2 |
| 14 | 5.9.6 | Columns, Pillars, Piers, Abutments, Posts and Struts | Sqm | 536 | 961.3 | 515256.8 |
| | 5.12S | PRE-CAST RCC | | | | |
| 15 | 5.12 | Providing, hoisting and fixing above plinth level up to floor five level precast reinforced cement concrete work in string courses, bands, copings, bed plates, anchor blocks, plain window sills and the like, including the cost of required centering, shuttering but , excluding cost of reinforcement with 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources). | cum | 97 | 10585.9 | 1026832.3 |
| | 5.22S | STEEL REINFORCEMENT | | | | |
| | 5.22 | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. | | | | |
| 16 | 5.22.6 | Thermo-Mechanically Treated bars of grade Fe-500D or more. | Kg | 41138 | 107.85 | 4436733.3 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|----------|---|---------|-------|---------|-----------|
| | 5.22A | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level. | | | | |
| 17 | 5.22A.6 | Thermo-Mechanically Treated bars of grade Fe-500D or more. | Kg | 10240 | 107.85 | 1104384 |
| | 5.33S | DESIGN MIX CONCRETE | | | | |
| | 5.33 | Providing and laying in position ready mixed or site batched design mix cement concrete for reinforced cement concrete work; using coarse aggregate and fine aggregate derived from natural sources, Portland Pozzolana / Ordinary Portland /Portland Slag cement, admixtures in recommended proportions as per IS: 9103 to accelerate / retard setting of concrete, to improve durability and workability without impairing strength; including pumping of concrete to site of laying, curing, carriage for all leads; but excluding the cost of centering, shuttering, finishing and reinforcement as per direction of the engineer-in-charge, for the following grades of concrete.: | | | | |
| | 5.33.1 | All works upto plinth level | | | | |
| 18 | 5.33.1.1 | Concrete of M25 grade with minimum cement content of 330 kg /cum | cum | 440 | 9504.75 | 4182090 |
| | 5.33.2 | All works above plinth level upto floor V level | | | | |
| 19 | 5.33.2.1 | Concrete of M25 grade with minimum cement content of 330 kg /cum | cum | 126 | 9860.4 | 1242410.4 |
| 20 | 5.35 | Add for using extra cement in the items of design mix over and above the specified cement content therein. | Quintal | 172 | 733.5 | 126162 |
| | 6.0 | MASONRY WORK | | | | |
| | 6.1S | General | | | | |
| | 6.1 | Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: | | | | |
| 21 | 6.1.2 | Cement mortar 1:6 (1 cement : 6 coarse sand) | cum | 38 | 7132.25 | 271025.5 |
| | 6.12S | HALF BRICK MASONRY | | | | |
| | 6.13 | Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. | | | | |
| 22 | 6.13.2 | Cement mortar 1:4 (1 cement :4 coarse sand) | Sqm | 9.2 | 1123.8 | 10338.96 |
| | 6.26S | EXPOSED BRICK WALL | | | | |
| | 6.34 | Brick work with non modular fly ash bricks conforming to IS:12894, class designation 10 average compressive strength in super structure above plinth level up to floor V level in : | | | | |
| 23 | 6.34.2 | Cement mortar 1:6 (1 cement : 6 Coarse sand) | cum | 69 | 8752.55 | 603925.95 |
| | 6.45 | Half brick masonry with non modular fly ash bricks of class designation 10, conforming to IS :12894, in super structure above plinth and upto floor V level | | | | |
| 24 | 6.45.2 | Cement mortar 1 : 4 (1 cement : 4 coarse sand) | Sqm | 14 | 1105.8 | 15481.2 |
| | 8.0 | CLADDING WORK | | | | |
| | 8.1S | General | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|---------|---|-----|-----|----------|-----------|
| | 8.2 | Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels | | | | |
| | 8.2.2 | Granite stone slab colour black, Cherry/Ruby red | | | | |
| 25 | 8.2.2.1 | Area of slab upto 0.50 sqm | Sqm | 86 | 5413.5 | 465561 |
| 26 | 8.2.2.2 | Area of slab over 0.50 sqm | Sqm | 47 | 5136.3 | 241406.1 |
| | 8.20S | STONE WORK DRY CLADDING | | | | |
| 27 | 8.31 | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. | Sqm | 140 | 1267.95 | 177513 |
| | 9.0 | WOOD AND P.V.C. WORK | | | | |
| | 9.1S | FRAMES AND TRUSSES | | | | |
| | 9.1 | Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length (hold fast lugs or dash fastener shall be paid for separately). | | | | |
| 28 | 9.1.1 | Second class teak wood | cum | 1.4 | 142949.7 | 200129.58 |
| 29 | 9.7.1 | Second class teak wood | Sqm | 17 | 3323.2 | 56494.4 |
| | 9.20 | Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. | | | | |
| 30 | 9.20.1 | 35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws | Sqm | 29 | 3473.85 | 100741.65 |
| | 9.40S | MISCELLANEOUS-WOOD WORK | | | | |
| | 9.48 | Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete. | | | | |
| 31 | 9.48.2 | Fixed to openings /wooden frames with rawl plugs screws etc. | Kg | 435 | 238.35 | 103682.25 |
| | 9.57S | COPER OXIDISED MILD STEEL FITTINGS (COPPER OXIDISED AS PER IS: 1378) | | | | |
| | 9.62 | Providing and fixing ISI marked oxidised M.S. sliding door bolts with nuts and screws etc. complete (Copper oxidised as per IS 1378) | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|---------|--|------|----|--------|---------|
| 32 | 9.62.2 | 250x16 mm | Each | 10 | 193.7 | 1937 |
| | 9.63 | Providing and fixing ISI marked oxidised M.S. tower bolt black finish, (Barrel type) with necessary screws etc. complete (Copper oxidised as per IS 1378) | | | | |
| 33 | 9.63.2 | 200x10 mm | Each | 2 | 69.4 | 138.8 |
| 34 | 9.63.3 | 150x10 mm | Each | 24 | 59.45 | 1426.8 |
| | 9.66 | Providing and fixing ISI marked oxidised M.S. handles conforming to IS:4992 with necessary screws etc. complete (Copper oxidised as per IS 1378) | | | | |
| 35 | 9.66.1 | 125 mm | Each | 13 | 39.95 | 519.35 |
| 36 | 9.66.3 | 75 mm | Each | 18 | 29.7 | 534.6 |
| | 9.95S | ANODISED ALUMINIUM FITTINGS (ALL FITTINGS SHALL BE ISI MARKED) | | | | |
| | 9.95 | Providing and fixing ISI marked aluminium butt hinges anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with necessary screws etc.complete: | | | | |
| 37 | 9.95.3 | 100x75x4 mm | Each | 60 | 115.4 | 6924 |
| | 9.96 | Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete : | | | | |
| 38 | 9.96.2 | 250x16 mm | Each | 30 | 260.6 | 7818 |
| | 9.97 | Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : | | | | |
| 39 | 9.97.2 | 250x10 mm | Each | 30 | 115.15 | 3454.5 |
| | 9.105S | GYPSUM BOARD PARTITIONS | | | | |
| | 9.118 | Providing and fixing to existing door frames. | | | | |
| 40 | 9.118.2 | 30 mm thick factory made Polyvinyl Chloride (PVC) door shutter made of styles and rails of a uPVC hollow section of size 60x30 mm and wall thickness 2 mm (+/- 0.2 mm), with inbuilt decorative moulding edging on one side. The styles and rails mitred and joint at the corners by means of M.S. galvanised/ plastic brackets of size 75x220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 25x20 mm and 1 mm (+/- 0.1 mm) wall thickness. The lock rail made up of 'H' section, a uPVC hollow section of size 100x30 mm and 2 mm (+/- 0.2 mm) wall thickness fixed to the shutter styles by means of plastic/ galvanised M.S. 'U' cleats. The shutter frame filled with a uPVC multi-chambered single panel of size not less than 620 mm, having over all thickness of 20 mm and 1 mm (+/- 0.1 mm) wall thickness . The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer-in-charge. | Sqm | 21 | 3253.8 | 68329.8 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|---------|--|-------|----|---------|-----------|
| 41 | 9.121 | Providing and fixing Fiber Glass Reinforced plastic (FRP) Door Frames of cross-section 90 mm x 45 mm having single rebate of 32mm x 15 mm to receive shutter of 30 mm thickness. The laminate shall be moulded with fire resistant grade unsaturated polyester resin and chopped mat. Door frame laminate shall be 2 mm thick and shall be filled with suitable wooden block in all the three legs. The frame shall be covered with fiber glass from all sides. M.S. stay shall be provided at the bottom to steady the frame. | Metre | 45 | 570.95 | 25692.75 |
| | 9.122 | Providing and fixing to existing door frames. | | | | |
| 42 | 9.122.1 | 30 mm thick Glass Fibre Reinforced Plastic (FRP) panelled door shutter of required colour and approved brand and manufacture, made with fire - retardant grade unsaturated polyester resin, moulded to 3 mm thick FRP laminate for forming hollow rails and styles, with wooden frame and suitable blocks of seasoned wood inside at required places for fixing of fittings, cast monolithically with 5 mm thick FRP laminate for panels conforming to IS: 14856, including fixing to frames. | Sqm | 27 | 3720.75 | 100460.25 |
| 43 | 9.141 | Providing and fixing PVC Door Frame of size 50x47 mm with a wall thickness of 5 mm (+/- 0.2 mm), made out of single piece extruded PVC profile, with mitred cut joints and joint with 2 nos of PVC bracket of size 190 mm x 100 mm long arms of cross section size 35 x 15 mm & self driven self tapping screws, the vertical door profiles to be reinforced with 40x20 mm M.S. rectangular tube of 0.8 mm , including providing EPDM rubber gasket weather seal throughout the frame, including jointing 5 mm PVC frame strip with PVC solvent cement on the back of the profile. The door frame to be fixed to the wall using 8 x100 mm long anchor fasteners complete, all as per manufacturer's specification and direction of Engineer -in- charge. | Metre | 45 | 573.45 | 25805.25 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|------------|---|-----|-----|----------|----------|
| | 9.147 | Providing and fixing factory made uPVC glazed/wire mesh windows/ doors comprising of lead free uPVC multi-chambered frame, sash and mullion/coupler (where ever required) extruded profiles having minimum wall thickness of 1.70 mm for Series R1 and R2 profiles and 2.10 mm for Series R3 and R4 profiles conforming to EN: 12608 in any shape, colour and design duly reinforced with galvanized mild steel section made of required shape & size as per CPWD Specification, uPVC extruded glazing beads, interlocks and Inline sash adaptor (where ever required) of appropriate dimension, EPDM gasket, hardware, SS 304 grade fasteners of minimum 8 mm dia with countersunk head, comprising of matching polyamide PA6 grade sleeve for fixing frame to finished wall as per IS 1367 : Part 1 to 14, plastic packers, plastic caps and necessary stainless steel screws etc. Profile of frame, sash & mullion (if required) shall be mitred cut and fusion welded/mechanically jointed duly sealed at all corners, including drilling of holes for fixing hardware and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealant over backer rod of approved size and quality, all complete as per approved drawing conforming to CPWD specification & direction of Engineer-in-Charge. Section of steel reinforcement and cross sections of uPVC profiles to be as per design approved by Engineer-in-Charge. Wire mesh / Glazing of plain/ toughened/ laminated/ double glass unit with / without high performance coatings as per design requirements and conforming to IS: 3548 & IS: 16231 shall be paid separately. | | | | |
| | 9.147.A4 | Three track three panels sliding window with two glazed & one wire mesh panels with Aluminium channel for roller track, wool pile, nylon rollers with SS 304 body. | | | | |
| 44 | 9.147.A4.1 | Using R2 series with frame (70 mm & above) x (40 mm & above) & both glazed and fly screen sash (25 mm & above) x (50 mm & above) with zinc alloy (zamak) powder coated touch locks with hook. (Height upto 1.2 metre). | Sqm | 5 | 10993.55 | 54967.75 |
| | 9.147.D1 | Ventilator Casement window single panel with or without fixed panel with S.S. 304 friction hinges as per size and weight of sash, single point locking zinc alloy (zamak) powder coated handles | | | | |
| 45 | 9.147.D1.3 | Using R3 series with frame (55mm & above) x (45mm & above) & sash /mullion (55mm & above) x (65mm & above). (Height above 1.2 meter) | Sqm | 4 | 11919.85 | 47679.4 |
| | 10.0 | STEEL WORK | | | | |
| | 10.1S | General | | | | |
| 46 | 10.1 | Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete. | Kg | 545 | 117.35 | 63955.75 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|---------|--|-----|-------|---------|-----------|
| 47 | 10.2 | Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete. | Kg | 1060 | 133.7 | 141722 |
| | 10.16 | Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. | | | | |
| 48 | 10.16.1 | Hot finished welded type tubes | Kg | 19615 | 194.4 | 3813156 |
| 49 | 10.19 | Providing and fixing mild steel round holding down bolts with nuts and washer plates complete. | Kg | 600 | 97.2 | 58320 |
| 50 | 10.20 | Providing and fixing bolts including nuts and washers complete. | Kg | 180 | 159.35 | 28683 |
| | 10.25 | Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. | | | | |
| 51 | 10.25.2 | In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works | Kg | 500 | 172.6 | 86300 |
| | 11.0 | FLOORING | | | | |
| | 11.1S | General | | | | |
| 52 | 11.7 | Cement concrete pavement with 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size), including finishing complete. | cum | 12 | 8595.15 | 103141.8 |
| | 11.26S | KOTA STONE FLOORING | | | | |
| | 11.26 | Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) : | | | | |
| 53 | 11.26.1 | 25 mm thick | Sqm | 381 | 1948.25 | 742283.25 |
| | 11.37S | CERAMIC GLAZED TILES | | | | |
| 54 | 11.37 | Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete. | Sqm | 153 | 1096.55 | 167772.15 |
| 55 | 11.37A | Providing and fixing 1st quality ceramic glazed floor tiles conforming to IS : 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete. | Sqm | 430 | 1112.7 | 478461 |
| | 11.41S | VITRIFIED FLOOR TILES | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|---------|---|-------|-----|---------|----------|
| | 11.41 | Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. | | | | |
| 56 | 11.41.2 | Size of Tile 600x600 mm | Sqm | 55 | 1553.45 | 85439.75 |
| | 11.55 | Providing and laying flamed finish Granite stone flooring in required design and patterns, in linear as well as curvilinear portions of the building all complete as per the architectural drawings with 18 mm thick stone slab over 20 mm (average) thick base of cement mortar 1:4 (1 cement : 4 coarse sand) laid and jointed with cement slurry and pointing with white cement slurry admixed with pigment of matching shade including rubbing, curing and polishing etc. all complete as specified and as directed by the Engineer-in-Charge : | | | | |
| 57 | 11.55.1 | Flamed finish granite stone slab Jet Black, Cherry Red, Elite Brown, Cat Eye or equivalent. | Sqm | 48 | 3186.7 | 152961.6 |
| | 12.0 | ROOFING | | | | |
| | 12.1S | SHEET ROOFING | | | | |
| | 12.1 | Providing corrugated G.S. sheet roofing including vertical / curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal/ vertical or curved surfaces), excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required. | | | | |
| 58 | 12.1.3 | 0.63 mm thick with zinc coating not less than 275 gm/ m2 | Sqm | 22 | 1087.65 | 23928.3 |
| | 12.4 | Providing ridges or hips of width 60 cm overall width plain G.S. sheet fixed with polymer coated J or L hooks, bolts and nuts 8mm dia G.I. limpet and bitumen washers complete. | | | | |
| 59 | 12.4.2 | 0.63 mm thick with zinc coating not less than 275 gm/m2 | Metre | 9 | 980.5 | 8824.5 |
| | 12.37S | RAIN WATER SPOUT AND PIPE | | | | |
| | 12.41 | Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes. | | | | |
| 60 | 12.41.1 | 75 mm diameter | Metre | 137 | 248.8 | 34085.6 |
| 61 | 12.41.2 | 110 mm diameter | Metre | 410 | 377.4 | 154734 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|-----------|--|-------|-----|---------|---------|
| | 12.42 | Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. | | | | |
| | 12.42.1 | Coupler | | | | |
| 62 | 12.42.1.1 | 75 mm | Each | 50 | 91.7 | 4585 |
| 63 | 12.42.1.2 | 110 mm | Each | 50 | 136.15 | 6807.5 |
| | 12.42.5 | Bend 87.5 degree | | | | |
| 64 | 12.42.5.1 | 75 mm bend | Each | 61 | 105.9 | 6459.9 |
| 65 | 12.42.5.2 | 110 mm bend | Each | 86 | 150.35 | 12930.1 |
| | 12.42.6 | Shoe (Plain) | | | | |
| 66 | 12.42.6.1 | 75 mm Shoe | Each | 25 | 93.1 | 2327.5 |
| 67 | 12.42.6.2 | 110 mm Shoe | Each | 61 | 131.85 | 8042.85 |
| | 12.47 | Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated 'J' or 'L' hooks, bolts & nuts 8 mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovings incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified. | | | | |
| 68 | 12.47.2 | 2 mm thick flat | Sqm | 20 | 1245.65 | 24913 |
| 69 | 12.50 | Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) of total coated thickness 0.50 mm (base metal of minimum 0.45 mm thickness with total coating thickness of 0.05 mm) with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required. | Sqm | 120 | 738.65 | 88638 |
| | 12.51 | Providing and fixing precoated galvanised steel sheet roofing accessories of total coated thickness 0.50 mm (base metal of minimum 0.45 mm thickness with total coating thickness of 0.05 mm) with Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete : | | | | |
| 70 | 12.51.1 | Ridges plain (500 - 600mm) | Metre | 80 | 532.35 | 42588 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|---------|---|-------|------|---------|-----------|
| 71 | 12.51.6 | Gutter (600 mm over all girth) | Metre | 80 | 1313.7 | 105096 |
| | 12.65 | Providing & fixing at all heights, levels and locations colour finish Aluminium alloy roofing sheets of alloy IS designation 31500, temper Hx8 conforming to IS 737 and dimensions as per IS code 2676 with characteristics of good formability and corrosion resistance. The profile sheets shall be fixed to truss members in slope or required pitch or curvature with Hex cap headed self drilling/tapping Stainless steel screws M6, 50 mm long with 3 mm EPDM seal washer etc. all inclusive of labour, scaffolding, T&P and sundries etc. complete as per directions of the Engineer-In-Charge. (Cost of truss/frame work shall be paid separately). | | | | |
| 72 | 12.65.6 | 0.91 mm Aluminium color coated profile with center to center pitch of 175 mm, depth of 46 mm, top crest width of 41 mm, bottom valley width of 80 mm, overall profile width of 1144 mm, cover width 1050 mm. | Sqm | 250 | 2335.45 | 583862.5 |
| | 13.0 | FINISHING | | | | |
| | 13.1S | CEMENT PLASTER (IN FINE SAND) | | | | |
| | 13.1 | 12 mm cement plaster of mix : | | | | |
| 73 | 13.1.2 | 1:6 (1 cement: 6 fine sand) | Sqm | 425 | 333.35 | 141673.75 |
| | 13.2 | 15 mm cement plaster on the rough side of single or half brick wall of mix : | | | | |
| 74 | 13.2.2 | 1:6 (1 cement: 6 fine sand) | Sqm | 256 | 383 | 98048 |
| | 13.11S | CEMENT PLASTER IN TWO COATS | | | | |
| 75 | 13.11 | 18 mm cement plaster in two coats under layer 12 mm thick cement plaster 1:5 (1 cement : 5 coarse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement : 6 fine sand). | Sqm | 255 | 518.55 | 132230.25 |
| 76 | 13.12 | 18 mm cement plaster in two coats under layer 12 mm thick cement plaster 1:5 (1 cement : 5 coarse sand) and a top layer 6 mm thick cement plaster 1:3 (1 cement : 3 coarse sand) finished rough with sponge. | Sqm | 342 | 537.45 | 183807.9 |
| | 13.16S | 6 mm CEMENT PLASTER | | | | |
| | 13.16 | 6 mm cement plaster of mix : | | | | |
| 77 | 13.16.1 | 1:3 (1 cement : 3 fine sand) | Sqm | 142 | 300.45 | 42663.9 |
| | 13.44S | EXTERIOR FINISHING | | | | |
| | 13.48 | Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications : | | | | |
| 78 | 13.48.1 | Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including one coat of Special primer applied @ 0.75 ltr /10 sqm | Sqm | 700 | 193.7 | 135590 |
| | 13.61 | Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : | | | | |
| 79 | 13.61.1 | Two or more coats on new work | Sqm | 1405 | 155.9 | 219039.5 |
| | 13.63 | Painting with aluminium paint of approved brand and manufacture to give an even shade . | | | | |
| 80 | 13.63.1 | Two or more coats on new work | Sqm | 1000 | 146.8 | 146800 |
| 81 | 13.80 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | Sqm | 300 | 156.05 | 46815 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|---------|--|------|------|---------|---------|
| | 13.82 | Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. | | | | |
| 82 | 13.82.2 | Two coats | Sqm | 1200 | 137.45 | 164940 |
| | 14.0 | REPAIRS TO BUILDING | | | | |
| | 14.26S | WOOD WORK | | | | |
| | 14.35 | Providing and fixing bright finished brass hard drawn hooks and eyes : | | | | |
| 83 | 14.35.4 | 150 mm | Each | 35 | 70.55 | 2469.25 |
| | 15.0 | DISMANTLING AND DEMOLISHING | | | | |
| | 15.1S | General | | | | |
| | 15.2 | Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. | | | | |
| 84 | 15.2.1 | Nominal concrete 1:3:6 or richer mix (including equivalent design mix) | cum | 104 | 2434.25 | 253162 |
| | 15.7 | Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. | | | | |
| 85 | 15.7.4 | In cement mortar | cum | 2 | 2060.2 | 4120.4 |
| | 15.23 | Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead. | | | | |
| 86 | 15.23.1 | For thickness of tiles 10 mm to 25 mm | Sqm | 200 | 73.4 | 14680 |
| 87 | 15.25 | Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 metres lead. | Sqm | 20 | 266.45 | 5329 |
| | 15.28 | Dismantling roofing including ridges, hips, valleys and gutters etc., and stacking the material within 50 metres lead of: | | | | |
| 88 | 15.28.1 | G.S. Sheet | Sqm | 4 | 164.95 | 659.8 |
| 89 | 15.60 | Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved. | cum | 8 | 263.95 | 2111.6 |
| | 16.0 | ROAD WORK | | | | |
| | 16.1S | ROADS | | | | |
| 90 | 16.1 | Preparation and consolidation of sub grade with power road roller of 8 to 12 tonne capacity after excavating earth to an average of 22.5 cm depth, dressing to camber and consolidating with road roller including making good the undulations etc. and re-rolling the sub grade and disposal of surplus earth with lead upto 50 metres. | Sqm | 40 | 218.9 | 8756 |
| | 16.3 | Supplying and stacking at site. | | | | |
| 91 | 16.3.3 | 53 mm to 22.4 mm size stone aggregate | cum | 12 | 1842.3 | 22107.6 |
| 92 | 16.3.7 | Stone screening 11.2 mm nominal size (Type B) | cum | 8 | 2247.75 | 17982 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|----|---------|--|-----|-----|----------|----------|
| 93 | 16.4 | Laying, spreading and compacting stone aggregate of specified sizes to WBM specifications in uniform thickness, hand picking, rolling with 3 wheeled road/vibratory roller 8-10 tonne capacity in stages to proper grade and camber, applying and brooming requisite type of screening / binding material to fill up interstices of coarse aggregate, watering and compacting to the required density . | cum | 40 | 1046.95 | 41878 |
| | 16.42S | CONCRETE PAVEMENTS | | | | |
| 94 | 16.42 | Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40 mm nominal size) in pavements, laid to required slope and camber in panels as required including consolidation finishing and tamping complete. | cum | 4 | 7993.8 | 31975.2 |
| | 16.43 | Providing and laying design mix cement concrete of M-30 grade, in roads/taxi tracks/ runways, using cement content as per design mix, using coarse sand and graded stone aggregate of 40 mm nominal size in appropriate proportions as per approved and specified design criteria, providing dowel bars with sleeve/ tie bars wherever required, laying at site, spreading and compacting mechanically by using needle and surface vibrators, levelling to required slope/ camber, finishing with required texture, including steel form work with sturdy M.S. channel sections, curing, making provision for contraction/ expansion, construction and longitudinal joints (10 mm wide x 50 mm deep) by groove cutting machine, providing and filling joints with approved joint filler and sealants, complete all as per direction of Engineer-in-charge (Item of joint fillers, sealants, dowel bars with sleeve/ tie bars to be paid separately). | | | | |
| 95 | 16.43.1 | Cement concrete prepared with batch mixing machine | cum | 10 | 10529.35 | 105293.5 |
| | 16.49S | MISCELLANEOUS | | | | |
| 96 | 16.79 | Providing, laying, spreading and compacting graded stone aggregate (size range 53 mm to 0.075 mm) to wet mix macadam (WMM) specification including premixing the material with water at OMC in for all leads & lifts, laying in uniform layers with mechanical paver finisher in sub- base / base course on well prepared surface and compacting with vibratory roller of 8 to 10 tonne capacity to achieve the desired density, complete as per specifications and directions of Engineer-in-Charge. | cum | 141 | 2914.3 | 410916.3 |
| | 17.0 | SANITARY INSTALLATIONS | | | | |
| | 17.1S | General | | | | |
| | 17.1 | Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231,with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required: | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|-----|-----------|---|-------|-----|---------|----------|
| 97 | 17.1.1 | White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests | Each | 6 | 6767.4 | 40604.4 |
| | 17.2 | Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required : | | | | |
| 98 | 17.2.1 | W.C. pan with ISI marked white solid plastic seat and lid | Each | 9 | 6515.55 | 58639.95 |
| | 17.4 | Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm and 340x410x265 mm sizes respectively with automatic flushing cistern with standard flush pipe and C.P. brass spreaders with brass unions and G.I clamps complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required : | | | | |
| 99 | 17.4.1 | One urinal basin with 5 litre white P.V.C. automatic flushing cistern | Each | 15 | 6258.75 | 93881.25 |
| | 17.7 | Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require: | | | | |
| 100 | 17.7.3 | White Vitreous China Wash basin size 550x400 mm with a pair of 15 mm C.P. brass pillar taps | Each | 19 | 2301.75 | 43733.25 |
| | 17.13 | Providing and fixing white vitreous china water closet squatting pan (Indian type) : | | | | |
| 101 | 17.13.2 | Orissa pattern W.C. pan of size 580x440 mm | Each | 4 | 3169.05 | 12676.2 |
| | 17.35 | Providing and fixing soil, waste and vent pipes : | | | | |
| | 17.35.2 | 75 mm diameter : | | | | |
| 102 | 17.35.2.3 | Hubless centrifugally cast (spun) iron pipes epoxy coated inside & outside IS:15905 | Metre | 210 | 964.25 | 202492.5 |
| | 17.38 | Providing and fixing bend of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete. | | | | |
| | 17.38.2 | 75 mm dia | | | | |
| 103 | 17.38.2.3 | Hubless centrifugally cast (spun) iron epoxy coated inside & outside as per IS:15905 | Each | 70 | 418.95 | 29326.5 |
| 104 | 17.81 | Providing and fixing floor mounted, white vitreous china single piece, double traps syphonic water closet of approved brand/make, shape, size and pattern including integrated white vitreous china cistern of capacity 10 litres with dual flushing system, including all fittings and fixtures with seat cover, cistern fittings, nuts, bolts and gasket etc including making connection with the existing P/S trap, complete in all respect as per directions of Engineer-in-Charge. | Each | 5 | 18212.9 | 91064.5 |
| | 18.0 | WATER SUPPLY | | | | |
| | 18.7S | C.P.V.C. PIPES | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|-----|---------|---|-----------|-------|---------|----------|
| | 18.8 | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings and fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. | | | | |
| 105 | 18.8.1 | 15 mm nominal dia Pipes | Metre | 148 | 497.8 | 73674.4 |
| 106 | 18.8.3 | 25 mm nominal dia Pipes | Metre | 116 | 627.25 | 72761 |
| | 18.9 | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings This includes jointing of pipes & fittings with one step CPVC solvent cement, trenching, refilling & testing of joints complete as per direction of Engineer in Charge. External work | | | | |
| 107 | 18.9.1 | 15 mm nominal dia Pipes | Metre | 94 | 244.7 | 23001.8 |
| 108 | 18.9.2 | 20 mm nominal dia Pipes | Metre | 190 | 274.3 | 52117 |
| 109 | 18.9.3 | 25 mm nominal dia Pipes | Metre | 292 | 355.4 | 103776.8 |
| 110 | 18.9.6 | 50 mm nominal dia Pipes | Metre | 1200 | 794.25 | 953100 |
| | 18.10 | Providing and fixing G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc. (Internal work - Exposed on wall) | | | | |
| 111 | 18.10.1 | 15 mm dia nominal bore | Metre | 14 | 366.4 | 5129.6 |
| 112 | 18.10.6 | 50 mm dia nominal bore | Metre | 51 | 1048.35 | 53465.85 |
| | 18.15S | BRASS FITTINGS | | | | |
| | 18.17 | Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) : | | | | |
| 113 | 18.17.1 | 25 mm nominal bore | Each | 34 | 622.4 | 21161.6 |
| 114 | 18.17.4 | 50 mm nominal bore | Each | 14 | 1026.65 | 14373.1 |
| | 18.31S | C.I. SLUICE VALVES/ FIRE HYDRANTS & FIXTURES | | | | |
| 115 | 18.48 | Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS : 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. | Per Litre | 14500 | 11 | 159500 |
| | 18.49S | C.P. BRASS FITTINGS | | | | |
| | 18.51 | Providing and fixing C.P. brass long body bib cock of approved quality conforming to IS standards and weighing not less than 690 gms. | | | | |
| 116 | 18.51.1 | 15 mm nominal bore | Each | 44 | 798.95 | 35153.8 |
| | 18.52 | Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. | | | | |
| 117 | 18.52.1 | 15 mm nominal bore | Each | 36 | 670.45 | 24136.2 |
| | 18.53 | Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 | | | | |
| 118 | 18.53.1 | 15mm nominal bore | Each | 32 | 574.3 | 18377.6 |
| | 18.54S | PTMT FITTINGS | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|-----|----------|--|-------|-----|--------|---------|
| | 18.54 | Providing and fixing PTMT bib cock of approved quality and colour. | | | | |
| 119 | 18.54.3 | 15 mm nominal bore, 165 mm long, weighing not less than 110 gms | Each | 30 | 176.85 | 5305.5 |
| | 19.0 | DRAINAGE | | | | |
| | 19.1S | STONE WARE PIPES AND FITTINGS | | | | |
| | 19.6 | Providing and laying non-pressure NP2 class (light duty) R.C.C. pipes with collars jointed with stiff mixture of cement mortar in the proportion of 1:2 (1 cement : 2 fine sand) including testing of joints etc. complete : | | | | |
| 120 | 19.6.2 | 150 mm dia. R.C.C. pipe | Metre | 100 | 556.45 | 55645 |
| | 21.0 | ALUMINIUM WORK | | | | |
| | 21.1S | General | | | | |
| | 21.1 | Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately) : | | | | |
| | 21.1.1 | For fixed portion | | | | |
| 121 | 21.1.1.1 | Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) | Kg | 200 | 495.05 | 99010 |
| | 21.1.2 | For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) | | | | |
| 122 | 21.1.2.1 | Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) | Kg | 200 | 598.6 | 119720 |
| | 21.3 | Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item): | | | | |
| 123 | 21.3.1 | With float glass panes of 4.0 mm thickness (weight not less than 10kg/sqm) | Sqm | 36 | 1176.8 | 42364.8 |
| | 26.0 | NEW TECHNOLOGIES AND MATERIALS | | | | |
| | 26.41S | NEW TECHNOLOGY ITEMS | | | | |
| | 26.68 | Providing and laying factory made Precast concrete solid blocks of 200 mm thickness of grade M10 made of C&D waste from approved manufacturer in foundation and plinth in: | | | | |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|-----------------|------------------------------------|---|-------------|------------|--------------|--------------------|
| 124 | 26.68.1 | Cement mortar 1:6 (1 cement : 6 coarse sand) | cum | 75 | 7387.25 | 554043.75 |
| | 26.69 | Providing and laying factory made Precast concrete solid blocks of 200 mm thickness of grade M10 made of C&D waste from approved manufacturer in superstructure above plinth level up to floor V level | | | | |
| 125 | 26.69.1 | Cement mortar 1:6 (1 cement : 6 coarse sand) | cum | 60 | 9844.65 | 590679 |
| | 26.73S | PREFAB/PRECAST TECHNOLOGY | | | | |
| | 26.86 | Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid door/window/Ceoseatory windows & other Frames/Chowkhat comprising of virgin PVC polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/ wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) fabricated with miter joints after applying PVC solvent cement and screwed with full body threaded star headed SS screws having minimum frame density of 750 kg/cum, screw withdrawal strength of 2200 N (Face) & 1100 N (Edge), minimum compressive strength of 58 N/mm ² , modulus of elasticity 900 N/mm ² and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In- Charge. (M.S hold fast/lugs or SS dash fasteners shall be paid for separately). | | | | |
| 126 | 26.86.5 | Frame size 65 x 100 mm | Metre | 72 | 1111.3 | 80013.6 |
| | 26.88 | Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid decorative type flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm ² , modulus of elasticity 850 N/mm ² and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant. WPC to be laminated with PVC foil of minimum 14 microns thick of approved design pasted with hot melt adhesive on both faces of shutter and fixing with stainless steel butt hinges of required size with necessary full body threaded star headed counter sunk S.S screws, all as per direction of Engineer-In-Charge. | | | | |
| 127 | 26.88.1 | 30 mm thick | Sqm | 81 | 4764.2 | 385900.2 |
| | | | | | Total | 33052740.49 |
| Schedule | Schedule D-NS Item of Tactile Tile | | | | | |
| Item- 04 | NS Item of Tactile Tile | | | | | |
| S No. | Item No | Description of Item | Unit | Qty | Rate | Amount |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|-----------------|-------------------------------------|---|-------------|------------|-------------|-------------------|
| 1 | 01 | Providing and laying tactiletile (for vision impairedpersons as per standards) ofsize 300x300x25mmapproved make in all coloursand shades in for outdoorfloors such as footpath, courtyard, multi modals locationetc., laid on 20mm thickbase of cement mortar 1:4(1 cement : 4 coarse sand)in all shapes & patternsincluding grouting the jointswith white cement mixedwith matching pigments etc.complete as per direction ofEngineer-in-Charge. | Sqm | 67.80 | 3391.43 | 229938.95 |
| Total | | | | | | 229938.95 |
| Schedule | Schedule E-NS Item of PLATFORM WALL | | | | | |
| Item- 05 | NS Item of PLATFORM WALL | | | | | |
| S No. | Item No | Description of Item | Unit | Qty | Rate | Amount |
| 1 | 01 | Providing, hoisting, andfixing in position M-30grade reinforced cementconcrete as per theapproved mix design inprecast standard platformwall sections as perapproved design ofrailway, including the costof cement, centering,shuttering, finishing, andadmixture in therecommended proportions(as per IS 9103) toaccelerate or retardsetting, improveworkability withoutcompromising strengthand durability, includingall leads and lifts including crossing of tracks with thecontractor's ownmaterials, labor, andequipmentetc underrunning traffic or trafficblock conditions if any,but excluding the cost ofsteel reinforcement, asper the approved plan anddirection of the Engineerin charge. Note:- 1.Minimum Cement contentshould be 400 Kg/cum 2.Extra cement up to 10%of the minimum specifiedcement content in designmix shall be payableseparately. In case thecement content in designmix is more than 1.10times of the specifiedminimum cement content,the contractor shall havediscretion to either re-design the mix or bearthe cost of extra Cement. | cum | 114.00 | 11500.00 | 1311000.00 |
| Total | | | | | | 1311000.00 |
| Schedule | Schedule F-Power NS Items | | | | | |
| Item- 06 | NS Items | | | | | |
| S No. | Item No | Description of Item | Unit | Qty | Rate | Amount |
| 1 | 01 | Wiring of light/fan/exhaust fan/common light points in concealed manner with modular accessories | Numbers | 16.00 | 408.00 | 6528.00 |
| 2 | 02 | Providing plug point, 6 Amp in concealed manner on existing board with modular accessories | Numbers | 2.00 | 97.00 | 194.00 |
| 3 | 03 | Providing plug point, 6 Amp in concealed manner on separate board with modular accessories | Numbers | 2.00 | 335.00 | 670.00 |
| 4 | 04 | Providing power plug point, 16 Amp in concealed manner on separate board with modular accessories | Numbers | 2.00 | 446.00 | 892.00 |
| 5 | 05 | Concealed wiring of sub-main with 2.5 sq. mm copper wire, single-core in PVC conduit | Metre | 50.00 | 89.00 | 4450.00 |
| 6 | 06 | Concealed wiring of sub-main with 4.0 sq. mm copper wire, single-core in PVC conduit | Metre | 30.00 | 109.00 | 3270.00 |
| 7 | 07 | Providing electronic fan regulator, modular type | Numbers | 4.00 | 279.00 | 1116.00 |
| 8 | 08 | Fixing, testing and commissioning of ceiling fan | Numbers | 4.00 | 173.00 | 692.00 |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | | | |
|---|----------------|---|-------------|------------|--------------|-----------------|
| 9 | 09 | Providing heavy duty exhaust fan, 300 mm sweep with louver/bird guard | Numbers | 2.00 | 1461.00 | 2922.00 |
| 10 | 10 | Providing MCB and starter with three-pin plug top for Air Conditioner unit | Numbers | 2.00 | 1191.00 | 2382.00 |
| 11 | 11 | Providing M.S. stand for outdoor unit of Split Air Conditioner | Numbers | 2.00 | 474.00 | 948.00 |
| 12 | 12 | Providing lighting control board with MCB DP, 32 Amp - 1 No, Time Switch, 16 Amp - 1 No and Single-Phase Contactor, 32 Amp - 1 No | Numbers | 1.00 | 4211.00 | 4211.00 |
| 13 | 13 | Providing Distribution Board with incomer MCB DP, 16/32 Amp - 1 No, RCBO, 25 Amp - 1 No and outgoing MCB SP, 6/10/16 Amp - 4 Nos | Numbers | 2.00 | 5151.00 | 10302.00 |
| 14 | 14 | Laying of cable on wall/cover shed/existing tray with MS clamp | Metre | 40.00 | 33.00 | 1320.00 |
| 15 | 15 | Providing maintenance free earthing | Numbers | 2.00 | 10594.00 | 21188.00 |
| | | | | | Total | 61085.00 |
| Schedule Schedule G-NS Items for LED | | | | | | |
| Item- 07 NS Item for LED | | | | | | |
| S No. | Item No | Description of Item | Unit | Qty | Rate | Amount |
| 1 | 01 | Providing four-feet long, 18/20 Watt LED fitting complete with all accessory and LED tube | Numbers | 10.00 | 499.00 | 4990.00 |
| | | | | | Total | 4990.00 |

4. ELIGIBILITY CONDITIONS

Special Financial Criteria

| S.No. | Description | Confirmation Required | Remarks Allowed | Documents Uploading |
|-------|---|-----------------------|-----------------|---------------------|
| 1 | Financial Eligibility Criteria:- The tenderer must have minimum average annual contractual turnover of V/N or 'V' whichever is less; where V= Advertised value of the tender in crores of Rupees N= Number of years prescribed for completion of work for which bids have been invited. The average annual contractual turnover shall be calculated as an average of "total contractual payments" in the previous three financial years, as per the audited balance sheet. However, in case balance sheet of the previous year is yet to be prepared/ audited, the audited balance sheet of the fourth previous year shall be considered for calculating average annual contractual turnover. The tenderers shall submit requisite information as per Annexure-VIB , along with copies of Audited Balance Sheets duly certified by the Chartered Accountant/ Certificate from Chartered Accountant duly supported by Audited Balance Sheet. | No | No | Allowed (Mandatory) |
| 2 | All rates are inclusive of GST and bidders should be registered in GST. | No | No | Allowed (Mandatory) |

Special Technical Criteria

| S.No. | Description | Confirmation Required | Remarks Allowed | Documents Uploading |
|-------|---|-----------------------|-----------------|---------------------|
| 1 | Technical Eligibility Criteria: (a) The tenderer must have successfully completed or substantially completed (Which should have been issued not prior to 60 days of date of invitation of present tender) any one of the following categories of work(s) during last 07 (seven) years, ending last day of month previous to the one in which tender is invited:(i) Three similar works each costing not less than the amount equal to 30% of advertised value of the tender, or (ii) Two similar works each costing not less than the amount equal to 40% of advertised value of the tender, or (iii) One similar work costing not less than the amount equal to 60% of advertised value of the tender. | No | No | Allowed (Mandatory) |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | |
|-----|---|----|----|---------------------|
| 1.1 | Note for Item 10.1: Work experience certificate from private individual shall not be considered. However, in addition to work experience certificates issued by any Govt. Organisation, work experience certificate issued by Public listed company having average annual turnover of Rs 500 crore and above in last 3 financial years excluding the current financial year, listed on National Stock Exchange or Bombay Stock Exchange, incorporated/registered at least 5 years prior to the date of closing of tender, shall also be considered provided the work experience certificate has been issued by a person authorized by the Public listed company to issue such certificates. In case tenderer submits work experience certificate issued by public listed company, the tenderer shall also submit along with work experience certificate, the relevant copy of work order, bill of quantities, bill wise details of payment received duly certified by Chartered Accountant, TDS certificates for all payments received and copy of final/last bill paid by company in support of above work experience certificate. | No | No | Not Allowed |
| 2 | Similar Nature of work:- " Any Civil Engineering Work. " | No | No | Allowed (Mandatory) |

Bidders shall confirm and certify on the behalf of the tenderer including its constituents as under:

| S.No. | Description |
|-------|--|
| 1 | I/we the tenderer (s) am/are signing this document after carefully reading the contents. |
| 2 | I/We the tenderer(s) also accept all the conditions of the tender and have signed all the pages in confirmation thereof. |
| 3 | I/we hereby declare that I/we have downloaded the tender documents from Indian Railway website www.ireps.gov.in . I/we have verified the content of the document from the website and there is no addition, no deletion or no alteration to the content of the tender document. In case of any discrepancy noticed at any stage i.e. evaluation of tenders, execution of work or final payment of the contract, the master copy available with the railway Administration shall be final and binding upon me/us. |
| 4 | I/we declare and certify that I/we have not made any misleading or false representation in the forms, statements and attachments in proof of the qualification requirements. |
| 5 | I/We also understand that my/our offer will be evaluated based on the documents/credentials submitted along with the offer and same shall be binding upon me/us. |
| 6 | I/We declare that the information and documents submitted along with the tender by me/us are correct and I/we are fully responsible for the correctness of the information and documents, submitted by us. |
| 7 | I/we certify that I/we the tenderer(s) is/are not blacklisted or debarred by Railways or any other Ministry / Department of Govt. of India from participation in tender on the date of submission of bids, either in individual capacity or as a HUF/ member of the partnership firm/LLP/JV/Society/Trust. |
| 8 | I/we understand that if the contents of the certificate submitted by us are found to be forged/false at any time during process for evaluation of tenders, it shall lead to forfeiture of the Bid Security and may also lead to any other action provided in the contract including banning of business for a period of upto two year. Further, I/we and all my/our constituents understand that my/our offer shall be summarily rejected. |
| 9 | I/we also understand that if the contents of the certificate submitted by us are found to be false/forged at any time after the award of the contract, it will lead to termination of the contract, along with forfeiture of Bid Security/Security Deposit and Performance guarantee and may also lead to any other action provided in the contract including banning of business for a period of upto two year. |
| 10 | I/We have read the clause regarding restriction on procurement from a bidder of a country which shares a land border with India and certify that I am/We are not from such a country or, if from such a country, have been registered with the competent Authority. I/We hereby certify that I/we fulfil all the requirements in this regard and am/are eligible to be considered (evidence of valid registration by the competent authority is enclosed) |

Partnership firm/Joint Venture (JV) / Hindu Undivided Family (HUF) / Limited Liability Partnership (LLP) etc.

| S.No. | Description |
|-------|---|
| 1 | Partnership firm/Joint Venture (JV) / Hindu Undivided Family (HUF) / Limited Liability Partnership (LLP) etc. Please submit a certificate in the prescribed format (please download the format from the link given below). Non submission of the certificate, or submission of certificate either not properly filled in, or in a format other than the prescribed format shall lead to summary rejection of your offer. (Click here to download the Format of Self Certification) |

5. COMPLIANCE

Commercial-Compliance

| S.No. | Description | Confirmation Required | Remarks Allowed | Documents Uploading |
|-------|-------------|-----------------------|-----------------|---------------------|
|-------|-------------|-----------------------|-----------------|---------------------|

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | |
|---|---|----|-----|--------------------|
| 1 | Please enter the percentage of local content in the material being offered. Please enter 0 for fully imported items, and 100 for fully indigenous items. The definition and calculation of local content shall be in accordance with the Make in India policy as incorporated in the tender conditions. | No | Yes | Allowed (Optional) |
|---|---|----|-----|--------------------|

Technical-Compliances

| S.No. | Description | Confirmation Required | Remarks Allowed | Documents Uploading |
|-------|--|-----------------------|-----------------|---------------------|
| 1 | The tenderer shall clearly specify whether the tender is submitted on his own (Proprietary Firm) or on behalf of a Partnership Firm / Company / Joint Venture (JV) / Registered Society / Registered Trust / HUF etc. The tenderer(s) shall enclose the attested copies of the constitution of their concern, and copy of PAN Card along with their tender. Tender Documents in such cases are to be signed by such persons as may be legally competent to sign them on behalf of the firm, company, association, trust or society, as the case may be.(Para 14.1 (see Page-17 of GCC, April-2022) & Tenderer shall submit the documents in support of their constitution of the firm as per Para 14 of GCC, April-2022 (See Page-17 to 19). | Yes | No | Allowed (Mandatory) |
| 1.1 | As per instructions please attach proforma of ANNEXURE V-A this certificate is to be given by attorney/authorized signatory/each member of partnership firm / Joint Venture (JV)/ Hindu Undivided Family (HUF) / Limited Liability Partnership (LLP) etc.) Non submission of above certificate (s) by the bidder shall result in summarily rejection of his/their bid. It shall be mandatorily incumbent up on the tenderer to identify, state and submit the supporting documents duly self-attested / digitally signed by which they/he is qualifying the Qualifying Criteria mentioned in the Tender Document. Proforma is available in uploaded documents. | No | No | Allowed (Mandatory) |
| 2 | Certificate of Information regarding Employment/Partnership etc. of Retired Railway Employees with the tender as per the attached Performa. As per clause No 16 (a) and (b) of GCC Part-I April 2022 corrected up to date. (As per Para 16 of GCC, April2022 (See Page-19 to 20). | No | No | Allowed (Mandatory) |
| 2.1 | Restrictions on the Employment of Retired Engineers of Railway Services Within One Year of their Retirement: As per Para 59.9, of GCC, April-2022 (see Page-91). | Yes | No | Allowed (Mandatory) |
| 2.2 | Certificate of NO Relative being an employee of Western Railway as per attached Performa. | No | No | Allowed (Mandatory) |
| 3 | The tenderer should upload the scan copy of EPFO and ESI registration number. However EPFO and ESI registration would be mandatory and documents towards EPFO and ESI registration must be submitted before execution of the agreement. | No | No | Allowed (Mandatory) |
| 4 | In case of Bid Security in the form of Bank Guarantee, the same should be in favor of Sr. DFM Vadodara with the tender for due performance with the stipulation to keep the offer open till such date as specified in the tender, under condition of tender. (GCC April 2022 Part I Instructions to tenderers (ITT) para 5 Bid Security (1) (a,b,c),(2) (3)(i-viii). As per ACS 2 issued vide Rly. Board letter No.2022/CEI/ CT/GCC-2022/Policy date 13.12.2022: (ii) The original Bank Guarantee should be delivered in person to the official nominated as indicated in the tender document within 5 working days before closing date for submission of bids. As pr ACS 5 RB No. 2022/CE-I/CT/GCC-2022/Policy date 20.10.2023:- Para 5(3) II The original bank guarantee should be delivered in person to the official nominated as indicated in the tender document before closing date for submission of bid.(i.e. excluding the last date of submission of bids). | No | No | Allowed (Optional) |

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

| | | | | |
|---|---|----|----|---------------------|
| 5 | The tenderer whether sole proprietor / a company or a partnership firm / joint venture (JV) / registered society / registered trust / HUF / LLP etc if they want to act through agent or individual partner(s), should submit along with the tender, a copy of power of attorney duly stamped and authenticated by a Notary Public or by Magistrate in favour of the specific person whether he/they be partner(s) of the firm or any other person, specifically authorizing him/them to sign the tender, submit the tender and further to deal with the Tender/ Contract up to the stage of signing the agreement except in case where such specific person is authorized for above purposes through a provision made in the partnership deed / Memorandum of Understanding / Article of Association /Board resolution, failing which tender shall be summarily rejected. As par Para 15 of GCC, April-2022 (see Page-19). | No | No | Allowed (Mandatory) |
| 6 | Maintenance period for the work is "06 Months" from the certified date of the completion. | No | No | Allowed (Optional) |
| 7 | Tenderer should submit Valid electrical license for electrical contract to execute electrical portion of work. | No | No | Allowed (Mandatory) |

Undertakings

| S.No. | Description | Confirmation Required | Remarks Allowed | Documents Uploading |
|-------|---|-----------------------|-----------------|---------------------|
| 1 | I/ We have visited the works site and I / We am / are aware of the site conditions. | No | No | Not Allowed |

Custom

| S.No. | Description | Confirmation Required | Remarks Allowed | Documents Uploading |
|-------|--|-----------------------|-----------------|---------------------|
| 1 | Please submit a certificate in the prescribed format for verification / confirmation of the documents submitted for compliance of eligibility / qualifying criteria. Non submission of the certificate, or submission of certificate either not properly filled in, or in a format other than the prescribed format shall lead to summary rejection of your offer. | No | No | Allowed (Mandatory) |

6. Documents attached with tender

| S.No. | Document Name | Document Description |
|-------|--|--------------------------------------|
| 1 | DRMBRC052of2026-27C.pdf | Tender Document |
| 2 | Annexure-F.pdf | JPO for Safety at Work Site |
| 3 | JPOSTDepartment.pdf | JPO ST Department |
| 4 | PCECircular88forQualityofWorks.pdf | PCE Circular 88 for Quality of Work |
| 5 | IRSGCCApril-2022.pdf | IRGCC April 2022 |
| 6 | AdvancecorrectionslipNo01to11GCCApril2022.pdf | Advance correction slip No 01 to 11 |
| 7 | ImplementationofContractore-MB.pdf | Implementation of Contractor e MB |
| 8 | Annexure-VIB.pdf | Annexure VIB of GCC April 2022 |
| 9 | compositetenderletter.pdf | composite tender letter |
| 10 | conditionofcompositetender.pdf | condition of composite tender |
| 11 | Dainikkaaryanishpaadan anumati.pdf | Dainik kaarya nishpaadan anumati |
| 12 | Recommendedmakermanufacturerofcivilmaterials.pdf | Recommended maker manufacturer Civil |
| 13 | 052SpecialCondition.pdf | Special Condition |

This tender complies with Public Procurement Policy (Make in India) Order 2017, dated 15/06/2017, issued by Department of Industrial Promotion and Policy, Ministry of Commerce, circulated vide Railway Board letter no. 2015/RS(G)/779/5 dated 03/08/2017 and 27/12/2017 and amendments/ revisions thereof.

As a Tender Inviting Authority, the undersigned has ensured that the issue of this tender does not violate provisions of GFR regarding procurement through GeM.

**VADODARA DIVISION-ENGINEERING/WESTERN RLY
TENDER DOCUMENT**

Tender No: DRM-BRC-052-OF-2026-27

Closing Date/Time: 02/07/2026 15:00

Signed By: RAKESH KUMAR ROUSHAN

Designation : Sr.DENS