

19256655

46

Revised Specification of Steel Filling Cabinet Storage

Specification	Sub-Spec	Value
	Type of Steel Filling Cabinets	Four – drawer type
	The drawer provided with	Cradle strip
	The drawer is fitted with an automatic check (to provide rebound)	Yes
	Type of drawer suspension	Ball-bearing suspension
	Drawer pull-up	With a handle
	Assembly components by	Welding
Material	Steel sheet material	Cold-reduced carbon steel conforming to CR0 grade of IS513:2016 (with the latest amendment)
	The minimum thickness of the side steel sheet	0.8mm
	The minimum thickness of the back steel sheet	0.8mm
	The minimum thickness of the top steel sheet	0.8mm
	The minimum thickness of the bottom steel sheet	0.8mm
	The minimum thickness of the filling drawer steel sheet	0.63mm
	The minimum thickness of the clutch compressor plate	1.0mm
	Cradle strips material	Painted steel
	Handle material	Corrosion- nresistant material
	Label holder material	Mild steel sheet
	Label holder material thickness (minimum)	0.63mm
Locks	Lock type	Minimum 6 levers Automatic unit type conforming to IS 729:2021(with the latest amendment)
	Locking mechanism	Minimum 1.6mm thick steel sheet
	Lock key provided with a duplicate key	Yes
	Lock key material	Non-corrosive material
Dimension	Overall height from finished floor level to top of the cabinet including pedestal (±5mm)	1380mm
	Depth from face to back (±5mm)	700mm
	Width (±5mm)	470mm
	Dimension of the label holder	100 x 50 (mm)
Color and Finish	Product colour	Grey
	The corner is to be rounded	No
	Finish with	Powder coat/coats
Warranty	Warranty period	36 months
Make	Make/Brand	Delite Kom/ Durian/ Godrej or Similar

DEE/OP&Chg./PRYJ

SSE/OP/Tech./PRYJ