

Digitally signed by  
TANAJI VISHNU SHIR  
Date: 2024.10.01 17:28:03 IST  
Reason: IREPS  
Document  
Location: IREPS-GRIS

ii. BGP Version 4

iii. Multi-Protocol BGP Version 4

The Router shall have following IP Routing features:

- i. Bidirectional Forwarding Detection (BFD) for Static and OSPF Routing.
- ii. Option to define a Router as Designated Router (DR) in OSPF Domain.
- iii. Option to define "Point to Point" and "Point to Multi-point" links in OSPF Domain.
- iv. Option to change the LSA and SPF timers as well as other timers / counters in OSPF.
- v. Router shall support tracking the reachability to remote destination which is not directly connected and thereby deciding the validity of static routes etc.

Router shall support following quality of service (QoS) features:

- i. Weighted Fair Queuing (WFQ)/Weighted Round Robin (WRR) or equivalent queuing mechanism
- ii. IP Precedence i.e. Priority based on TOS field of IPv4 and IPv6
- iii. Differentiated Services (Diff Serve) i.e. Priority based on DS field of the IPv4 and IPv6.
- iv. Weighted Random Early Detection for congestion avoidance.

The router shall have minimum eight hardware queues per port feature for assignment of bandwidth/priority to group(s) of applications.

The router shall support forwarding of traffic in load-balancing mode on links with equal metric based on Per session or Per destination-based load balancing.

The router shall support following Security features:

- i. PAP and CHAP
- ii. Data Encryption as per DES, 3DES and AES Standards
- iii. Generic Routing Encapsulation

iv. Hardware Accelerated IPsec based Point to Point secure tunnels for minimum 50 IPsec tunnels and minimum IPsec throughput of 100 kbps.

v. Access lists based on Network Address, Mask, Protocol Type and Socket Type

vi. Access list violation Logging & Accounting

vii. MD5 Route Authentication

viii. Controlled SNMP Access through the use of SNMP with MD5 Authentication.

ix. Multiple Privilege levels to provide different levels of access

x. Remote Authentication Dial in User Service (RADIUS)

The Router shall support authentication, authorization and accounting through RADIUS / TACACS+.

Router shall support Network Management through:

i. SNMP V-2 & V-3

ii. MIB I/II

iii. Router shall support all standard MIBs based on OSPF, BGP etc.

iv. Software Upgrade through FTP or TFTP

v. TELNET Client and Server

vi. SSH Version-2

Router shall support following in the user level of access i.e. the user with minimum privileges:

i. Ping

ii. Telnet

iii. Traceroute

iv. Display of pre-configured description / label on each interface.

v. Display of Input and Output error statistics on all interfaces.

vi. Display of Input and Output data rate statistics on all interfaces.