



## SIDE ELEVATION

RT-10234



7. DIMENSIONAL INSPECTION OF LINERS SHOULD BE DONE WITH THE INSPECTION GAUGE AS PER DRAWING NCROSOFT-102836
8. POLYMER COLOUR OF FINISHED LINER SHALL BE AS PER TABLE TITLED "COLOUR CODE FOR LINER" AND THE COLOUR OF XZ SHALL BE SCREEN PRINTED IN WHITE COLOUR/ LASER PRINTED WITH CHARACTERS SIZE NOT LESS THAN 3MM.
9. THE GFN LINER SHALL BE SCREEN PRINTED WITH COLOUR BANDS IN DIFFERENT COLOURS AS PER TABLE TITLED "SCHEME FOR SCREEN PRINTING FOR GFN LINER " WITH CHARACTERS SIZE 3MM APPEARING IN NATURAL COLOUR OF THE LINER. THE LOCATION OF COLOUR BAND IS SHOWN IN THE PLAN.
10. (a) G.S. STANDS FOR GAUGE SIDE OF 52KG RAIL.  
(b) N.G.S STANDS FOR NON GAUGE SIDE OF 52KG RAIL
11. ALL SHARP EDGES TO BE ROUNDED OFF TO ABOUT 2R, EXCEPT WHERE OTHERWISE MENTIONED.
12. TOLERANCES ON DIMENSIONS WHERE NOT MENTIONED, SHALL BE  $\pm 0.2\text{mm}$
13. ALL DIMENSIONS ARE IN MM.

## NOTE

**SCALE**

MILLIMETRES

10 0 10 20 30 40

REVISED & REDRAWN	DESCRIPTION
01	ALT:

USE WITH PSC SLEEPER (RT-2496) SUITABLE FOR 60Kg.(UIC)/ 60E1 & 52 Kg RAILS.	STAND NO. .... REV. ....	ADVANCE 01-07-2025	(T)
26.08.25		DATE RDSO/T- 10232 TO RDSO/T-10234	

AND SHALL NOT BE USED, COPIED, REPRODUCED IN PART OR WHOLE WITHOUT PRIOR CONSENT IN WRITING

R.D.S.O.

GFN-66/ HVN-66 INSULATING CUT  
LINER AT FISH PLATED JOINT FOR  
USE WITH PSC SLEEPER (RT-2496)  
SUITABLE FOR 60Kg.(UIC)/ 60E1 &  
52 Kg RAILS.