



0.20
start

3. P.V.C. FLEXIBLE WIRE 802020, IS: 804.
2. EYELET SHOULD BE SMOOTH ALLOVER & FINISHED CLEAN.
1. ALL DIMENSIONS ARE IN m.m.

MATERIAL FOR EYELET 'A' & 'D'
COPPER SHEET IS: 3487 (HALF HARD)
NICKEL PLATED TO IS: 1068 (1958)
GRADE 'C'.

(E)	GASKET, DRG. NO. R.D.S.O. 10924A.	1
(D)	EYELET. - 'D'	9
(C)	P.V.C. TUBE 5mm BORE x 35 (BLUE)	9
B	P.V.C. TUBE 5mm BORE x 35 (BLACK)	9
(A)	EYELET. - 'A'	9
S.N.	FOR ASSEMBLY	REQD. NO.

TRUE COPY MADE, INCORPORATING ALL ALTERATIONS UPTQ ALT. 0.

माप	पिचोक्त संख्या
SCALE	DRAWING No.
NOT TO SCALE	SW/PM/2008/9

**इनेक्ट्रिक प्वाइन्ट मशीन(रोटरी) हेतु
दमिनल वायर**

**TERMINAL WIRE USED FOR
ELECTRIC POINT MACHINE (ROTARY)**

सिगनाल कारखाना/३०३/गो.छा.	
SIGNAL WORKSHOP/NGK	
Sd. 5/4/06 A. KUMAR सोई/इडिंग S.E./DRG.	Sd. A. HENRY सोई/इडिंग SSE./DRG.

टिप्पणी तथा विनिर्दिष्ट
NOTES & SPECIFICATION

