

NAME OF WORK :- Remaining Work of Fire Fighting Network, Sump & Pump Room at PSQ Cat B-32(P+4) Units at Atkot (Including Electrification) Dist: Rajkot.

Statement showing the standard specification with Item No.& Para No. with reference to standard specification

Item No.	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
1	Providing 20 mm thick SAND FACED cement PLASTER on walls above ground level consisting 12 mm thick backing coat of C.M. 1: 3 (1 cement : 3 sand) and 8mm thick finishing coat of C.M. 1:1 (1 cement : 1 sand) etc. Complete for any height(Gutka Plaster).	127	11(17.95)	1.0 to 3.2	FOR ANY HEIGHT In The Measurement Of Interior & Exterior Plaster, Where Jambs, Soffit & Seal Granite Have Been Laid In The Window/Door, Then The Entire Area Of Window/Door Should Be Deducted In The Measurement Of Plaster For Both Side Internal & External Plaster	
2	Providing and fixing standard extruded of ALLUMINIUM SECTION of size 63mm x 38.10mm x 1.2mm (Jindal Section :20033,@Wt.0.593 kg per mt) with colour anodized alluminium frame for ventilation with 5mm thick transparent bronze colour tinted float glass as details etc complete for VENTILATION.	224-227	53[22.72]		FOR All Floor.	
3	Ceiling painting (two coats) with plastic emulsion paint on undecorated wall surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth With Applying two coats of Fine Putty & One coats of primer on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. paint, primer and putty shall be as per approved make list of GSPHCL	136	11[18.21]		Read Ceilling surface instead of Wall.	
4	Wall painting (two coats) with plastic emulsion paint on undecorated wall surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth With Applying two coats of Fine Putty One Coat of Primer on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. paint, primer and putty shall be as per approved make list of GSPHCL	136	11[18.21]	-	-	
5	Finishing wall with Weather proof exterior emulsion paint on wall surface (Two Coat) over and above applying one coat of primer to give an required shape even shade after thoroughly Brushing This surface to remove all Dirt and remains of loose powder material etc. complete. Primer shall be exterior weather coat and Paint shall be Appex Weather Emulsion Only Paint and primer shall be as per approved make list of GSPHCL	139	12[18.22]	-	-	

6	Painting Two coats (excluding priming coat) on previously painted steel and other metal surface with enamel paint, brushing, to give an even shade including cleaning the surface of all dirt, dust and other foreign matter.	142	5[19.11], 6[19.12],	-	Painting two coats	-
7	Providing & fixing to Concealed center point to wall, ceiling & floor CPVC (SDR 13.5) PIPE having National Sanitation foundation (NSF) seal for potable water of following dia nominal bore tube fitting and clamps including of making good the wall ceiling & floor etc. Complete (excavation of earth in trenches and filling will be paid separately)[C] 25 mm	157	34[23.28 (C)]	1.0-3.0	CPVC Pipes are to be used despite of UPVC. C PVC Pipes Confirming to SDR-13.5 ISI Mark only are to be provided.	
8	Providing & fixing to Concealed center point to wall, ceiling & floor CPVC (SDR 13.5) PIPE having National Sanitation foundation (NSF) seal for potable water of following dia nominal bore tube fitting and clamps including of making good the wall ceiling & floor etc. Complete (excavation of earth in trenches and filling will be paid separately)[D] 32 mm	157	34[23.28 (D)]	1.0-3.0	CPVC Pipes are to be used despite of UPVC. C PVC Pipes Confirming to SDR-13.5 ISI Mark only are to be provided.	
9	Providing and Fixing to Wall Ceilling and Floor SWR Rain Water pipe as Per IS-13592 of 90mm Dia Complete with Special flings, Compressor type Fittings, Wall clips on wooden patty including making good the ceiling and floor on terrace rain water pipe shall be 90 mm Dia. SWR horizontal pipe and vertical pipe and 90mm bend at the end near by Ground level rate are Inclusive of all Necessary Fittings G.I. Slotted Z Patti (Minium 1.6 mm thick) With Minumum 6mm Dia Etc.. required.	176	22[24.15](B)	1.0 to 2.0	Pipe shall be used 90mm Dia For Rain water pipe .	
10	Providing and fixing Gun metal check or non-return fullway wheel valve/Handle valve.(C) 25mm dia.	155	27[23.22](E)	1.0 to 3.2	Only ISI make valve shall be used joint shall be sealed by pipe sealent.	
11	Providing and fixing Gun metal check or non-return fullway wheel valve/Handle valve.(E) 40mm dia.	155	27[23.22](E)	1.0 to 3.2	Only ISI make valve shall be used joint shall be sealed by pipe sealent.	
12	Providing and fixing Gun metal check or non-return fullway wheel valve/Handle valve. 80mm dia.	As Per Attached Specification				
13	Constructing brick masnory chamber for under ground C.I.Inspection chamber and bends with Brick having crushing strength not less than 35 Kg/Sq.cm.in cement mortar 1:5,RCC top slab with 1:3:6 in cement mortar 1:5 (cover with 8 mm dia. steel @ 15 c/c and R.C.C. top slab with 1:2:4 mix (1 cement : 2 coarse sand,4- stone aggregates 20mm nominal size) foundation cocrete 1:5:10 inside laster 15 mm th. c:m 1:3 finished smooth with a floating coat of neat cement on walls & bed concrete etc. complete. Rate are also inclusive of outside plaster 15mm thick in C.M 1:3 from top of chamber and all side upto 45cm deep below ground level (I) inside dimensions 455mm x 610mm and 450mm deep for Single or multi purpose pipe line. Rate Also Inclusive RCC Frame with cover MD 10 ton (Rubber mould Finish) Inner Size 600 x 450mm with all necessary fittings	171	15[24.10(A)]	1.0 to 3.0		
14	Extra over above item for every additional depth of 0.1mtr. or part thereof beyond 450mm depth for brick masonry chamber.	172	18[24.11](i)	1.0-2.2		
15	Providing,fabricating and fixing of M.S. grill/Gate of approved pattern fabricated from M.S.flat , square bars, round bars,C-channel, box pipe as per detail Drawings.Rate is inclusive of welding with grinding smooth surface ,two coat of Oil paint and one coat of yellow Zink chromate primer coat of approved brand only.Oil paint shall be Luxol Enamel paint of Berger Paint India Ltd. or Asian paint Apcolite premium gloss Enamel of Asian paint or Dulux premium gloss enamel of Dulux paint Only M.S. grill/Gate material should be ISI Mark only.	191	18[22.37]	-	For all Floors. Oil paints of two coats and priming coat for Grill/Gate shall be done without any extra cost. The steel shall be used of ISI Mark only.	

16	Providing and fixing in position ISI marked Rotational moulded Polyethylene double layer cylindrical vertical storage tank (IS : 12701) water tank size including making inlet and outlet. Overflow and wash out arrangement with GI connection including using necessary M H for connection etc. Complete with closed cover including applying two coats of oil painting outside the tank etc complete.	160	36[23.30]		-	
17	Making of Core in RCC work of size 200 mm etc. complete RCC Core Cutting (MR)	As Per Attached Specification				
18	Providing I.S.I. mark 7 levers three keys brass pad lock of Navtal (Godrej) make 65mm dia on completion Project..	192	19[22.38]		Size shall be 65mm Instead of 75mm.	
19	Providing and Fixing 3mm thick acrylic sheet with Vinyl letter color- 2073-dark grey for back ground and color -2199-white letter with required screws...etc as per required sizes complete etc as per specification & instruction of Engineer incharge.	233-234	63[22.82]		Acrylic Name Plate made from S.S. Sinage Board (Name Plate)(18"x4.5"),For All Floor	

Signature of Contractor

I/C. Executive Engineer
Gujarat State Police Housing Corporation Ltd.
Rajkot