



## GUJARAT STATE POLICE HOUSING CORPORATION LTD., RAJKOT



**Name of Work :- Special Repair work to Barrack at Marine Task Force Commando Center at Naliya (Hothiwandh), Dist:- Kutch  
(Including Electrification)**

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
1	Removing and scraping of old deteriorated plaster of any thickness from wall / R.C.C member ... all lead and lift.	257	15[5.0]		-	
2	Dismantling tiled of stone floors laid in mortar.... all lead and lift.	257	15[1.0]		-	
3	Providing 10 mm thick cement PLASTER in single coat on ceilings .. at GROUND FLOOR.	124-125 126 126	1[17.58(1)] 5[17.59] 7[17.61]		For Ground Floor Read C.M.1:4 instead of C.M.1:3.	
4	Providing 15 mm thick cement PLASTER in single coat on brick or concrete wall .. at GROUND FLOOR.	125 126	2(17.58(2)) 5[17.59]	-	Plaster Shall Be 15 mm Thick for Ground floor. In The Measurement Of Interior & Exterior Plaster, Where Jambs, Soffit & Seal Granite Have Been Laid In The Window/Door, Then The Entire Area Of Window/Door Should Be Deducted In The Measurement Of Plaster For Both Side Internal & External Plaster.	
5	Providing 15 mm thick cement PLASTER in single coat on brick or concrete wall .. at FIRST FLOOR.	125 126	2(17.58(2)) 5[17.59]	-	Plaster Shall Be 15 mm Thick for Ground floor. In The Measurement Of Interior & Exterior Plaster, Where Jambs, Soffit & Seal Granite Have Been Laid In The Window/Door, Then The Entire Area Of Window/Door Should Be Deducted In The Measurement Of Plaster For Both Side Internal & External Plaster.	
6	Providing 20 mm thick SAND FACED cement PLASTER on walls.. etc. Complete for any height.	127	11(17.95)	-	FOR ANY HEIGHT In The Measurement Of Interior & Exterior Plaster, Where Jambs, Soffit & Seal Granite Have Been Laid In The Window/Door, Then The Entire Area Of Window/Door Should Be Deducted In The Measurement Of Plaster For Both Side Internal & External Plaster.	

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
7	Providing and fixing to wall, ceiling and floor U.PVC SWR Soil Waste Pipe with 'O' Ring 75mm dia. of ISI 13592/92. ..etc. complete and making good the Wall, Ceiling and Floor.	176	22[24.15](A)	1.0 to 2.0	Pipe shall be used 75mm Dia For Rain water pipe .	
8	Providing and fixing in position U.PVC SWR COWEL VENT to pipe 75 mm dia directed.	177	23[24.16]	-	75mm SWR cowel vent shall be used ISI mark.	
9	Providing and fixing to wall, ceiling and floor U.PVC SWR Soil Waste Pipe with 'O' Ring 110mm dia. of ISI 13592/92. .. etc. complete and making good the Wall, Ceiling and Floor.	176	22[24.15](C)	1.0 to 2.0	Pipe shall be used 110mm Dia For Rain water pipe .	
10	Providing and fixing in position U.PVC SWR COWEL VENT to pipe 110 mm dia directed.	177	23[24.16]	-	110mm SWR cowel vent shall be used ISI mark.	
11	Celling painting (two coats) with plastic emulsion paint on undecorated wall surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth With Applying two coats of Fine Putty & One coats of primer on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. paint, primer and putty shall be as per approved make list of GSPHCL	136	11[18.21]		Read Ceilling surface instead of Wall.	
12	Wall painting (two coats) with plastic emulsion paint on undecorated wall surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth With Applying two coats of Fine Putty One Coat of Primer on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. paint, primer and putty shall be as per approved make list of GSPHCLS.	136	11[18.21]	-	-	
13	Finishing wall with Weather proof exterior emulsion paint on wall surface (Two Coat) over and above applying one coat of primer to give an required shape even shade after thoroughly Brushing This surface to remove all Dirt and remains of loose powder material etc. complete. Primer shall be exterior weather coat and Paint shall be Appex Weather Emulsion Only Paint and primer shall be as per approved make list of GSPHCL	139	12[18.22]	-	-	

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
14	Providing & Laying 24" x 24" vitrified 8 mm thick tile flooring over 20mm (average) base of cement mortar 1:6 ( 1 cement: 6 coarse sand) on new surface or fixing on existing flooring by adhesive	116	8[14.6(A)]	-	-	
15	Providing & laying Printed / Coloured GLAZED TILES 8 mm thick in skirting, risers of steps and DADO on 10mm thick cement plaster 1: 3 ( 1 cement : 3 coarse sand ) & jointed with white cement slurry.(300mm x 600mm)	111	2[14.2( B)]	-	Colour, printed & Size 300 x 600mm	
16	P & L 24" x 24" Double Charge vitrified 8 to 10 mm thick tile flooring over 20 mm (average) base of cement mortar 1:6 ( 1 cement: 6 coarse sand) on new surface or fixing on existing flooring by adhesive including dismantling of existing flooring and material jointed with color cement slurry including finished with flush pointing & cleaning the surface etc.Completed Brand of the tiles shall be as per approved make list of GSPHCL. Shade & Size of tiles shall be as specified in tender item.	116	8[14.6(A)]	-	SIZE 600X600MM	
17	P & L 24" x 24" in Skirting riser of steps and dado Double Charge vitrified 8 to 10 mm thick tile over 10 mm thick Cement plaster of cement mortar 1:3 (1 cement: 3 coarse sand) jointed with color cement slurry including finished with flush pointing & cleaning the surface etc. complete Brand of the tiles shall be as per approved make list of GSPHCL. Shade & Size of tiles shall be as specified in tender item.	116	9[14.6(B)]	-	-	
18	Providing & fixing to Concealed center point to wall, ceiling & floor CPVC ( SDR 13.5 ) PIPE....[E] 40 mm	157	34[23.28 (E)]	1.0-3.0	CPVC Pipes are to be used despite of UPVC. C PVC Pipes Confirming to SDR-13.5 ISI Mark only are to be provided.	
19	Providing & fixing to Concealed center point to wall, ceiling & floor CPVC ( SDR 13.5 ) PIPE....[E] 32 mm	157	34[23.28 (D)]	1.0-3.0	CPVC Pipes are to be used despite of UPVC. C PVC Pipes Confirming to SDR-13.5 ISI Mark only are to be provided.	
20	Providing & fixing to Concealed center point to wall, ceiling & floor CPVC ( SDR 13.5 ) PIPE....[E] 20 mm	157	34[23.28 (B)]	1.0-3.0	CPVC Pipes are to be used despite of UPVC. C PVC Pipes Confirming to SDR-13.5 ISI Mark only are to be provided.	
21	Providing and fixing gun metal check or non return full way WHEEL / HANDLE VALVE 40 mm dia.	155	27[23.22](E)	1.0 to 3.2	Only ISI make valve shall be used joint shall be sealed by pipe sealent.	
22	Providing and fixing gun metal check or non return full way WHEEL / HANDLE VALVE 32 mm dia	155	27[23.22](D)	1.0 to 3.2	Only ISI make valve shall be used joint shall be sealed by pipe sealent	

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
23	Providing & Fixing 15mm One way Bib Tap .. as per the Approved Make List of GSPHCL.	154	20[23.20(A)]	1.0 TO 2.1	-	
24	Constructing brick masnory chamber for under ground C.I.Inspection chamber and bends with Brick having crushing strength not less than 35 Kg/Sq.cm.in cement mortar 1:5,RCC top slab with1:3:6 in cement mortar 1:5 ( cover with 8 mm dia. steel @ 15 c/c and R.C.C. top slab with 1:2:4 mix ( 1 cement : 2 coarse sand,4- stone aggregates 20mm nominal size) foundation cocrete 1:5:10 inside laster 15 mm th. c:m 1:3 finished smooth with a floating coat of neat cement on walls & bed concrete etc. complete. Rate are also inclusive of outside plaster 15mm thick in C.M 1:3 from top of chamber and all side upto 45cm deep below ground level (I) inside dimensions 455mm x 610mm and 450mm deep for Single or multi purpose pipe line. Rate Also Inclusive RCC Frame with cover MD 10 ton (Rubber mould Finish) Inner Size 600 x 450mm with all necessary fittings	170-171	14[24.9]	1.0 to 3.3		
25	Providing, supplying and Fixing Corrugated DWC HDPE Pipes of Class SN8 Structured Wall polyethelene Piping systems (Pipe with online/offline coupler and elastomeric sealing ring) with non-smooth External Annular Corrugated and Smooth Internal Surfaces (Double Wall) for non-pressure underground Sewerage & Drainage application as per EN:13476-3 including all local and central taxes, transportation, freight charges, octroi, inspection charges, loading, unloading, conveyance to the departmental stores etc. complete. (150mm ID Dia) Including Lowering, laying and jointing of class SN 8 structured wall ( External Annular Corrugated & Smooth Internal surface) Polyethylene Piping and fittings with the help of coupler ( on line / off line ) attached with one end of pipes, sliding over the elastomeric sealing rubber ring placed on the specified valley of the corrugation at the spigot end, lowering the same into the trench, laying on the lower bedding (constructed at bottom of trenches) at prescribed gradient,depth & alignment ,testing the water tightness of the joints, ensuring the continuity tests of specified pipe segments etc. complete as per drawing specifications & detailed engineering including carriage	173	21[24.14]	-		

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
26	Providing and fixing 24 mm thick THREE LAYER RIGID PVC PLAIN DOOR shutter with Frame .. Complete as per direction of Engineer-in-charge, manufacturer's specification & drawing.	211	49[22.68]	-	-	
27	Removing & Refixing existing door or window with frame and shutter.. including two coats of oil paint	205	40[22.59]	-	-	
28	Removing, providing and fixing <b>Bajri glass 4mm thick</b> .. as directed.	201	31[22.50]	-	-	
29	Providing & Fixing Single Hole Wash Basin with C.I or M.S. brackete & M. I . fisher union, P.V.C water pipe with Connection from Stop Cock to Pillar Tap,PVC Bottle Trap with connection 32mm dia. C.P. brassa waste coupling with Connection 32mm dia waste Pipe up to N.T etc. Complete. Rate are inclusive of all matreials, Labour & Necessary Fittings etc. Complet as per Detailed Drawings, Specifications and as per the Instruction of Engineer In charge. Materials used for the above items Must be list approved by G.S.P.H.C.L.	152	10[23.10]	1.0 to 3.2	-	
30	Provinding and fixing 600mm x 450mm bevelled edge MIRROR ... C.P. brass screws & washers.	153	17[23.17]	1.0 to 3.1	-	

---

Signature of Contractor

I/C Executive Engineer  
Gujarat State Police Housing Corporation Ltd.  
Rajkot