



GUJARAT STATE POLICE HOUSING CORPORATION LTD., RAJKOT



Name of Work : -SR Work of Door and window repairing, replacement of flooring, concertina coil over compound wall at halvad police line and door & window repairing, china mosaic at old police station and concertina coil over compound wall at New police station at Halvad (Including Electrification Work) DIST:-MORBI(Revise).

Statement showing the standard specification with Item No.& Para No. with reference to standard specification to the item description shall be as specified for in column No.3,4& 5.

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
1	Excavation for foundation upto 1.5 M. depth including sorting out and stacking of useful materials and disposing of the excavated stuff upto any lead & Lift. [A] Loose or Soft Soil	61	1[4.0.0(A)]	1.0 to 3.0	At the time of excavation, if ground water found, same shall be dewatered by Agency without any extra cost.disposing of the exccavated stuf up to any lead and lift.Rate inclusive of disposing of surplus earth from site upto any lead.	
2	Excavation for foundation upto 1.5 m depth including sorting out and stacking of useful materials and disposing off the excavated stuff upto any lead & Lift. (B) Dense or Hard soil	62	2[4.0.0(B)]	1.0 to 3.0	At the time of excavation, if ground water found, same shall be dewatered by Agency without any extra cost.disposing of the exccavated stuf up to any lead and lift.Rate inclusive of disposing of surplus earth from site upto any lead.	
3	Providing and laying Cement Concrete 1:4:8 (1cement : 4-coarse sand:8 M/C stone aggregates of 40 mm nominal size) curing complete,excluding cost of formwork in Foundation & Plinth.	71	2[5.3.3(A)]	-	Including the Cost of formwork instead of excluding cost of from work if required.	

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
4	Providing 15mm. thick cement plaster in single coat on ceiling for interior plastering and finished even and smooth in C:M 143 (1 cement;4 sand) including finishing with a floating coat of neat cement slurry AT GROUND FLOOR.	125 126	2(17.58(2)) 5[17.59]	-	Plaster Shall Be 15 mm Thick for Ground floor. In The Measurement Of Interior & Exterior Plaster, Where Jambs, Soffit & Seal Granite Have Been Laid In The Window/Door, Then The Entire Area Of Window/Door Should Be Deducted In The Measurement Of Plaster For Both Side Internal & External Plaster.	
5	Providing and laying controlled cement concrete M - 200 and finishing smooth with curing etc complete Including the Cost Of Form Work Of Plywood Only With Fair Finish And Proping Must Be Of Steel Only So As To Give A Fair Finish but excluding cost of reinforcement and Rate also inclusive of providing & mixing of plasticizer as per approved make in proportion as per mix design for R.C.C. work in COPING	81 103 104 223	19[5.8.2] 2[9.1(B)] 6[9.1(F)] 52[22.71]	1.0 to 3.20	Including cost of formwork of plywood only with fair finish and proping must be of steel only so as to give a fair finish	
6	Providing & laying TMT Steel Fe 500 reinforcement for RCC work including cutting, bending, binding & placing in position etc. complete for all floors. TMT steel shall be as per approved make list of GSPHCL	79 79	15[5.4.16] 16[5.4.17]	-	-	
7	Repairing of windows, door or cupboard shutters including removing old hinges and refixing of shutter with new hinges	200	30[22.49]	-		
8	Providing and fixing U.PVC/SWR Multi nahni trap of the following nominal dia self cleaning design with top tile and strainer including cost of cutting and making good the wall and floors 100mm inlet and 50mm outlet including 150mm x 150mm stainless steel jali.	178	26[24.19]	1.0 to 3.2	Multi NT shall be used instead of NT	

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
9	BRICK WORK using common burnt clay building brick having crushing strength not less than 35 kg/sq.cm.in foundation and plinth in cement mortar 1:6 brick with frog only shall be used.	85	1[6.13(B)]	-	-	
10	Providing & Laying Double Charge vitrified 8 to 10 mm thick tile flooring over 20 mm (average) base of cement mortar 1:6 (1 cement: 6 coarse sand) on new surface jointed with color cement slurry	116	8[14.6(A)]	-	-	
11	Providing & laying Printed / Coloured Ceramic GLAZED TILES 8 mm thick in skirting, risers of steps and DADO on 10mm thick cement plaster 1: 3 (1 cement : 3 coarse sand) & jointed with white cement slurry.	111	2[14.2(B)]	-	Colour, printed & Size 300 x 600mm	
12	Providing,fabricating and fixing of M.S. grill/Gate of approved pattern fabricated from M.S.flat , square bars, round bars,C-channel, box pipe as per detail	191	18[22.37]	-	For all Floors. Oil paints of two coats and priming coat for Grill/Gate shall be done without any extra cost. The steel shall be used of ISI Mark only.	
13	Providing and fixing solid PVC Flush Door shutter 24mm thick. made from Co-extruded three layer rigid PVC foam sheet(single Extruded) with density not less than 600kg/cbm outer layer (0.8-1mm)thick should be rigid PVC with density of not less than 1400kg/cbm.	211	49[22.68]			
14	Providing and fixing standard extruded of alluminium section of size 63.50 mm x 38.10mm x 1.01mm (Jindal section :20033,@ Wt.0.593kg/Mt) with colour anodized alluminium frame for ventilation with 5 mm thick frosted glass as fetails etc complete for ventilation.	224	53[22.72]			

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
15	Providing and fixing 4mm thick bajari glass bended in putty /wooden bedding patti with scrapping of existing putty and glass in existing windows as directed by Engineer in charge.	201	31[22.50]			
16	Providing and laying Integrated cement based proprietary water proofing treatment of required thickness over the roof incl.10mm thick waterproofing cement plaster in cement mortar 1:3 and china mosaic fitting	121	17[14.9]			
17	Providing and laying Cement Concrete 1:2:4 (1cement : 2-coarse sand:4 M/C stone aggregates of 20 mm nominal size) curing complete,including the cost of formwork in Foundation & Plinth.	71	3[5.3.4(A)]			
18	Providing & Fixing 600mm dia. loop hot dip galvenised iron concertina coil made out of 2.5mm dia wire 22mm long razor sharp barbs at 35mm center fitted on 40mm x 40mm x 5mm M.S. Angle	Attached Seprately				
19	Providing and laying Double Charge vitrified tiles 8mm to 10 mm thick in skirting , risers of steps and dado on 10 mm thick cement plaster 1:3 (1Cement : 3 Coarse Sand) & jointed with color cement slurry including finished with flush pointing & cleaning the surface etc. complete. Brand of the tiles shall be as per approved make list of GSPHCL. Shade & Size of tiles shall be as specified in tender item.	116	9[14.6(B)]	-	Antiskid size 600mmx600mm	

It. No	Description of Item	Page No.	Specification Item No.	Para No.	Amendment in para column No.5 & specification binding to the contractor.	Remarks
1	2	3	4	5	6	7
20	Wall painting (two coats) with plastic emulsion paint and manufacture on undecorated wall surface to give an even shade including thoroughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth With Applying two coats of Fine Putty One Coat of Primer and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth.paint, primer and putty shall be as per approved make list of GSPHCL.	136	11[18.21]	-	Scrap old Paint & Apply New Paint	

Signature of Contractor

I/C Executive Engineer
Gujarat State Police Housing Corporation Ltd.
Rajkot